

# HIGH TECK SEAM SEALERS.

FAST-DRYING, PAINTABLE, & FLEXIBLE –  
SUPERIOR ELASTICITY FOR ANY TEMPERATURE!



## HIT.9274-9278

### Seam Sealers

- NON-Sagging, Fast Drying
- High Rubber Content
- Paintable in 30 Minutes
- Highly Elastic
- Flexibility in Temperature Range

## HIT.9279

### High Teck Urethane Sealer

- One component, permanently flexible, polyurethane adhesive sealer.
- Excellent adhesion to painted & non-painted metals, aluminum, SMC, fiberglass, and most plastics.
- Paintable & sandable.

## HIT.9280

### Urethane Auto Glass Adhesive/Sealant

- Primerless Urethane
- Passes U.S. MVSS212 & 216 Drive Away Tests
- Average Drive away time is 2 hours
- Can be used as high strength adhesive when applying moldings and ground effects

\* On bare metal joints, one should always apply a primer first for corrosion prevention.\*

\*The best choice is High Teck 7420 series 2K HB, DTM & Sealer.\*

PART #	DESCRIPTION	UOM
HIT.9274	PROFESSIONAL SEAM SEALER (WHITE)	CART
HIT.9275	PROFESSIONAL SEAM SEALER (BLACK)	CART
HIT.9276	PROFESSIONAL SEAM SEALER (GRAY)	CART
HIT.9277	PROFESSIONAL SEAM SEALER (TAN)	CART
HIT.9278	PROFESSIONAL SEAM SEALER (CLEAR)	CART
HIT.9279	URETHANE SEALER	CART
HIT.9280	URETHANE AUTO GLASS ADHESIVE/SEALANT	CART