



# Safety Data Sheet

## HIGH TECK 7795 VOC EX SLOW

Version 1.1

Revision Date: 05/09/2023

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name** : HIGH TECK 7795 VOC EX SLOW

**Recommended use of the chemical and restrictions on use**

Recommended use : Reserved for industrial and professional use.

**Manufacturer or supplier's details**

**Company** : High Teck Products  
**Address** : PO Box 24631  
West Palm Beach, FL 33416  
USA

**Emergency telephone number:**

High Teck Products:-877-900-8325

**Additional Information:** : Regulatory Information Number: 877-900-8325  
Email: [highteck@highteck.com](mailto:highteck@highteck.com)

### SECTION 2. HAZARDS IDENTIFICATION

**GHS Classification**

Flammable liquids : Category 2  
Eye irritation : Category 2A  
Skin sensitisation : Category 1  
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

**GHS label elements**

Hazard pictograms : 

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.  
No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.



# Safety Data Sheet

## HIGH TECK 7795 VOC EX SLOW

Version 1.1

Revision Date: 05/09/2023

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P363 Wash contaminated clothing before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

CAS-No.	Chemical name	Weight percent
98-56-6	Parachlorobenzotrifluoride (PCBTF)	50 - 70
67-64-1	Acetone	30 - 50

Actual concentration is withheld as a trade secret

Any Concentration shown as a range is due to batch variation.

## SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical



## Safety Data Sheet

# HIGH TECK 7795 VOC EX SLOW

Version 1.1

Revision Date: 05/09/2023

- advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : toxic fumes  
Carbon oxides
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for : Contain spillage, and then collect with non-combustible ab-



# Safety Data Sheet

## HIGH TECK 7795 VOC EX SLOW

Version 1.1

Revision Date: 05/09/2023

containment and cleaning up : sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
67-64-1	Acetone	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA Z-1
		TWA	750 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
		STEL	1,000 ppm	OSHA P0



# Safety Data Sheet

## HIGH TECK 7795 VOC EX SLOW

Version 1.1

Revision Date: 05/09/2023

			2,400 mg/m <sup>3</sup>	
		STEL	750 ppm 1,780 mg/m <sup>3</sup>	CAL PEL
		C	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m <sup>3</sup>	CAL PEL

### Personal protective equipment

- Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection. In the case of vapour formation use a respirator with an approved filter.
- Hand protection
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid  
Colour : Clear, colorless  
Odour : characteristic  
Odour Threshold : No data available  
pH : No data available
- Freezing Point : No data available  
Boiling Point : No data available  
Flash point :  $\geq -18\text{ }^{\circ}\text{C}$  ( $-0.40\text{ }^{\circ}\text{F}$ )
- Evaporation rate : No data available  
Flammability (solid, gas) : No data available  
Upper explosion limit : No data available
- Lower explosion limit : No data available



# Safety Data Sheet

## HIGH TECK 7795 VOC EX SLOW

Version 1.1

Revision Date: 05/09/2023

Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: 1.121 @ 20 °C (68 °F) Reference substance: (water = 1)
Density	: 1.121 g/cm <sup>3</sup> @ 20 °C (68 °F) 9.3503 lb/gal @ 20 °C (68 °F)
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Amines Bases Light metals Oxidizing agents Strong acids

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Skin corrosion/irritation

**Product:**

Remarks: May cause skin irritation and/or dermatitis.

#### Serious eye damage/eye irritation

**Product:**

Remarks: May cause irreversible eye damage.

**Components:**

**67-64-1:**

Species: Rabbit  
Result: Irritating to eyes.  
Exposure time: 24 h



# Safety Data Sheet

## HIGH TECK 7795 VOC EX SLOW

Version 1.1

Revision Date: 05/09/2023

### Respiratory or skin sensitisation

**Product:**

Remarks: Causes sensitisation.

**Components:**

**98-56-6:**

Test Type: lymph node assay

Species: Mouse

Result: The product is a skin sensitiser, sub-category 1B.

### Carcinogenicity

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### STOT - single exposure

**Components:**

**67-64-1:**

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

### Further information

**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

**Components:**

**98-56-6:**

Toxicity to fish

: LC50 (Danio rerio (zebra fish)): 3 mg/l  
Exposure time: 96 h



# Safety Data Sheet

## HIGH TECK 7795 VOC EX SLOW

Version 1.1

Revision Date: 05/09/2023

Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates : IC50 (Daphnia magna (Water flea)): 2 mg/l  
Exposure time: 48 h  
Test Type: semi-static test

Acute aquatic toxicity- Assessment : Toxic to aquatic life.  
Chronic aquatic toxicity- Assessment : Toxic to aquatic life with long lasting effects.

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

## SECTION 14. TRANSPORT INFORMATION

DOT (Department of Transportation):





# Safety Data Sheet

## HIGH TECK 7795 VOC EX SLOW

Version 1.1

Revision Date: 05/09/2023

UN1993, Flammable liquids, n.o.s., (ACETONE, PARACHLOROBENZOTRIFLUORIDE (PCBTF)), 3, II

### IATA (International Air Transport Association):

UN1993, FLAMMABLE LIQUID, N.O.S., (ACETONE, PARACHLOROBENZOTRIFLUORIDE (PCBTF)), 3, II

### IMDG (International Maritime Dangerous Goods):

UN1993, FLAMMABLE LIQUID, N.O.S., (ACETONE, PARACHLOROBENZOTRIFLUORIDE (PCBTF)), 3, II,  
Flash Point:-18 °C(-0.40 °F)

**Special Notes:** : This product may be marked LTD QTY (Limited Quantity) and may be considered not regulated for transport by road and rail, due to its form, quantity, and packaging presenting a limited hazard during transportation.

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Acetone	67-64-1	5000	12500
**Benzene	71-43-2	10	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Serious eye damage or eye irritation  
Respiratory or skin sensitisation  
Specific target organ toxicity (single or repeated exposure)

**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

67-64-1 Acetone

#### Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

71-43-2 \*\*Benzene



# Safety Data Sheet

## HIGH TECK 7795 VOC EX SLOW

Version 1.1

Revision Date: 05/09/2023

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

71-43-2           \*\*Benzene

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

### Massachusetts Right To Know

67-64-1           Acetone  
71-43-2           \*\*Benzene

### Pennsylvania Right To Know

98-56-6           Parachlorobenzotrifluoride (PCBTF)  
67-64-1           Acetone

### California Prop 65

**⚠ WARNING:** This product can expose you to chemicals including Parachlorobenzotrifluoride (PCBTF), \*\*Benzene, which is/are known to the State of California to cause cancer, and \*\*Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### The components of this product are reported in the following inventories:

TSCA                               : On TSCA Inventory  
DSL                                 : All components of this product are on the Canadian DSL  
AICS                                : On the inventory, or in compliance with the inventory  
NZIoC                              : Not in compliance with the inventory  
ENCS                               : On the inventory, or in compliance with the inventory  
KECI                                : On the inventory, or in compliance with the inventory  
PICCS                              : On the inventory, or in compliance with the inventory  
IECSC                              : On the inventory, or in compliance with the inventory



# Safety Data Sheet


## HIGH TECK 7795 VOC EX SLOW

Version 1.1

Revision Date: 05/09/2023

### SECTION 16. OTHER INFORMATION

**NFPA:**



**HMIS III:**

<b>HEALTH</b>	<b>2*</b>
<b>FLAMMABILITY</b>	<b>3</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

**Revision Date** : 05/09/2023

**Material number:**

16207316, 16207369, 16207368

<b>Key or legend to abbreviations and acronyms used in the safety data sheet</b>			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value



## Safety Data Sheet

# HIGH TECK 7795 VOC EX SLOW

Version 1.1

Revision Date: 05/09/2023

IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		