

Safety Data Sheet

according to HPR, Schedule 1

Printing date 03/14/2017

Reviewed on 03/14/2017

* 1 Identification

- **Product identifier**
- **Trade name:** 77423 2.1 VOC High Solids DTM Primer/Sealer - White
- **Article number:** 77423
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
High Teck Products
PO Box 24631, West Palm Beach, FL 33416
- **Information department:**
877-900-8325
info@highteckproducts.com
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

* 2 Hazard identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids - Category 2

H225 Highly flammable liquid and vapour.



GHS07

Skin Irritation - Category 2

H315 Causes skin irritation.

Eye Irritation - Category 2A

H319 Causes serious eye irritation.

Skin Sensitizer - Category 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure -
Category 3

H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

ACETOACETATE RESIN

Talc

4-chloro-alpha,alpha,alpha-trifluorotoluene

(Contd. on page 2)

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 03/14/2017

Reviewed on 03/14/2017

Trade name: 77423 2.1 VOC High Solids DTM Primer/Sealer - White

(Contd. of page 1)

EPOXY RESIN

Fluorosurfactant

· Hazard statements*H225 Highly flammable liquid and vapour.**H315 Causes skin irritation.**H319 Causes serious eye irritation.**H317 May cause an allergic skin reaction.**H335 May cause respiratory irritation.***· Precautionary statements***P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**P241 Use explosion-proof [electrical/ventilating/lighting] equipment.**P261 Avoid breathing dust/fume/gas/mist/vapours/spray.**P280 Wear protective gloves/protective clothing/eye protection/face protection.**P240 Ground and bond container and receiving equipment.**P242 Use non-sparking tools.**P243 Take actions to prevent static discharges.**P264 Wash thoroughly after handling.**P271 Use only outdoors or in a well-ventilated area.**P272 Contaminated work clothing should not be allowed out of the workplace.**P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].**P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P321 Specific treatment (see on this label).**P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.**P312 Call a POISON CENTER/doctor if you feel unwell.**P333+P313 If skin irritation or rash occurs: Get medical advice/attention.**P337+P313 If eye irritation persists: Get medical advice/attention.**P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.**P362+P364 Take off contaminated clothing and wash it before reuse.**P405 Store locked up.**P403+P233 Store in a well-ventilated place. Keep container tightly closed.**P403+P235 Store in a well-ventilated place. Keep cool.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.***· Classification system:****· NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

(Contd. on page 3)

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 03/14/2017

Reviewed on 03/14/2017

Trade name: 77423 2.1 VOC High Solids DTM Primer/Sealer - White

(Contd. of page 2)

· **HMS-ratings (scale 0 - 4)**

HEALTH	1
FIRE	3
REACTIVITY	0

Health = 1

Fire = 3

Reactivity = 0

* 3 Composition/Information on ingredients

· **Chemical characterization: Mixtures**· **Description:**

Mixture: consisting of the following components.
Weight percentages

· **Dangerous components:**

67-64-1 acetone	10-30% w/w
7727-43-7 barium sulphate, natural	10-30% w/w
ACETOACETATE RESIN	10-30% w/w
14807-96-6 Talc	7-13% w/w
110-43-0 heptan-2-one	5-10% w/w
98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene	1-5% w/w
25036-25-3 EPOXY RESIN	1-5% w/w
Fluorosufactant	≤ 1% w/w

* 4 First aid measures

· **Description of first aid measures**· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed** No further relevant information available.· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

* 5 Firefighting measures

· **Extinguishing media**· **Suitable extinguishing agents:**CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.· **For safety reasons unsuitable extinguishing agents:** Water with full jet· **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 03/14/2017

Reviewed on 03/14/2017

Trade name: 77423 2.1 VOC High Solids DTM Primer/Sealer - White

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/ Personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
- 67-64-1 acetone**
EL Short-term value: 500 ppm
Long-term value: 250 ppm
- EV Short-term value: 750 ppm
Long-term value: 500 ppm
- 7727-43-7 barium sulphate, natural**
EL Long-term value: 10* 3** mg/m³
*total dust, **respirable fraction
- EV Long-term value: 10 mg/m³
total dust

(Contd. on page 5)

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 03/14/2017

Reviewed on 03/14/2017

Trade name: 77423 2.1 VOC High Solids DTM Primer/Sealer - White

(Contd. of page 4)

110-43-0 heptan-2-one

EL Long-term value: 50 ppm

EV Long-term value: 115 mg/m³, 25 ppm· **Additional information:** The lists that were valid during the creation were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:**

Liquid

Color:

According to product specification

(Contd. on page 6)

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 03/14/2017

Reviewed on 03/14/2017

Trade name: 77423 2.1 VOC High Solids DTM Primer/Sealer - White

(Contd. of page 5)

· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C
· Flash point:	-18 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	465 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	2.6 Vol %
Upper:	13.0 Vol %
· Vapor pressure at 20 °C:	233 hPa
· Density at 20 °C:	2.28973 g/cm ³
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	28.6 %
VOC content:	9.0 %
	209.9 g/l / 1.75 lb/gl
Solids content:	71.4 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 7)

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 03/14/2017

Reviewed on 03/14/2017

Trade name: 77423 2.1 VOC High Solids DTM Primer/Sealer - White

(Contd. of page 6)

- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**
7779-90-0 trizinc bis(orthophosphate)
 Oral LD50 >5000 mg/kg (rat)
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
 The product shows the following dangers according to internally approved calculation methods for preparations:
 Irritant
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**

13463-67-7 titanium dioxide	2B
14807-96-6 Talc	3
1330-20-7 xylene	3
7631-86-9 silicon dioxide, chemically prepared	3
- **NTP (National Toxicology Program)**
 None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

CA
(Contd. on page 8)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 03/14/2017

Reviewed on 03/14/2017

Trade name: 77423 2.1 VOC High Solids DTM Primer/Sealer - White

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

*14 Transport information

- **UN-Number**
- **DOT, TDG, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint
- **TDG** 1263 Paint, ENVIRONMENTALLY HAZARDOUS, special provision 640D
- **IMDG, IATA** PAINT
- **Transport hazard class(es)**
- **DOT**



- **Class** 3 Flammable liquids
- **Label** 3
- **TDG (Transport dangerous goods):**



- **Class** 3 Flammable liquids
- **Label** 3
- **IMDG, IATA**



- **Class** 3 Flammable liquids
- **Label** 3

(Contd. on page 9)

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 03/14/2017

Reviewed on 03/14/2017

Trade name: 77423 2.1 VOC High Solids DTM Primer/Sealer - White

(Contd. of page 8)

· Packing group	
· DOT, TDG, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special marking (TDG):	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· EMS Number:	F-E, S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· TDG	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II, ENVIRONMENTALLY HAZARDOUS

*15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):**
None of the ingredient is listed.
- **Section 313 (Specific toxic chemical listings):**
 - 7727-43-7 barium sulphate, natural
 - 14807-96-6 Talc
 - 7779-90-0 trizinc bis(orthophosphate)
 - 1314-13-2 zinc oxide
 - 1330-20-7 xylene
 - 71-36-3 butan-1-ol
- **TSCA (Toxic Substances Control Act):**
 - 13463-67-7 titanium dioxide
 - 67-64-1 acetone

(Contd. on page 10)

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 03/14/2017

Reviewed on 03/14/2017

Trade name: 77423 2.1 VOC High Solids DTM Primer/Sealer - White

(Contd. of page 9)

7727-43-7 barium sulphate, natural

14807-96-6 Talc

110-43-0 heptan-2-one

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

7779-90-0 trizinc bis(orthophosphate)

25036-25-3 EPOXY RESIN

1314-13-2 zinc oxide

1330-20-7 xylene

71-36-3 butan-1-ol

7631-86-9 silicon dioxide, chemically prepared

21645-51-2 aluminium hydroxide

· **Canadian substance listings:**· **Canadian Domestic Substances List (DSL)**

13463-67-7 titanium dioxide

67-64-1 acetone

7727-43-7 barium sulphate, natural

14807-96-6 Talc

110-43-0 heptan-2-one

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

7779-90-0 trizinc bis(orthophosphate)

25036-25-3 EPOXY RESIN

1314-13-2 zinc oxide

1330-20-7 xylene

71-36-3 butan-1-ol

7631-86-9 silicon dioxide, chemically prepared

21645-51-2 aluminium hydroxide

· **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients is listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

67-64-1 acetone

110-43-0 heptan-2-one

1314-13-2 zinc oxide

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**

GHS02



GHS07

· **Signal word Danger**

(Contd. on page 11)

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 03/14/2017

Reviewed on 03/14/2017

Trade name: 77423 2.1 VOC High Solids DTM Primer/Sealer - White

(Contd. of page 10)

- **Hazard-determining components of labeling:**

ACETOACETATE RESIN

Talc

4-chloro-alpha,alpha,alpha-trifluorotoluene

EPOXY RESIN

Fluorosurfactant

- **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P240 Ground and bond container and receiving equipment.

P242 Use non-sparking tools.

P243 Take actions to prevent static discharges.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.

- **Contact:** 877 900 8325

- **Date of preparation / last revision** 03/14/2017 / 10

- **Abbreviations and acronyms:**

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 12)

CA

Safety Data Sheet
according to HPR, Schedule 1

Printing date 03/14/2017

Reviewed on 03/14/2017

Trade name: 77423 2.1 VOC High Solids DTM Primer/Sealer - White

(Contd. of page 11)

*DOT: US Department of Transportation**IATA: International Air Transport Association**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**** Data compared to the previous version altered.**

CA