

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/13/2015

Reviewed on 08/13/2015

1 Identification

- **Product identifier**
- **Trade name:** 77425 2.1 VOC High Solids DTM Primer/Sealer - Gray
- **Article number:** 77425
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
High Teck Products
PO Box 24631, West Palm Beach, FL 33416
- **Information department:**
877-900-8325
info@highteckproducts.com
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

titanium dioxide

Talc

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/13/2015

Reviewed on 08/13/2015

Trade name: 77425 2.1 VOC High Solids DTM Primer/Sealer - Gray

(Contd. of page 1)

ACETOACETATE RESIN

acetone

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves / eye protection / face protection.

P240 Ground/bond container and receiving equipment.

P303+P361+P353 **IF ON SKIN (or hair):** Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.P305+P351+P338 **If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P304+P340 **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

* 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:**

Mixture: consisting of the following components.

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/13/2015

Reviewed on 08/13/2015

Trade name: 77425 2.1 VOC High Solids DTM Primer/Sealer - Gray

(Contd. of page 2)

Weight percentages

· Dangerous components:		
13463-67-7	titanium dioxide	13 - 30%
7727-43-7	barium sulphate, natural	13 - 30%
	ACETOACETATE RESIN	13 - 30%
14807-96-6	Talc	13 - 30%
67-64-1	acetone	10 - 13%
110-43-0	heptan-2-one	7 - 10%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	1.5 - 5%
25036-25-3	EPOXY RESIN	1.5 - 5%
1314-13-2	zinc oxide	1.5 - 5%
7631-86-9	silicon dioxide, chemically prepared	1.5 - 5%
1330-20-7	xylene	1-1.5%
	Fluorosufactant	≤1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/13/2015

Reviewed on 08/13/2015

Trade name: 77425 2.1 VOC High Solids DTM Primer/Sealer - Gray

(Contd. of page 3)

- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7727-43-7 barium sulphate, natural

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV Long-term value: 5* mg/m³
*inhalable fraction; E

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 1187 mg/m³, 500 ppm
Long-term value: 594 mg/m³, 250 ppm
BEI

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 233 mg/m³, 50 ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/13/2015

Reviewed on 08/13/2015

Trade name: 77425 2.1 VOC High Solids DTM Primer/Sealer - Gray

(Contd. of page 4)

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI

· **Ingredients with biological limit values:**

67-64-1 acetone

BEI 50 mg/L
Medium: urine
Time: end of shift
Parameter: Acetone (nonspecific)

1330-20-7 xylene

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/13/2015

Reviewed on 08/13/2015

Trade name: 77425 2.1 VOC High Solids DTM Primer/Sealer - Gray

(Contd. of page 5)

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· Form:	Liquid
· Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	55 °C

· **Flash point:** -19 °C· **Flammability (solid, gaseous):** Not applicable.· **Ignition temperature:** 465 °C· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.· **Explosion limits:**

· Lower:	2.6 Vol %
· Upper:	13.0 Vol %

· **Vapor pressure at 20 °C:** 233 hPa· **Density at 20 °C:** 1.64659 g/cm³· **Relative density** Not determined.· **Vapour density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with**· **Water:** Not miscible or difficult to mix.· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

· Dynamic:	Not determined.
· Kinematic:	Not determined.

· **Solvent content:**· **Organic solvents:** 24.1 %

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/13/2015

Reviewed on 08/13/2015

Trade name: 77425 2.1 VOC High Solids DTM Primer/Sealer - Gray

(Contd. of page 6)

VOC content: 9.5 %
207.2 g/l / 1.73 lb/gal

Solids content: 75.9 %
· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
14807-96-6	Talc	2B
7631-86-9	silicon dioxide, chemically prepared	3
1330-20-7	xylene	3
1333-86-4	Carbon black	2B
108-88-3	toluene	3
111-76-2	2-butoxyethanol	3
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

USA

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/13/2015

Reviewed on 08/13/2015

Trade name: 77425 2.1 VOC High Solids DTM Primer/Sealer - Gray

(Contd. of page 7)



12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Not known to be hazardous to water.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | |
|---|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA UN1263 |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT Paint · ADR 1263 Paint, special provision 640D · IMDG, IATA PAINT |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT <div style="text-align: center; margin: 10px 0;">  </div> <ul style="list-style-type: none"> · Class 3 Flammable liquids · Label 3 |
| <ul style="list-style-type: none"> · ADR, IMDG, IATA <div style="text-align: center; margin: 10px 0;">  </div> <ul style="list-style-type: none"> · Class 3 Flammable liquids |

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/13/2015

Reviewed on 08/13/2015

Trade name: 77425 2.1 VOC High Solids DTM Primer/Sealer - Gray

(Contd. of page 8)

· Label	3
· Packing group · DOT, ADR, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · EMS Number:	Warning: Flammable liquids F-E, S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information: · DOT · Quantity limitations · Remarks	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L ORM-D CFR49-173-150,156,306
· ADR · Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN1263, Paint, special provision 640D, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):	
None of the ingredient is listed.	
· Section 313 (Specific toxic chemical listings):	
7727-43-7	barium sulphate, natural
14807-96-6	Talc
1314-13-2	zinc oxide
1330-20-7	xylene
71-36-3	butan-1-ol
	ACRYLIC RESIN
108-88-3	toluene
111-76-2	2-butoxyethanol
100-41-4	ethylbenzene

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/13/2015

Reviewed on 08/13/2015

Trade name: 77425 2.1 VOC High Solids DTM Primer/Sealer - Gray

(Contd. of page 9)

· TSCA (Toxic Substances Control Act):	
13463-67-7	titanium dioxide
7727-43-7	barium sulphate, natural
14807-96-6	Talc
67-64-1	acetone
110-43-0	heptan-2-one
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene
25036-25-3	EPOXY RESIN
1314-13-2	zinc oxide
7631-86-9	silicon dioxide, chemically prepared
21645-51-2	aluminium hydroxide
1330-20-7	xylene
71-36-3	butan-1-ol
51274-00-1	YELLOW IRON OXIDE
1333-86-4	Carbon black
108-88-3	toluene

· Proposition 65

· Chemicals known to cause cancer:	
13463-67-7	titanium dioxide
25036-25-3	EPOXY RESIN
1330-20-7	xylene
1333-86-4	Carbon black
100-41-4	ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

108-88-3	toluene
----------	---------

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3	toluene
----------	---------

· Cancerogenity categories

· EPA (Environmental Protection Agency)		
7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
67-64-1	acetone	I
1314-13-2	zinc oxide	D, I, II
1330-20-7	xylene	I
71-36-3	butan-1-ol	D
108-88-3	toluene	II
111-76-2	2-butoxyethanol	NL
100-41-4	ethylbenzene	D

· TLV (Threshold Limit Value established by ACGIH)

13463-67-7	titanium dioxide	A4
14807-96-6	Talc	A4

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/13/2015

Reviewed on 08/13/2015

Trade name: 77425 2.1 VOC High Solids DTM Primer/Sealer - Gray

(Contd. of page 10)

67-64-1	acetone	A4
1330-20-7	xylene	A4
1333-86-4	Carbon black	A4
108-88-3	toluene	A4
111-76-2	2-butoxyethanol	A3
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

titanium dioxide

Talc

ACETOACETATE RESIN

acetone

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves / eye protection / face protection.

P240 Ground/bond container and receiving equipment.

P303+P361+P353 **IF ON SKIN (or hair):** Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 **If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P304+P340 **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/13/2015

Reviewed on 08/13/2015

Trade name: 77425 2.1 VOC High Solids DTM Primer/Sealer - Gray

(Contd. of page 11)

P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** 877 900 8325

· **Date of preparation / last revision** 08/13/2015 / 6

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

· *** Data compared to the previous version altered.**

USA