



HIGH TECK™

SAFETY DATA SHEETS

ISOPROPYL ALCOHOL 99%

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: Isopropyl Alcohol 99%

Product Name: Isopropyl Alcohol 99%

Revision Date: Feb 13, 2020 **Date Printed:** Feb 13, 2020

Version: 1.2 **Supersedes Date:** May 09, 2015

Manufacturer's Name: HIGH TECK PRODUCTS
PO BOX 24631
WEST PALM BEACH
33416 - USA

Address: T 877-900-8325
info@nationaloak.com

Emergency Phone: CHEMTREC US : 1-800-424-9300, INTERNATIONAL CALLS : 1-703-527-3887

Information Phone Number:

Fax:

Product/Recommended Uses: Industrial solvent

SECTION 2) HAZARDS IDENTIFICATION

Classification

Eye Irritation - Category 2A

Flammable Liquids - Category 2

Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) - Category 3

Pictograms



Signal Word

Danger

Hazardous Statements - Physical

Highly flammable liquid and vapor

Hazardous Statements - Health

Causes serious eye irritation

May cause drowsiness or dizziness

Precautionary Statements - General

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Precautionary Statements - Prevention

Wash with soap and water thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.



Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Take action to prevent static discharges.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse with water or shower.
In case of fire: Use DRY chemical, alcohol- resistant foam, water spray/fog or carbon-dioxide to extinguish.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool.
Store locked up.

Precautionary Statements - Disposal

Dispose of contents/container to disposal recycling center.
Waste management should be in full compliance with federal, state and local laws.

SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0000067-63-0	ISOPROPYL ALCOHOL	80.0% - 100.0%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES**Inhalation**

Remove source of exposure or move person to fresh air and keep comfortable for breathing. If victim is not breathing, call 911 and administer CPR as directed.
Eliminate all ignition sources if safe to do so.

Skin Contact

Rinse/wash with lukewarm, gently flowing water (and mild soap) for 15-20 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention.

Eye Contact

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing. Take care not to rinse contaminated water into the unaffected eye or onto the face. Get immediate medical attention.

Ingestion

Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position. Immediately call 911 POISON CENTER/doctor/. Immediately transport to the nearest medical facility for treatment.

SECTION 5) FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Dry chemical, foam, carbon dioxide or fog is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only.

Unsuitable Extinguishing Media



No data available.

Specific Hazards in Case of Fire

No data available.

Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

RELEASE CAN CAUSE FIRE/EXPLOSION. LIQUIDS/VAPORS MAY IGNITE.

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Recommended Equipment

Positive pressure, full-facepiece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Use explosive proof equipment. Avoid inhalation of dust and contact with skin and eyes. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning up

Sand, clay and absorbent socks can be used to contain a spill.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous.

Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

Ground and bond containers and receiving equipment. Avoid static electricity by grounding.

Electrostatic charges may be generated during pumping. Keep away from aerosols, flammables, oxidizing agents, corrosives and from



other flammable products.

SECTION 8) EXPOSURE CONTROLS, PERSONAL PROTECTION

Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Eye Protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)
ISOPROPYL ALCOHOL	400	980			1			400

Chemical Name	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
ISOPROPYL ALCOHOL	980	500	1225		200		400	

Chemical Name	ACGIH Carcinogen	ACGIH Notations	ACGIH TLV Basis
ISOPROPYL ALCOHOL	A4	A4; BEI	Eye & URT irr; CNS impair

(C) - Ceiling limit, A4 - Not Classifiable as a Human Carcinogen, BEI - Substances for which there is a Biological Exposure Index or Indices, CNS - Central nervous system, impair - Impairment, irr - Irritation, URT - Upper respiratory tract

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Specific Gravity

Density

% VOC

Density VOC

% Solids By Weight

Appearance

Clear liquid

Odor Threshold

N/A

Odor Description

Characteristic

pH

N/A

Water Solubility

N/A



HIGH TECK™

SAFETY DATA SHEETS

ISOPROPYL ALCOHOL 99%

Flammability	Flash point below 73°F/23°C
Flash Point Symbol	F
Flash Point	57 °F
Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Pressure	N/A
Vapor Density	N/A
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	N/A
High Boiling Point	N/A
Auto Ignition Temp	750 °F
Decomposition Pt	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A
VOC Composite Partial Pressure	30.9376 mmHg

SECTION 10) STABILITY AND REACTIVITY

Stability

Stable under normal conditions of use.

Conditions to Avoid

Avoid heat, sparks, open flames and other ignition sources.

Hazardous Reactions/Polymerization

No data available.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

SECTION 11) TOXICOLOGICAL INFORMATION

Acute toxicity

Ingestion: May be harmful or fatal if swallowed.

0000067-63-0 ISOPROPYL ALCOHOL

If ingested causes drunkenness and vomiting. Inhalation can irritate the nose and throat.

LC50 (Rat, Inhalation) = 16,000 ppm/8H Reference : Registry of Toxic Effects of Chemical Substances If ingested causes drunkenness and vomiting. Inhalation can irritate the nose and throat.

LC50 (Rat, Inhalation) = 16,000 ppm/8H Reference : Registry of Toxic Effects of Chemical Substances If ingested causes drunkenness and vomiting. Inhalation can irritate the nose and throat.

Skin Corrosion/Irritation

0000067-63-0 ISOPROPYL ALCOHOL

Contact can irritate and burn the skin. Prolonged or repeated contact can cause a skin rash, itching, dryness and redness.

Serious eye damage/irritation

Causes serious eye irritation

0000067-63-0 ISOPROPYL ALCOHOL

Liquid irritates eyes and may cause injury.

Germ cell mutagenicity



HIGH TECK™

SAFETY DATA SHEETS

ISOPROPYL ALCOHOL 99%

No data available.

Carcinogenicity

No data available.

Respiratory/Skin Sensitization

Slightly irritating to respiratory system.

No data available.

Reproductive toxicity

No data available.

Specific Target Organ Toxicity - Repeated Exposure

0000067-63-0 ISOPROPYL ALCOHOL

Repeated high exposure can cause headache, dizziness, confusion, loss of coordination, unconsciousness and even death.

Aspiration hazard

No data available.

Specific Target Organ Toxicity - Single Exposure

May cause drowsiness or dizziness

0000067-63-0 ISOPROPYL ALCOHOL

Vapors cause mild irritation of upper respiratory tract; high concentrations may be anesthetic.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

0000067-63-0 ISOPROPYL ALCOHOL

The substance can be absorbed into the body by inhalation of its vapour.

Potential Health Effects - Miscellaneous

0000067-63-0 ISOPROPYL ALCOHOL

The following medical conditions may be aggravated by exposure: dermatitis, respiratory disease. Developmental toxicity was seen in rat's offspring at doses that were maternally toxic. Contact will cause moderate to severe redness and swelling, itching, tingling sensation, painful burning. May cause injury to the cornea of the eyes. Prolonged or repeated exposure may cause damage to any of the following organs/systems: liver. Ingestion studies on laboratory animals showed that very high oral doses caused increased liver and kidney weights.

0000067-63-0 ISOPROPYL ALCOHOL

LC50 (rat): 17000 ppm (4-hour exposure); cited as 12000 ppm (8-hour exposure) (18)

LD50 (oral, male rat): 4710 mg/kg (cited as 6.0 mL/kg) (19)

LD50 (oral, mouse): 3600 mg/kg (20, unconfirmed)

LD50 (dermal, rabbit): 12870 mg/kg (cited as 16.4 mL/kg) (14)

SECTION 12) ECOLOGICAL INFORMATION

Bio-accumulative Potential

0000067-63-0 ISOPROPYL ALCOHOL

Substance is not expected to bioaccumulate.

Persistence and Degradability

0000067-63-0 ISOPROPYL ALCOHOL

Readily biodegradable

Mobility in Soil

No data available.

Toxicity

No data available.

Other adverse effects

No data available.



HIGH TECK™

SAFETY DATA SHEETS

ISOPROPYL ALCOHOL 99%

Results of the PBT and vPvB assessment

0000067-63-0 ISOPROPYL ALCOHOL

Substance is readily biodegradable and therefore not considered to be persistent. It is not expected to bioaccumulate as it has a Log Kow < 4.5 and aquatic acute toxicity greatly exceeds the screening criteria of EC50 < 0.1 mg/l.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal Method

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

U.S. DOT Information

UN1219, Isopropanol, 3, PG II

Emergency Response Guide (ERG)

Emergency Response Guide 129

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0000067-63-0	ISOPROPYL ALCOHOL	80.0% - 100.0%	SARA313, SARA312,VOC,IARCCarcinogen,TS CA,OSHA

SECTION 16) OTHER INFORMATION

General

A.G. Layne, Inc. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. It is the Buyer's/User's responsibility to ensure that his activities comply with all Federal, State, Provincial or Local laws. The information presented here pertains only to the product as shipped. The information contained herein is based on our current knowledge of the underlying data and is intended to describe the product for the purpose of health, safety and environmental requirements only. NO warranty or guarantee is expressed or implied regarding the accuracy of this data or the results to be obtained from the use of the product.

HMIS

Health	/	
FLAMMABILITY		
Physical Hazard		
Personal Protection	H	

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks



HIGH TECK™

SAFETY DATA SHEETS

ISOPROPYL ALCOHOL 99%

Version 1.2:

Revision Date: Feb 13, 2020

Revisions Sections 2 and 16

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither A. G. Layne, Inc. nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.