



# SAFETY DATA SHEET

## 1. Identification

<b>Product identifier</b>	<b>H.S. ACRYLIC LACQUER PRIMER SU</b>		
<b>Other means of identification</b>			
<b>Product Code</b>	HT-7350-1		
<b>Recommended use</b>	Automotive Refinish Primer		
<b>Manufacturer/Importer/Supplier/Distributor information</b>			
<b>Manufacturer</b>			
<b>Company name</b>	High Teck Products		
<b>Address</b>	P. O. Box 24631 West Palm Beach, FL 33416 United States		
<b>Telephone</b>	General Assistance	877-900-8235	
<b>E-mail</b>	info@highteckproducts.com		
<b>Contact person</b>	SDS Coordinator		
<b>Emergency phone number</b>	CHEMTREC	800-424-9300	

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 1
<b>Health hazards</b>	Acute toxicity, oral	Category 4
	Acute toxicity, inhalation	Category 3
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
	Germ cell mutagenicity	Category 2
	Carcinogenicity	Category 2
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 3
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



**Signal word**

Danger

**Hazard statement**

Extremely flammable liquid and vapor. Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing genetic defects. Suspected of causing cancer. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

### Response

If swallowed: Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor. Rinse mouth. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

### Storage

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Hazard(s) not otherwise classified (HNOC)

None known.

### Supplemental information

47.78% of the mixture consists of component(s) of unknown acute oral toxicity. 67.72% of the mixture consists of component(s) of unknown acute inhalation toxicity. 62.36% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 62.36% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
4-Methyl-2-pentanone		108-10-1	10 to <20
acetone		67-64-1	10 to <20
Talc		14807-96-6	10 to <20
Toluene		108-88-3	10 to <20
Nitrocellulose		9004-70-0	5 to <10
2-butanone		78-93-3	1 to <5
isopropanol		67-63-0	1 to <5
Magnesium carbonate		546-93-0	1 to <5
Titanium dioxide		13463-67-7	1 to <5
Xylene		1330-20-7	1 to <5
Carbon Black		1333-86-4	0.1 to <1
Ethyl benzene		100-41-4	0.1 to <1
Other components below reportable levels			10 to <20

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.

### Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

### Ingestion

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

<b>Most important symptoms/effects, acute and delayed</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Extremely flammable liquid and vapor.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.  Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water.  Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
--------------------------------------	---

**Conditions for safe storage, including any incompatibilities**

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

**8. Exposure controls/personal protection****Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
2-butanone (CAS 78-93-3)	PEL	590 mg/m3 200 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	PEL	410 mg/m3	
acetone (CAS 67-64-1)	PEL	100 ppm 2400 mg/m3	
Carbon Black (CAS 1333-86-4)	PEL	1000 ppm 3.5 mg/m3	
Ethyl benzene (CAS 100-41-4)	PEL	435 mg/m3	
isopropanol (CAS 67-63-0)	PEL	100 ppm 980 mg/m3	
Magnesium carbonate (CAS 546-93-0)	PEL	400 ppm 5 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
Xylene (CAS 1330-20-7)	PEL	15 mg/m3	Total dust.
		435 mg/m3 100 ppm	

**US. OSHA Table Z-2 (29 CFR 1910.1000)**

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

Components	Type	Value	Form
Talc (CAS 14807-96-6)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
2-butanone (CAS 78-93-3)	STEL	300 ppm	
	TWA	200 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	75 ppm	
	TWA	20 ppm	
acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Ethyl benzene (CAS 100-41-4)	TWA	20 ppm	
isopropanol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Toluene (CAS 108-88-3)	TWA	20 ppm	

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
2-butanone (CAS 78-93-3)	STEL	885 mg/m3 300 ppm	
	TWA	590 mg/m3 200 ppm	
4-Methyl-2-pentanone (CAS 108-10-1)	STEL	300 mg/m3	
	TWA	75 ppm 205 mg/m3 50 ppm	
acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm	
Carbon Black (CAS 1333-86-4)	TWA	0.1 mg/m3	
Ethyl benzene (CAS 100-41-4)	STEL	545 mg/m3	
	TWA	125 ppm 435 mg/m3 100 ppm	
isopropanol (CAS 67-63-0)	STEL	1225 mg/m3 500 ppm	
	TWA	980 mg/m3 400 ppm	
Magnesium carbonate (CAS 546-93-0)	TWA	5 mg/m3	Respirable.
Talc (CAS 14807-96-6)	TWA	10 mg/m3	Total
Toluene (CAS 108-88-3)	TWA	2 mg/m3	Respirable.
	STEL	560 mg/m3 150 ppm	
	TWA	375 mg/m3 100 ppm	

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
2-butanone (CAS 78-93-3)	2 mg/l	MEK	Urine	*
4-Methyl-2-pentanone (CAS 108-10-1)	1 mg/l	Methyl isobutyl ketone	Urine	*
acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Ethyl benzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
isopropanol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines****US - California OELs: Skin designation**

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

## US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3)

Skin designation applies.

**Appropriate engineering controls** Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

#### Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**Other** Wear appropriate chemical resistant clothing.

**Respiratory protection** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations** When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

### Appearance

**Physical state** Liquid.

**Form** Liquid.

**Color** Grey.

**Odor** Solvent.

**Odor threshold** Not available.

**pH** Not available.

**Melting point/freezing point** -138.82 °F (-94.9 °C) estimated

**Initial boiling point and boiling range** 93.2 °F (34 °C) estimated

**Flash point** -4.0 °F (-20.0 °C) estimated

**Evaporation rate** Not available.

**Flammability (solid, gas)** Not applicable.

### Upper/lower flammability or explosive limits

**Flammability limit - lower (%)** 1.3 % estimated

**Flammability limit - upper (%)** 12.8 % estimated

**Explosive limit - lower (%)** Not available.

**Explosive limit - upper (%)** Not available.

**Vapor pressure** 83.33 hPa estimated

**Vapor density** Not available.

**Relative density** Not available.

### Solubility(ies)

**Solubility (water)** Not available.

**Partition coefficient (n-octanol/water)** Not available.

**Auto-ignition temperature** 338 °F (170 °C) estimated

**Decomposition temperature** Not available.

**Viscosity** Not available.

## Other information

Density	9.42 lb/gal
Flammability class	Flammable IA estimated
Percent volatile	52.44 %
Specific gravity	1.13
VOC	3.6 lb/gal Material 4.5 lb/gal Regulatory 429 g/l Material 542 g/l Regulatory

## 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens.
Hazardous decomposition products	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

Inhalation	Toxic if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Harmful if swallowed.

**Symptoms related to the physical, chemical and toxicological characteristics** Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

### Information on toxicological effects

**Acute toxicity** Toxic if inhaled. Harmful if swallowed. Narcotic effects. May cause an allergic skin reaction. May cause respiratory irritation.

Components	Species	Test Results
2-butanone (CAS 78-93-3)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 8000 mg/kg
<b>Inhalation</b>		
LC50	Mouse	11000 ppm, 45 Minutes
	Rat	11700 ppm, 4 Hours
<b>Oral</b>		
LD50	Mouse	670 mg/kg
	Rat	2300 - 3500 mg/kg
4-Methyl-2-pentanone (CAS 108-10-1)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 16000 mg/kg
<b>Inhalation</b>		
LC50	Rat	8.2 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	2080 mg/kg

Components	Species	Test Results
acetone (CAS 67-64-1)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	20000 mg/kg 20 ml/kg
<b>Inhalation</b>		
LC50	Rat	76 mg/l, 4 Hours 50.1 mg/l, 8 Hours
<b>Oral</b>		
LD50	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
Carbon Black (CAS 1333-86-4)		
<b><u>Acute</u></b>		
<b>Oral</b>		
LD50	Rat	> 8000 mg/kg
Ethyl benzene (CAS 100-41-4)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	17800 mg/kg
<b>Oral</b>		
LD50	Rat	3500 mg/kg
isopropanol (CAS 67-63-0)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	12800 mg/kg
<b>Oral</b>		
LD50	Mouse	3600 mg/kg
	Rabbit	5.03 g/kg
	Rat	4.7 g/kg
Toluene (CAS 108-88-3)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	12124 mg/kg 14.1 ml/kg
<b>Inhalation</b>		
LC50	Mouse	5320 ppm, 8 Hours 400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours
<b>Oral</b>		
LD50	Rat	2.6 g/kg
Xylene (CAS 1330-20-7)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	> 43 g/kg
<b>Inhalation</b>		
LC50	Mouse	3907 mg/l, 6 Hours



Components	Species	Test Results
	Rat	6350 mg/l, 4 Hours
<b>Oral</b>		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	May cause an allergic skin reaction.
<b>Germ cell mutagenicity</b>	Suspected of causing genetic defects.
<b>Carcinogenicity</b>	Suspected of causing cancer.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
4-Methyl-2-pentanone (CAS 108-10-1)	2B Possibly carcinogenic to humans.
Carbon Black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
Ethyl benzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	
Not listed.	
<b>Reproductive toxicity</b>	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.
<b>Specific target organ toxicity - single exposure</b>	May cause respiratory irritation. May cause drowsiness and dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Not an aspiration hazard.
<b>Chronic effects</b>	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

Components	Species	Test Results
Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.		
2-butanone (CAS 78-93-3)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna) 4025 - 6440 mg/l, 48 hours
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus) > 400 mg/l, 96 hours
4-Methyl-2-pentanone (CAS 108-10-1)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow (Pimephales promelas) 492 - 593 mg/l, 96 hours
acetone (CAS 67-64-1)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna) 21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 4740 - 6330 mg/l, 96 hours
Ethyl benzene (CAS 100-41-4)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna) 1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 7.5 - 11 mg/l, 96 hours

Components	Species	Test Results
isopropanol (CAS 67-63-0)		
<b>Aquatic</b>		
Fish	LC50	Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours
Titanium dioxide (CAS 13463-67-7)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna) > 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours
Toluene (CAS 108-88-3)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna) 5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch) 8.11 mg/l, 96 hours
Xylene (CAS 1330-20-7)		
<b>Aquatic</b>		
Fish	LC50	Bluegill (Lepomis macrochirus) 7.711 - 9.591 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

2-butanone	0.29
4-Methyl-2-pentanone	1.31
acetone	-0.24
Ethyl benzene	3.15
isopropanol	0.05
Toluene	2.73
Xylene	3.12 - 3.2

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal considerations**

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. Transport information**

**DOT**

<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint, Paint Related Material
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	I
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	T11, TP1, TP27

Packaging exceptions 150  
Packaging non bulk 201  
Packaging bulk 243

**IATA**

UN number UN1263  
UN proper shipping name Paint, Paint Related Material  
Transport hazard class(es)  
Class 3  
Subsidiary risk -  
Packing group I  
Environmental hazards No.  
ERG Code 3H  
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.  
Other information  
Passenger and cargo aircraft Allowed.  
Cargo aircraft only Allowed.

**IMDG**

UN number UN1263  
UN proper shipping name Paint, Paint Related Material  
Transport hazard class(es)  
Class 3  
Subsidiary risk -  
Packing group I  
Environmental hazards  
Marine pollutant No.  
EmS F-E, S-E  
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

**DOT**



**IATA; IMDG**



**15. Regulatory information**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**  
Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

2-butanone (CAS 78-93-3)	Listed.
4-Methyl-2-pentanone (CAS 108-10-1)	Listed.
acetone (CAS 67-64-1)	Listed.
Ethyl benzene (CAS 100-41-4)	Listed.
isopropanol (CAS 67-63-0)	Listed.
Nitrocellulose (CAS 9004-70-0)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

<b>Hazard categories</b>	Immediate Hazard - Yes
	Delayed Hazard - Yes
	Fire Hazard - Yes
	Pressure Hazard - No
	Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** No**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
4-Methyl-2-pentanone	108-10-1	10 to <20
Toluene	108-88-3	10 to <20
isopropanol	67-63-0	1 to <5
Xylene	1330-20-7	1 to <5
Ethyl benzene	100-41-4	0.1 to <1

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

4-Methyl-2-pentanone (CAS 108-10-1)  
 Ethyl benzene (CAS 100-41-4)  
 Toluene (CAS 108-88-3)  
 Xylene (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

2-butanone (CAS 78-93-3)	6714
4-Methyl-2-pentanone (CAS 108-10-1)	6715
acetone (CAS 67-64-1)	6532
Toluene (CAS 108-88-3)	6594

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

2-butanone (CAS 78-93-3)	35 %WV
4-Methyl-2-pentanone (CAS 108-10-1)	35 %WV
acetone (CAS 67-64-1)	35 %WV
Toluene (CAS 108-88-3)	35 %WV

**DEA Exempt Chemical Mixtures Code Number**

2-butanone (CAS 78-93-3)	6714
4-Methyl-2-pentanone (CAS 108-10-1)	6715
acetone (CAS 67-64-1)	6532
Toluene (CAS 108-88-3)	594

**US state regulations****US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.**

**(a)**

2-butanone (CAS 78-93-3)  
4-Methyl-2-pentanone (CAS 108-10-1)  
acetone (CAS 67-64-1)  
Carbon Black (CAS 1333-86-4)  
Ethyl benzene (CAS 100-41-4)  
isopropanol (CAS 67-63-0)  
Talc (CAS 14807-96-6)  
Titanium dioxide (CAS 13463-67-7)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

**US. Massachusetts RTK - Substance List**

2-butanone (CAS 78-93-3)  
4-Methyl-2-pentanone (CAS 108-10-1)  
acetone (CAS 67-64-1)  
Carbon Black (CAS 1333-86-4)  
Ethyl benzene (CAS 100-41-4)  
isopropanol (CAS 67-63-0)  
Magnesium carbonate (CAS 546-93-0)  
Nitrocellulose (CAS 9004-70-0)  
Talc (CAS 14807-96-6)  
Titanium dioxide (CAS 13463-67-7)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

**US. New Jersey Worker and Community Right-to-Know Act**

2-butanone (CAS 78-93-3)  
4-Methyl-2-pentanone (CAS 108-10-1)  
acetone (CAS 67-64-1)  
Carbon Black (CAS 1333-86-4)  
Ethyl benzene (CAS 100-41-4)  
isopropanol (CAS 67-63-0)  
Magnesium carbonate (CAS 546-93-0)  
Nitrocellulose (CAS 9004-70-0)  
Talc (CAS 14807-96-6)  
Titanium dioxide (CAS 13463-67-7)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

**US. Pennsylvania Worker and Community Right-to-Know Law**

2-butanone (CAS 78-93-3)  
4-Methyl-2-pentanone (CAS 108-10-1)  
acetone (CAS 67-64-1)  
Carbon Black (CAS 1333-86-4)  
Ethyl benzene (CAS 100-41-4)  
isopropanol (CAS 67-63-0)  
Nitrocellulose (CAS 9004-70-0)  
Talc (CAS 14807-96-6)  
Titanium dioxide (CAS 13463-67-7)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

**US. Rhode Island RTK**

2-butanone (CAS 78-93-3)  
4-Methyl-2-pentanone (CAS 108-10-1)  
acetone (CAS 67-64-1)  
Ethyl benzene (CAS 100-41-4)  
isopropanol (CAS 67-63-0)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

4-Methyl-2-pentanone (CAS 108-10-1) Listed: November 4, 2011

benzene (CAS 71-43-2)	Listed: February 27, 1987
Carbon Black (CAS 1333-86-4)	Listed: February 21, 2003
Cumene (CAS 98-82-8)	Listed: April 6, 2010
dioxane (CAS 123-91-1)	Listed: January 1, 1988
Ethanol (CAS 64-17-5)	Listed: April 29, 2011
	Listed: July 1, 1988
Ethyl benzene (CAS 100-41-4)	Listed: June 11, 2004
Silicon dioxide (CAS 14808-60-7)	Listed: October 1, 1988
Titanium dioxide (CAS 13463-67-7)	Listed: September 2, 2011

**US - California Proposition 65 - CRT: Listed date/Developmental toxin**

4-Methyl-2-pentanone (CAS 108-10-1)	Listed: March 28, 2014
benzene (CAS 71-43-2)	Listed: December 26, 1997
Ethanol (CAS 64-17-5)	Listed: October 1, 1987
Toluene (CAS 108-88-3)	Listed: January 1, 1991

**US - California Proposition 65 - CRT: Listed date/Female reproductive toxin**

Toluene (CAS 108-88-3)	Listed: August 7, 2009
------------------------	------------------------

**US - California Proposition 65 - CRT: Listed date/Male reproductive toxin**

benzene (CAS 71-43-2)	Listed: December 26, 1997
-----------------------	---------------------------

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

<b>Issue date</b>	06-01-2015
<b>Version #</b>	01
<b>HMIS® ratings</b>	Health: 3* Flammability: 4 Physical hazard: 0
<b>NFPA ratings</b>	Health: 3 Flammability: 4 Instability: 0

**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.