

Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED FOR:
 High Teck Quality Products

ADDRESS:
 West Palm Beach, FL 33413

EMERGENCY PHONE : (800) 424-9300
 INFORMATION PHONE : (877) 900-8325

DATE PRINTED : 10/15/2013
 PREPARER NAME : MSDS Coordinator

Section 02: COMPOSITION/INFORMATION INGREDIENTS

| Hazardous Ingredients | % | Exposure Limit | C.A.S.* | LD/50, Route, Species | LC/50 Route, Species |
|-----------------------|-------|----------------|------------|------------------------|------------------------------|
| VM&P NAPHTHA | 75-85 | 300 ppm | 64742-89-8 | NOT AVAILABLE | 3400 ppm (4 hr) INHAL - RAT |
| ISOPROPANOL | 3-7 | 400 ppm | 67-63-0 | >4720 mg/kg ORAL - RAT | 12000 ppm (8 hr) INHAL - RAT |
| XYLENE | 3-7 | 100 ppm | 1330-20-7 | 4.3 g/kg ORAL - RAT | 3400 ppm (4 hr) INHAL - RAT |
| ETHYLBENZENE | 1-5 | 100 ppm | 100-41-4 | | 3400 ppm (4 hr) INHAL - RAT |
| ISOBUTANE | 5-10 | 1000 ppm | 75-28-5 | | 3400 ppm (4 hr) INHAL - RAT |
| PROPANE | 5-10 | 1000 ppm | 74-98-6 | | 3400 ppm (4 hr) INHAL - RAT |

Section 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:

INGESTION MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS.

INHALATION

PROPELLANT IS A SIMPLE ASPHYXIANT. INHALATION OF SOLVENTS MAY CAUSE IRRITATION.

EYE CONTACT..

MAY CAUSE IRRITATION.

SKIN ABSORPTION

MAY BE ABSORBED BY THE SKIN.

SKIN CONTACT

MAY CAUSE IRRITATION

SKIN CONTACT

MAY CAUSE IRRITATION.

EFFECTS OF ACUTE EXPOSURE

DIZZINESS, NAUSEA. IRRITATION TO SKIN & EYES.

EFFECTS OF CHRONIC EXPOSURE

SOLVENTS MAY CAUSE DEFATTING DERMATITIS

EXPOSURE LIMIT OF MATERIAL

SEE SECTION 2.

Section 04: FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURE.....

IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOR OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

Section 05: FIRE FIGHTING MEASURES

AUTO IGNITION TEMPERATURE (°C)..... NOT AVAILABLE

SPECIAL PROCEDURES..... WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARTATUS SHOULD BE WORN IN A FIRE INVOLVING THIS MATERIAL.

FLAMMABILITY..... EXTREMELY FLAMMABLE.

IF YES, UNDER WHICH CONDITIONS?..... EXCESSIVE HEAT, SPARKS AND OPEN FLAME

EXTINGUISHING MEDIA..... WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM

UPPER FLAMMABLE LIMIT..... 16. (% BY VOLUME)

LOWER FLAMMABLE LIMIT..... 1. (% BY VOLUME)

EXPLOSION DATA

SENSITIVITY TO STATIC DISCHARGE..... NOT APPLICABLE

SENSITIVITY TO IMPACT..... NOT APPLICABLE

HAZARDOUS COMBUSTION PRODUCTS..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE

AEROSOL FLAME PROJECTION

CLASSIFIED AS:..... >100cm

FLASHBACK.....YES.

Section 06: ACCIDENTAL RELEASE MEASURES

LEAK/SPILL

REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL AND NON-SPARKING TOOLS.
 VENTILATE AREA.
 PREVENT FROM ENTERING A WATERCOURSE.

Section 07: HANDLING AND STORAGE

STORAGE NEEDS..... KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES
 ENGINEERING CONTROLS..... VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS).
 HANDLING PROCEDURES AND EQUIPMENT..... STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C.
 SYNERGISTIC MATERIALS..... NONE KNOWN.

Section 08: EXPOSURE CONTROLS/PERSONAL PROTECTION

GLOVES/ TYPE..... WEAR CHEMICAL RESISTANT GLOVES.
 RESPIRATORY/TYPE..... IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE
 TYPE RESPIRATOR (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED.
 EYE/TYPE..... SAFETY GLASSES. FOOTWEAR/TYPE..... NOT
 NORMALLY REQUIRED. OTHER/TYPE..... NOT REQUIRED.

Section 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE..... AEROSOL.
 APPEARANCE..... CLEAR LIQUID
 ODOR..... ALIPHATIC
 ODOR THRESHOLD..... NOT AVAILABLE
 VAPOR PRESSURE(PSIG)-AEROSOL.....30-40 @ 20 C
 BOILING POINT (°C)(CONC)..... 80-139
 EVAPORATION RATE..... GREATER THAN 1
 n-BUTYL ACETATE = 1
 VAPOR DENSITY (AIR=1)..... GREATER THAN 1 (BY WEIGHT)
 SOLUBILITY IN WATER g/L (20°C)..... NEGLIGIBLE
 pH..... NOT APPLICABLE
 SPECIFIC GRAVITY (LIQUID)..... 0.70-0.80
 COEFFICIENT OF WATER/OIL DIST.....NOT AVAILABLE
 FREEZING POINT: (°C)..... NOT AVAILABLE
 AEROSOL PERCENT VOLATILE.....100. (BY WEIGHT)
 SPECIFIC GRAVITY (AEROSOL).....0.70-0.85.

Section 10: STABILITY AND REACTIVITY

HAZARDOUS PRODUCTS OF DECOMPOSITION..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE
 COMBUSTION IS INCOMPLETE
 CHEMICAL STABILITY:
 YES... UNDER NORMAL CONDITIONS
 NO, WHICH CONDITIONS?.....NOT APPLICABLE
 COMPATIBILITY WITH OTHER SUBSTANCES:
 NO, WHICH ONES?.....STRONG OXIDIZING AGENTS
 REACTIVITY CONDITIONS?..... NOT APPLICABLE
 HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR.

Section 11: TOXICOLOGICAL INFORMATION

REPRODUCTIVE EFFECTS

XYLENE - HIGH EXPOSURES TO XYLENE IN SOME ANIMAL STUDIES, OFTEN AT LEVELS TOXIC TO THE MOTHER, AFFECTED EMBRYO/FETAL DEVELOPMENT. THE SIGNIFICANCE OF THIS FINDING TO HUMANS IS NOT KNOWN.

IRRITANCY OF MATERIAL

SKIN/EYE IRRITANT

SENSITIZING CAPABILITY OF MATERIAL

UNKNOWN

CARCINOGENICITY OF MATERIAL

XYLENE - THIS PRODUCT CONTAINS ETHYLBENZENE (ETHYLBENZENE IS IN XYLENE). ETHYLBENZENE HAS BEEN SHOWN TO CAUSE CANCER IN LABORATORY ANIMALS. TOXICITY TESTS CARRIED OUT FOR CHRONIC EFFECTS AND MUTAGENICITY HAVE BEEN NEGATIVE. THE RELEVANCE OF THIS FINDING TO HUMANS IS UNCERTAIN. IARC HAS CLASSIFIED ETHYLBENZENE AS A POSSIBLE HUMAN CARCINOGEN. ETHYL BENZENE: DESIGNATED AS IARC GROUP 2B CARCINOGEN-POSSIBLY CARINOGENIC TO HUMANS.

MUTAGENICITY

NONE KNOWN

TERATOGENICITY

NO INFORMATION IS AVAILABLE AND NO ADVERSE TERATOGENIC EFFECTS ARE ANTICIPATED.

Section 12: ECOLOGICAL CONSIDERATIONS

ENVIRONMENTAL

NOT AVAILABLE.

Section 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.

Section 14: TRANSPORTATION INFORMATION

T.D.G. CLASSIFICATION..... CONSUMER COMMODITY (AEROSOLS, UN1950, CLASS 2.1)

D.O.T. CLASSIFICATION..... CONSUMER COMMODITY, ORM-D.

Section 15: REGULATORY INFORMATION

CANADIAN REGULATIONS:

WHMIS CLASSIFICATION..... A,B5,D2A,D2B

CNFC SECTION 3.3.5..... LEVEL 3

CEPA (Canadian Environmental Protection Act)

ALL SUBSTANCES IN THIS PRODUCT ARE LISTED ON THE CANADIAN DOMESTIC SUBSTANCES LIST (DSL) OR ARE NOT REQUIRED TO BE LISTED

U.S. REGULATIONS:

HMIS RATING HEALTH..... 2 MODERATE HAZARD

HMIS RATING FLAMMABILITY..... 4 SEVERE HAZARD

HMIS RATING REACTIVITY..... 0 MINIMAL HAZARD

HMIS RATING PERSONAL PROTECTION..... B

NFPA CODE 30B.....LEVEL 3

SARA 313 INFORMATION:

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

CAS #:

*1330-20-7

*100-41-4

CHEMICAL NAME:

XYLENE

ETHYL BENZENE

CALIFORNIA PROPOSITION 65..

THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY WITH THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986: .

WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM

00008025

MATERIAL SAFETY DATA SHEET

HT-7800A WIPEOUT (Aerosol)

100%VOC

Page 1 of 4

CAS #:

*100-41-4

CHEMICAL NAME:

ETHYL BENZENE IN XYLENE

TSCA (Toxic Substances Control Act).....

ALL COMPONENT OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY. ANY IMPURITIES PRESENT IN THIS PRODUCT ARE EXEMPT FROM LISTING.

VOC (w/w%)..... 100.

Section 16: OTHER INFORMATION

THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY HIGH TECK QUALITY PRODUCTS. FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. HIGH TECK QUALITY PRODUCTS. ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE. THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS.

PREPARATION DATE Jan1/2013