


# MATERIAL SAFETY DATA SHEET

## Wipeout



|                     |   |   |   |
|---------------------|---|---|---|
| <b>HEALTH</b>       | * | 1 |   |
| <b>FLAMMABILITY</b> |   | 3 |   |
| <b>PHYSICAL</b>     |   | 0 |   |
| <b>PPE</b>          |   |   | X |



Printed: 07/03/2013  
Revision: 07/03/2013  
Supersedes Revision: 08/26/2010

### 1. Product and Company Identification

**Product Code:** 1700.4D  
**Product Name:** Wipeout  
**Manufacturer Information**  
**Company Name:** High Teck Quality Products  
 West Palm Beach, FL 33413  
 No data available.  
**Emergency Contact:** (800)424-9300  
**Information:** (877)900-8325  
**Preparer Name:** EHS Department  
**Synonyms**  
 7800-1, 7800-4, 7800-5  
**Revision Date:** 07/03/2013

### 2. Composition/Information on Ingredients

| Hazardous Components (Chemical Name)  | CAS #      | Concentration   | OSHA TWA  | ACGIH TLV  | Other Limits |
|---|------------|-----------------|-----------|------------|--------------|
| 1. Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits} | 8052-41-3  | 7.0 -13.0 %     | 500 ppm   | 100 ppm    | No data.     |
| 2. Light aliphatic solvent naphtha (petroleum)  | 64742-89-8 | 60.0 -100.0 %   | No data.  | No data.   | No data.     |
| 3. Heptane  | 142-82-5   | 5.0 -10.0 %     | 500 ppm   | 400 ppm    | No data.     |
| 4. Toluene {Benzene, Methyl-; Toluol}   | 108-88-3   | 1.0 -5.0 %      | 200 ppm   | 50 ppm     | No data.     |
| Hazardous Components (Chemical Name)  | CAS #      | OSHA STEL       | OSHA CEIL | ACGIH STEL | ACGIH CEIL   |
| 1. Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits} | 8052-41-3  | No data.        | No data.  | No data.   | No data.     |
| 2. Light aliphatic solvent naphtha (petroleum)  | 64742-89-8 | No data.        | No data.  | No data.   | No data.     |
| 3. Heptane  | 142-82-5   | No data.        | No data.  | No data.   | No data.     |
| 4. Toluene {Benzene, Methyl-; Toluol}   | 108-88-3   | 500 ppm/(10min) | 300 ppm   | No data.   | No data.     |

### 3. Hazards Identification

#### Emergency Overview

Danger! Flammable! Harmful or fatal if swallowed. Vapor harmful. Eye irritant.

#### Potential Health Effects (Acute and Chronic)

**Inhalation Acute Exposure Effects:**

Vapor concentration may cause headache, dizziness, irritation of the respiratory tract, eye irritation, stupor, depression of the central nervous system, watering of the eyes, weakness, nausea, muscle twitches, and kidney effects. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal. Severe overexposure may cause convulsions, unconsciousness, depression of the central nervous system, irritation of the respiratory tract, coma, and death.

**Skin Contact Acute Exposure Effects:**

May cause irritation, drying of the skin, burning sensation, redness, swelling, and/or blisters. Absorption may cause or increase severity of symptoms listed under inhalation. If the skin is damaged, absorption increases. Prolonged or repeated contact may cause moderate to severe dermatitis. Chronic symptoms may include drying, swelling, scaling, blistering, cracking, and severe tissue damage.

# MATERIAL SAFETY DATA SHEET

## Wipeout

Page: 2

Printed: 07/03/2013

Revision: 07/03/2013

Supersedes Revision: 08/26/2010

### Eye Contact Acute Exposure Effects:

May cause irritation, burning sensation, redness, swelling, watering of the eyes, and/or blurred vision.

### Ingestion Acute Exposure Effects:

Harmful or fatal if swallowed. Causes irritation of the stomach and intestines, resulting in nausea and vomiting. May cause burning sensation in mouth and stomach, headache, loss of appetite, weakness, muscle twitches, loss of coordination, convulsions, unconsciousness, coma, and death.

If the material enters the lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. This can result in severe lung damage or death.

### Chronic Exposure Effects:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Repeated or prolonged skin contact may cause redness, irritation, and scaling of the skin. May cause skin irritation, anemia, bone marrow damage, some loss of memory, heart palpitations, liver damage, kidney damage, and jaundice.

Target Organs: lungs, central nervous system, brain, mucous membranes, skin, eyes, liver, and kidneys.

### Signs and Symptoms Of Exposure

Primary routes of exposure:

Inhalation, ingestion, and dermal.

### Medical Conditions Generally Aggravated By Exposure

Pre-existing central nervous system disease, neurological conditions, skin disorders, liver or kidney function, or chronic respiratory diseases.

### OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

## 4. First Aid Measures

### Emergency and First Aid Procedures

Inhalation:

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

Skin contact:

Wash with soap, if available, and large quantities of water for at least 15 minutes. Seek medical attention if irritation from contact persists.

Eye contact:

Immediately flush eyes with water, remove any contact lens, continue flushing with water for at least 15 minutes. Get medical attention.

Ingestion:

Do not induce vomiting. Call your poison control center, hospital emergency room, or physician immediately.

### Note to Physician

Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

## 5. Fire Fighting Measures

**Flammability Classification:** OSHA Class IB  
**Flash Pt:** 52.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)  
**Explosive Limits:** LEL: No data. UEL: No data.  
**Autoignition Pt:** No data available.

### Fire Fighting Instructions

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

### Flammable Properties and Hazards

No data available.

### Hazardous Combustion Products

Carbon monoxide, carbon dioxide

### Extinguishing Media

Use carbon dioxide, dry powder, or foam.

### Unsuitable Extinguishing Media

No data available.

## 6. Accidental Release Measures

### Steps To Be Taken In Case Material Is Released Or Spilled

Danger! Flammable! Keep away from heat, sparks, flame and all other sources of ignition. Vapors may cause fire. Vapors may travel long distances to other areas and rooms away from work site. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition anywhere in the structure, dwelling or building during use and until all vapors are gone from work site and all areas away from the work site. Keep away from electrical outlets and switches. Beware of static electricity that may be generated by synthetic clothing and other sources.

Use non-metallic or non-sparking tools. Properly bond and ground all equipment.

#### Clean-up:

Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources, keep flares, smoking or flames out of hazard area.

#### Small spills:

Take up the spilled liquid with sand, earth, or other noncombustible absorbent material and place in a plastic container where applicable.

#### Large spills:

Dike far ahead of spill for later disposal.

## 7. Handling and Storage

### Precautions To Be Taken in Handling

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

### Precautions To Be Taken in Storing

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

## 8. Exposure Controls/Personal Protection

### Respiratory Equipment (Specify Type)

For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV or exposure limits. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

### Eye Protection

Chemical goggles, or face shields are recommended to safeguard against potential eye contact, irritation, or injury.

### Protective Gloves

Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information.

### Other Protective Clothing

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

### Engineering Controls (Ventilation etc.)

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering -- Stop -- ventilation is inadequate. Leave area immediately.

### Work/Hygienic/Maintenance Practices

A source of clean water should be available in the work area for flushing eyes and skin.  
Do not eat, drink, or smoke in the work area.  
Wash hands thoroughly after use.

## 9. Physical and Chemical Properties

|   |                    |              |  |
|---|--------------------|--------------|--|
| <b>Physical States:</b>                   | [ ] Gas            | [ X ] Liquid | [ ] Solid                              |
| <b>Melting Point:</b>                     | No data.           |              |  |
| <b>Boiling Point:</b>                     | 190.00 F           |              |  |
| <b>Autoignition Pt:</b>                   | No data.           |              |  |
| <b>Flash Pt:</b>                          | 52.00 F            | Method Used: | Setaflash Closed Cup (Rapid Setaflash) |
| <b>Specific Gravity (Water = 1):</b>      | 0.75               |              |  |
| <b>Vapor Pressure (vs. Air or mm Hg):</b> | No data.           |              |  |
| <b>Vapor Density (vs. Air = 1):</b>       | > 1                |              |  |
| <b>Evaporation Rate:</b>                  | No data.           |              |  |
| <b>Solubility in Water:</b>               | Insoluble          |              |  |
| <b>Percent Volatile:</b>                  | 100.0 % by weight. |              |  |
| <b>VOC / Volume:</b>                      | 750.0000 G/L       |              |  |

### Appearance and Odor

Free and clear, water white

## 10. Stability and Reactivity

**Stability:** Unstable [ ] Stable [ X ]

### Conditions To Avoid - Instability

No data available.

### Incompatibility - Materials To Avoid

Incompatible with strong oxidizing agents.

### Hazardous Decomposition Or Byproducts

Thermal decomposition may produce carbon monoxide and carbon dioxide.

**Hazardous Polymerization:** Will occur [ ] Will not occur [ X ]

### Conditions To Avoid - Hazardous Polymerization

No data available.

## 11. Toxicological Information

### Toxicological Information

Solvent Naphtha:

LD50 Rat oral >2000 mg/kg

LD50 Rat skin >2000 mg/kg

LC50 Rat Inhalation >5000 ppm / 1 hr

Stoddard Solvent:

LD50 Rat oral >34,600 mg/kg

LC50 Rat Inhalation >21,400 mg/m<sup>3</sup> / 4 hrs

LD50 Rabbit skin 15,400 mg/kg

Heptane:

LD50 Mouse iv 222 mg/kg

LD50 Mouse inhalation 75 g/cu m/2 hr

LC50 Rat inhalation 103 g/cu m/4 hr

Toluene:

LD50 Rat oral 2.6 to 7.5 g/kg

LD50 Rabbit dermal 14.1 ml/kg

LD50 Rat (female) ip 1.64 g/kg

LD50 Mouse IP 1.15 G/KG

LD50 Rat oral 5000 mg/kg

LD50 Rat ip 1332 mg/kg

LD50 Rat iv 1960 mg/kg

LC50 Mouse ihl 400 ppm/24 hr

LD50 Mouse ip 59 mg/kg

LD50 Mouse sc 2250 mg/kg

LD50 Mouse ip 640 mg/kg

LD50 Rabbit skin 12,124 mg/kg

LC50 Mice inhalation 5320 ppm/8 hr

CAS# 8052-41-3:

Acute toxicity, LD (Lethal dose), Oral, Rat, 5.000 GM/KG.

# MATERIAL SAFETY DATA SHEET

## Wipeout

Page: 6

Printed: 07/03/2013

Revision: 07/03/2013

Supersedes Revision: 08/26/2010

Result:

Behavioral: Somnolence (general depressed activity).

- Acute Toxicity Data. Journal of the American College of Toxicology, Part B., Mary Ann Liebert, Inc., 1651 Third Ave., New York, NY 10128, Vol/p/yr: 1,32, 1990

Acute toxicity, LC (Lethal concentration), Inhalation, Rat, 5500. MG/M3, 4 H.

Result:

Behavioral: Somnolence (general depressed activity).

- Acute Toxicity Data. Journal of the American College of Toxicology, Part B., Mary Ann Liebert, Inc., 1651 Third Ave., New York, NY 10128, Vol/p/yr: 1,32, 1990

Acute toxicity, LD (Lethal dose), Skin, Species: Rabbit, 3.000 GM/KG.

Result:

Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants).

Effects on Fertility: Litter size (e.g.; # fetuses per litter; measured before birth).

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

- Acute Toxicity Data. Journal of the American College of Toxicology, Part B., Mary Ann Liebert, Inc., 1651 Third Ave., New York, NY 10128, Vol/p/yr: 1,32, 1990

Acute toxicity, LC50, Inhalation, Rat, 1400. ppm.

Result:

Behavioral: Hallucinations, distorted perceptions.

Behavioral: Change in motor activity (specific assay).

Behavioral: Changes in psychophysiological tests.

Standard Draize Test, Eyes, Human, 100.0 ppm, Mild.

Result:

Brain and Coverings: Recordings from specific areas of CNS.

Behavioral: Antipsychotic.

Blood: Changes in bone marrow not included above.

### Chronic Toxicological Effects

No data available.

### Carcinogenicity/Other Information

No data available.

## 12. Ecological Information

### General Ecological Information

No data available.

## 13. Disposal Considerations

### Waste Disposal Method

Dispose in accordance with applicable local, state, and federal regulations.

## 14. Transport Information

### LAND TRANSPORT (US DOT)

**DOT Proper Shipping Name** Flammable Liquid, n.o.s.

**DOT Hazard Class:** 3

# MATERIAL SAFETY DATA SHEET

## Wipeout

**DOT Hazard Label:** FLAMMABLE LIQUID  
**UN/NA Number:** UN1993  
**Packing Group:** III

### Additional Transport Information

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

## 15. Regulatory Information

### US EPA SARA Title III

| Hazardous Components (Chemical Name)  | CAS #      | Sec.302 (EHS) | Sec.304 RQ  | Sec.313 (TRI) | Sec.110 |
|---|------------|---------------|-------------|---------------|---------|
| 1. Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits} | 8052-41-3  | No            | No          | No            | No      |
| 2. Light aliphatic solvent naphtha (petroleum)  | 64742-89-8 | No            | No          | No            | No      |
| 3. Heptane  | 142-82-5   | No            | No          | No            | No      |
| 4. Toluene {Benzene, Methyl-; Toluol}   | 108-88-3   | No            | Yes 1000 LB | Yes           | Yes     |

### US EPA CAA, CWA, TSCA

| Hazardous Components (Chemical Name)  | CAS #      | EPA CAA | EPA CWA NPDES | EPA TSCA                   | CA PROP 65 |
|---|------------|---------|---------------|----------------------------|------------|
| 1. Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits} | 8052-41-3  | No      | No            | Inventory                  | No         |
| 2. Light aliphatic solvent naphtha (petroleum)  | 64742-89-8 | No      | No            | Inventory                  | No         |
| 3. Heptane  | 142-82-5   | No      | No            | Inventory, 4 Test, 8A PAIR | No         |
| 4. Toluene {Benzene, Methyl-; Toluol}   | 108-88-3   | HAP     | Yes           | Inventory, 8A CAIR         | Yes        |

### EPA Hazard Categories:

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

- Yes  No Acute (immediate) Health Hazard
- Yes  No Chronic (delayed) Health Hazard
- Yes  No Fire Hazard
- Yes  No Sudden Release of Pressure Hazard
- Yes  No Reactive Hazard

## 16. Other Information

No data available.