

SAFETY DATA SHEET
HI TECK EURO 4:1 UNIVERSAL CLEAR

Page: 1
Compilation date: 13/08/2013
Revision date: 10/11/2010
Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: HI TECK EURO 4:1 UNIVERSAL CLEAR
Product code: 9000E

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PAINT PRODUCT CONTAINING XYLENE, MIXTURE OF ISOMERS

1.3. Details of the supplier of the safety data sheet

Company name: High Teck Quality Products
West Palm Beach
FL33413
Tel: (877) 900-8325
Email: info@highteckproducts.com

1.4. Emergency telephone number

Emergency tel: (800) 424-9300

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xn: R20/21; Xi: R38; -: R52/53

Most important adverse effects: Highly flammable. Harmful by inhalation and in contact with skin. Irritating to skin.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Highly flammable.
Harmful.



Risk phrases: R11: Highly flammable.
R20/21: Harmful by inhalation and in contact with skin.
R38: Irritating to skin.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S16: Keep away from sources of ignition - No smoking.

SAFETY DATA SHEET

HI TECK EURO 4:1 UNIVERSAL CLEAR

Page: 2

S23: Do not breathe vapour/spray

S36/37: Wear suitable protective clothing and gloves.

S42: During fumigation / spraying wear suitable respiratory equipment.

2.3. Other hazards

Other hazards: Harmful: may cause lung damage if swallowed.

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

XYLENE.

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	-	-	-	30-40%

N-BUTYL ACETATE

204-658-1	123-86-4	-: R10; -: R66; -: R67	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	1-12.5%
-----------	----------	------------------------	--	---------

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM... - REACH registered number(s): 01-2119455851-35-XXXX

265-199-0	64742-95-6	-: R10; Xi: R37; N: R51/53; Xn: R65; -: R66; -: R67	STOT SE 3: H335; STOT SE 3: H336; Aquatic Chronic 2: H411; Flam. Liq. 3: H226; Asp. Tox. 1: H304	1-12.5%
-----------	------------	---	--	---------

ETHYLBENZENE

202-849-4	100-41-4	F: R11; Xn: R20	Flam. Liq. 2: H225; Acute Tox. 4: H332	1-12.5%
-----------	----------	-----------------	--	---------

4-METHYLPENTAN-2-ONE

203-550-1	108-10-1	F: R11; Xn: R20; Xi: R36/37; -: R66	Flam. Liq. 2: H225; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; -: EUH066	1-12.5%
-----------	----------	-------------------------------------	--	---------

2-BUTOXYETHYL ACETATE

203-933-3	112-07-2	Xn: R20/21	Acute Tox. 4: H332; Acute Tox. 4: H312	1-12.5%
-----------	----------	------------	--	---------

METHYL ACETATE

201-185-2	79-20-9	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-12.5%
-----------	---------	---------------------------------	--	---------

2-METHOXY-1-METHYLETHYL ACETATE

203-603-9	108-65-6	-: R10	Flam. Liq. 3: H226	1-12.5%
-----------	----------	--------	--------------------	---------

[cont...]

SAFETY DATA SHEET
HI TECK EURO 4:1 UNIVERSAL CLEAR

Page: 3

ACETONE

200-662-2	67-64-1	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-12.5%
-----------	---------	---------------------------------	---	---------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. Wash out mouth with water. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and pain.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Dry chemical powder. Alcohol or polymer foam. Do not use water.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the neighbourhood to the presence of fumes or gas.

[cont...]

SAFETY DATA SHEET
HI TECK EURO 4:1 UNIVERSAL CLEAR

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Wash the spillage site with large amounts of water.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed. Keep away from direct sunlight.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	50 ppm	100 ppm	1 mg/m ³	-

Hazardous ingredients:

XYLENE.

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m ³	441 mg/m ³	-	-

N-BUTYL ACETATE

UK	724 mg/m ³	966 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

ETHYLBENZENE

UK	441 mg/m ³	552 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

4-METHYLPENTAN-2-ONE

UK	208 mg/m ³	416 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

2-BUTOXYETHYL ACETATE

UK	20 ppm	50 ppm	-	-
----	--------	--------	---	---

SAFETY DATA SHEET
HI TECK EURO 4:1 UNIVERSAL CLEAR

Page: 5

METHYL ACETATE

UK	616 mg/m3	770 mg/m3	-	-
----	-----------	-----------	---	---

2-METHOXY-1-METHYLETHYL ACETATE

UK	274 mg/m3	548 mg/m3	-	-
----	-----------	-----------	---	---

ACETONE

UK	1210 mg/m3	3620 mg/m3	-	-
----	------------	------------	---	---

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Compressed airline breathing apparatus (EN139).

Hand protection: Nitrile gloves.

Eye protection: Face-shield.

Skin protection: Protective clothing with elasticated cuffs and closed neck.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Aromatic

Evaporation rate: Moderate

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Kinematic viscosity: 15 seconds

Viscosity test method: DIN 4 Cup 20C

Boiling point/range°C: 40

Flammability limits %: lower: 1.0

upper: 6.6

Flash point°C: -18

Autoflammability°C: 490

Relative density: 0.94

VOC g/l: 553 less water and exempt compounds, 456 Total VOC

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

[cont...]

SAFETY DATA SHEET
HI TECK EURO 4:1 UNIVERSAL CLEAR

Page: 6

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Sources of ignition. Flames.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM	Hazardous: calculated
Irritation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and pain.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Volatile. Heavier than water.

[cont...]

SAFETY DATA SHEET
HI TECK EURO 4:1 UNIVERSAL CLEAR

Page: 7

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Incineration on land.

Recovery operations: Use principally as a fuel or other means to generate energy.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]

SAFETY DATA SHEET
HI TECK EURO 4:1 UNIVERSAL CLEAR

Page: 8

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

FOR PROFESSIONAL USE ONLY. Read full instructions before use.

IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used.

Phrases used in s.2 and 3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H312: Harmful in contact with skin.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

R10: Flammable.

R11: Highly flammable.

R20/21: Harmful by inhalation and in contact with skin.

R20: Harmful by inhalation.

R36/37: Irritating to eyes and respiratory system.

R36: Irritating to eyes.

R37: Irritating to respiratory system.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. Since conditions of use are outside our control, this company shall not be held liable for any damage resulting from handling or from contact with the above product.