



# HIGH TECK E9050 HIGH SOLIDS EURO CLEAR

## Safety Data Sheet NO9050-US

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/14/2015

Revision date: 01/06/2020

Supersedes: 12/10/2019

Version: 4.1

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Trade name : HIGH TECK E9050 HIGH SOLIDS EURO CLEAR  
Product code : NO9050E-1

#### 1.2. Recommended use and restrictions on use

Recommended use : Topcoat

#### 1.3. Supplier

HIGH TECK PRODUCTS  
PO BOX 24631  
WEST PALM BEACH  
33416 - USA  
T 877-900-8325  
[info@highteckproducts.com](mailto:info@highteckproducts.com)

#### 1.4. Emergency telephone number

Emergency number : (800) 424-9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

|   |   |
|---|---|
| Flammable liquids Category 3                                  | Flammable liquid and vapor  |
| Skin corrosion/irritation Category 2                          | Causes skin irritation  |
| Serious eye damage/eye irritation Category 2                  | Causes serious eye irritation                                     |
| Skin sensitization, Category 1                                | May cause an allergic skin reaction                               |
| Carcinogenicity Category 2                                    | Suspected of causing cancer                                       |
| Specific target organ toxicity (single exposure) Category 3   | May cause respiratory irritation                                  |
| Specific target organ toxicity (single exposure) Category 3   | May cause drowsiness or dizziness                                 |
| Specific target organ toxicity (repeated exposure) Category 2 | May cause damage to organs through prolonged or repeated exposure |

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

Flammable liquid and vapor  
Causes skin irritation  
May cause an allergic skin reaction  
Causes serious eye irritation  
May cause respiratory irritation  
May cause drowsiness or dizziness  
Suspected of causing cancer  
May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) :

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Keep container tightly closed.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe vapors, spray, fume.  
Wash hands thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear face protection, protective clothing, protective gloves.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

# HIGH TECK E9050 HIGH SOLIDS EURO CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use foam, extinguishing powder, dry sand to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name  | Product identifier     | %      | GHS US classification  |
|---|------------------------|--------|--|
| solvent naphtha (petroleum), light aromatic   | (CAS-No.) 64742-95-6   | < 23   | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411   |
| xylene  | (CAS-No.) 1330-20-7    | 5 – 23 | Flam. Liq. 3, H226<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4 (Inhalation), H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>STOT RE 2, H373<br>Asp. Tox. 1, H304 |
| 4-methylpentan-2-one, isobutyl methyl ketone  | (CAS-No.) 108-10-1     | 5 – 23 | Flam. Liq. 2, H225<br>Acute Tox. 4 (Inhalation), H332<br>Acute Tox. 4 (Inhalation:vapour), H332<br>Eye Irrit. 2, H319<br>Carc. 2, H351<br>STOT SE 3, H335                                    |
| reaction mass of ethylbenzene, m-xylene and p-xylene  |                        | < 5    | Flam. Liq. 3, H226<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4 (Inhalation), H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>STOT RE 2, H373<br>Asp. Tox. 1, H304 |
| ethylbenzene  | (CAS-No.) 100-41-4     | < 5    | Flam. Liq. 2, H225<br>Acute Tox. 4 (Inhalation:vapour), H332<br>Carc. 2, H351<br>STOT RE 2, H373<br>Asp. Tox. 1, H304  |
| reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-oxypoly(oxyethylene) | (CAS-No.) 104810-47-1  | < 5    | Skin Sens. 1, H317<br>Aquatic Chronic 2, H411  |
| reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate  | (CAS-No.) 1065336-91-5 | < 5    | Skin Sens. 1A, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410  |

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general

: IF exposed or concerned: Get medical advice/attention.

# HIGH TECK E9050 HIGH SOLIDS EURO CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                       |  |
|---------------------------------------|--|
| First-aid measures after inhalation   | : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.   |
| First-aid measures after skin contact | : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.                          |
| First-aid measures after eye contact  | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion    | : Call a poison center/doctor/physician if you feel unwell.  |

### 4.2. Most important symptoms and effects (acute and delayed)

|                                     |  |
|-------------------------------------|--|
| Symptoms/effects                    | : May cause drowsiness or dizziness.               |
| Symptoms/effects after inhalation   | : May cause respiratory irritation.                |
| Symptoms/effects after skin contact | : Irritation. May cause an allergic skin reaction. |
| Symptoms/effects after eye contact  | : Eye irritation.                                  |

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Specific hazards arising from the chemical

|             |                               |
|-------------|-------------------------------|
| Fire hazard | : Flammable liquid and vapor. |
| Reactivity  | : Flammable liquid and vapor. |

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

|                      |   |
|----------------------|---|
| Protective equipment | : Protective clothing. Safety glasses. Gloves.  |
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapors, spray, fume. Avoid contact with skin and eyes. |

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

|                         |   |
|-------------------------|---|
| For containment         | : Collect spillage. Contain released product, pump into suitable containers.                                  |
| Methods for cleaning up | : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. |
| Other information       | : Dispose of materials or solid residues at an authorized site.   |

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

|                               |   |
|-------------------------------|---|
| Precautions for safe handling | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, spray, fume. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. |
| Hygiene measures              | : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.   |

# HIGH TECK E9050 HIGH SOLIDS EURO CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 7.2. Conditions for safe storage, including any incompatibilities

|                            |  |
|----------------------------|--|
| Technical measures         | : Ground/bond container and receiving equipment.   |
| Storage conditions         | : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. |
| Storage temperature        | : < 25 °C  |
| Storage area               | : Store in well ventilated area.   |
| Special rules on packaging | : Keep only in original container.   |

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| 4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)  |                                |   |
|--|--------------------------------|---|
| ACGIH  | Local name                     | Methyl isobutyl ketone  |
| ACGIH  | ACGIH TWA (ppm)                | 20 ppm  |
| ACGIH  | ACGIH STEL (ppm)               | 75 ppm  |
| ACGIH  | Remark (ACGIH)                 | TLV® Basis: URT irr; dizziness; headache. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI                       |
| ACGIH  | Regulatory reference           | ACGIH 2019  |
| OSHA   | OSHA PEL (TWA) (mg/m³)         | 410 mg/m³   |
| OSHA   | OSHA PEL (TWA) (ppm)           | 100 ppm   |
| OSHA   | Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1  |
| ethylbenzene (100-41-4)  |                                |   |
| ACGIH  | Local name                     | Ethylbenzene  |
| ACGIH  | ACGIH TWA (ppm)                | 20 ppm  |
| ACGIH  | Remark (ACGIH)                 | TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI |
| ACGIH  | Regulatory reference           | ACGIH 2019  |
| OSHA   | OSHA PEL (TWA) (mg/m³)         | 435 mg/m³   |
| OSHA   | OSHA PEL (TWA) (ppm)           | 100 ppm   |
| OSHA   | Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1  |
| reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1) |                                |   |
| Not applicable   |                                |   |
| solvent naphtha (petroleum), light aromatic (64742-95-6)   |                                |   |
| Not applicable   |                                |   |
| reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)  |                                |   |
| Not applicable   |                                |   |
| reaction mass of ethylbenzene, m-xylene and p-xylene   |                                |   |
| Not applicable   |                                |   |
| xylene (1330-20-7)   |                                |   |
| ACGIH  | Local name                     | Xylene, mixed isomers (Dimethylbenzene)   |
| ACGIH  | ACGIH TWA (ppm)                | 100 ppm   |
| ACGIH  | ACGIH STEL (ppm)               | 150 ppm   |
| ACGIH  | Remark (ACGIH)                 | TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI  |
| ACGIH  | Regulatory reference           | ACGIH 2019  |
| OSHA   | OSHA PEL (TWA) (mg/m³)         | 435 mg/m³   |
| OSHA   | OSHA PEL (TWA) (ppm)           | 100 ppm   |
| OSHA   | Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1  |

# HIGH TECK E9050 HIGH SOLIDS EURO CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Gas mask. Gloves. Protective clothing. Safety glasses.

#### Materials for protective clothing:

Impermeable clothing

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Air-fed respiratory protective equipment should be worn when this product is sprayed

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|   |   |
|---|---|
| Physical state                                  | : Liquid  |
| Appearance                                      | : Liquid.<br>: Colorless<br>: aromatic                      |
| Odor threshold                                  | : No data available   |
| pH  | : No data available   |
| Melting point                                   | : Not applicable  |
| Freezing point                                  | : No data available   |
| Boiling point                                   | : > 35 °C   |
| Flash point                                     | : 27 °C   |
| Relative evaporation rate (butyl acetate=1)     | : No data available   |
| Flammability (solid, gas)                       | : Not applicable.   |
| Vapor pressure                                  | : No data available   |
| Relative vapor density at 20 °C                 | : No data available   |
| Relative density                                | : No data available   |
| Specific gravity / density                      | : ≈ 0.97 (0.96 – 0.98) g/cm <sup>3</sup>                    |
| Solubility                                      | : insoluble in water. soluble in most organic solvents.     |
| Partition coefficient n-octanol/water (Log Pow) | : No data available   |
| Auto-ignition temperature                       | : No data available   |
| Decomposition temperature                       | : No data available   |
| Viscosity, kinematic                            | : ≈ 171 (162 – 181) mm <sup>2</sup> /s (38-48s DIN4 @ 20°C) |
| Viscosity, dynamic                              | : No data available   |

# HIGH TECK E9050 HIGH SOLIDS EURO CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                      |                     |
|----------------------|---------------------|
| Explosion limits     | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |

### 9.2. Other information

|                            |                        |
|----------------------------|------------------------|
| As Packaged Regulatory VOC | : 521 g/l (4.3 lb/gal) |
| As Packaged Actual VOC     | : 521 g/l (4.3 lb/gal) |
| As Applied Regulatory VOC  | : 583 g/l (4.9 lb/gal) |
| As Applied Actual VOC      | : 583 g/l (4.9 lb/gal) |
| Water Content              | 0 wt%                  |
| Exempt Compounds by volume | : 0 vol %              |
| Exempt Compounds by weight | : 0 wt%                |
| Volatiles                  | : 53.9 wt%             |
| % HAPS                     | : 27.8 wt%             |
| Percent Solids             | : 46.08 wt%            |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapor.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                             |                  |
|-----------------------------|------------------|
| Acute toxicity (oral)       | : Not classified |
| Acute toxicity (dermal)     | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

| 4-methylpentan-2-one, isobutyl methyl ketone (108-10-1) |  |
|---|--|
| LD50 oral rat   | 2080 mg/kg (Equivalent or similar to OECD 401, Rat, Experimental value, Oral)                                    |
| LD50 dermal rat   | ≥ 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal) |
| LC50 inhalation rat (mg/l)                              | 8.2 – 16.4 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (vapours))          |
| ATE US (oral)   | 2080 mg/kg body weight   |
| ATE US (gases)  | 4500 ppmV/4h   |
| ATE US (vapors)   | 8.2 mg/l/4h  |
| ATE US (dust, mist)                                     | 1.5 mg/l/4h  |

| ethylbenzene (100-41-4)    |  |
|----------------------------|--|
| LD50 oral rat              | 3500 mg/kg (Rat, Male / female, Experimental value, Oral)                |
| LD50 dermal rabbit         | 15432 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal) |
| LC50 inhalation rat (mg/l) | 17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))     |
| ATE US (oral)              | 3500 mg/kg body weight   |
| ATE US (dermal)            | 15432 mg/kg body weight  |
| ATE US (vapors)            | 17.8 mg/l/4h   |
| ATE US (dust, mist)        | 17.8 mg/l/4h   |

# HIGH TECK E9050 HIGH SOLIDS EURO CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1)</b> |   |
|---|---|
| LD50 oral rat   | > 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female) |
| LD50 dermal rat   | > 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat, male/female) |
| LC50 inhalation rat (mg/l)  | 5800 mg/l (OECD Guideline 403, 14d, rat)  |
| ATE US (vapors)   | 5800 mg/l/4h  |
| ATE US (dust, mist)   | 5800 mg/l/4h  |

| <b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b> |   |
|---|---|
| LD50 oral rat   | 3592 mg/kg (OECD Test Guideline 401, rat) |
| LD50 dermal rabbit  | > 3160 mg/kg (OECD Test Guideline 402)    |
| ATE US (oral)   | 3592 mg/kg body weight                    |

| <b>reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)</b> |  |
|--|--|
| LD50 oral rat  | 3230 mg/kg (OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), rat, male/female) |
| LD50 dermal rat  | > 3170 mg/kg (OECD Guideline 402 (Acute Dermal Toxicity), read-across,                             |
| ATE US (oral)  | 3230 mg/kg body weight   |

| <b>reaction mass of ethylbenzene, m-xylene and p-xylene</b> |  |
|---|--|
| LD50 oral rat   | 3523 mg/kg<br>(EU Method B.1 (Acute Toxicity (Oral), rat, male)                                |
| LD50 dermal rabbit  | 12126 mg/kg (Weight of evidence, New Zealand White)  |
| LC50 inhalation rat (ppm)                                   | 6350 ppm/4h (4 h, EU Method B.2 (Acute Toxicity (Inhalation)), rat, male, Inhalation, vapours) |
| ATE US (oral)   | 3523 mg/kg body weight   |
| ATE US (dermal)   | 1100 mg/kg body weight   |
| ATE US (gases)  | 6350 ppmV/4h   |
| ATE US (vapors)   | 11 mg/l/4h   |
| ATE US (dust, mist)   | 1.5 mg/l/4h  |

| <b>xylene (1330-20-7)</b> |  |
|---------------------------|--|
| LD50 oral rat             | 3523 mg/kg body weight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rat           | 12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)   |
| LC50 inhalation rat (ppm) | 6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)   |
| ATE US (oral)             | 3523 mg/kg body weight   |
| ATE US (dermal)           | 1100 mg/kg body weight   |
| ATE US (gases)            | 6700 ppmV/4h   |
| ATE US (vapors)           | 11 mg/l/4h   |
| ATE US (dust, mist)       | 1.5 mg/l/4h  |

|                                   |  |
|-----------------------------------|--|
| Skin corrosion/irritation         | : Causes skin irritation.              |
| Serious eye damage/irritation     | : Causes serious eye irritation.       |
| Respiratory or skin sensitization | : May cause an allergic skin reaction. |
| Germ cell mutagenicity            | : Not classified                       |
| Carcinogenicity                   | : Suspected of causing cancer.         |

| <b>4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)</b> |                                      |
|--|--------------------------------------|
| IARC group   | 2B - Possibly carcinogenic to humans |

| <b>ethylbenzene (100-41-4)</b> |                                      |
|--------------------------------|--------------------------------------|
| IARC group                     | 2B - Possibly carcinogenic to humans |

| <b>xylene (1330-20-7)</b> |                      |
|---------------------------|----------------------|
| IARC group                | 3 - Not classifiable |

|                       |  |
|-----------------------|--|
| Reproductive toxicity | : Not classified   |
| STOT-single exposure  | : May cause respiratory irritation. May cause drowsiness or dizziness. |

| <b>4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)</b> |                                   |
|--|-----------------------------------|
| STOT-single exposure   | May cause respiratory irritation. |

# HIGH TECK E9050 HIGH SOLIDS EURO CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b> |  |
|---|--|
| STOT-single exposure  | May cause drowsiness or dizziness. May cause respiratory irritation. |

| <b>reaction mass of ethylbenzene, m-xylene and p-xylene</b> |                                   |
|---|-----------------------------------|
| STOT-single exposure  | May cause respiratory irritation. |

| <b>xylene (1330-20-7)</b> |                                   |
|---------------------------|-----------------------------------|
| STOT-single exposure      | May cause respiratory irritation. |

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

| <b>ethylbenzene (100-41-4)</b> |  |
|--------------------------------|--|
| STOT-repeated exposure         | May cause damage to organs through prolonged or repeated exposure. |

| <b>reaction mass of ethylbenzene, m-xylene and p-xylene</b> |  |
|---|--|
| NOAEL (oral, rat, 90 days)                                  | 150 mg/kg bodyweight/day ( OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), female) |
| STOT-repeated exposure                                      | May cause damage to organs through prolonged or repeated exposure.                                     |

| <b>xylene (1330-20-7)</b> |  |
|---------------------------|--|
| STOT-repeated exposure    | May cause damage to organs through prolonged or repeated exposure. |

Aspiration hazard : Not classified  
Viscosity, kinematic :  $\approx 171$  (162 – 181) mm<sup>2</sup>/s (38-48s DIN4 @ 20°C)  
Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after inhalation : May cause respiratory irritation.  
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

| <b>4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)</b> |  |
|--|--|
| LC50 fish 1  | 600 mg/l (96 h, Salmo gairdneri, Fresh water, Literature study)  |
| EC50 Daphnia 1   | > 200 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP) |
| LC50 fish 2  | > 179 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, GLP)               |

| <b>ethylbenzene (100-41-4)</b> |  |
|--------------------------------|--|
| LC50 fish 1                    | 4.2 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Salmo gairdneri, Semi-static system, Fresh water, Experimental value) |
| EC50 Daphnia 1                 | 2.1 (1.8 – 2.4) mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)                         |

| <b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1)</b> |   |
|---|---|
| LC50 fish 1   | 2.8 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)               |
| EC50 Daphnia 1  | 4 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)                       |
| ErC50 (algae)   | > 100 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration) |

| <b>reaction mass of ethylbenzene, m-xylene and p-xylene</b> |                       |
|---|-----------------------|
| LC50 fish 1   | 3300 – 4093 $\mu$ g/l |
| EC50 Daphnia 1  | 2930 – 4000 $\mu$ g/l |

| <b>xylene (1330-20-7)</b> |   |
|---------------------------|---|
| LC50 fish 1               | 2.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static renewal, Fresh water, Read-across, Lethal) |



# HIGH TECK E9050 HIGH SOLIDS EURO CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>xylene (1330-20-7)</b> |  |
|---------------------------|--|
| ErC50 (algae)             | 4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP) |

### 12.2. Persistence and degradability

| <b>4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)</b> |  |
|--|--|
| Persistence and degradability                                  | Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD)                                | 2.06 g O <sub>2</sub> /g substance   |
| Chemical oxygen demand (COD)                                   | 2.16 g O <sub>2</sub> /g substance   |
| ThOD   | 2.72 g O <sub>2</sub> /g substance   |
| BOD (% of ThOD)  | 0.76   |

| <b>ethylbenzene (100-41-4)</b>  |  |
|---------------------------------|--|
| Persistence and degradability   | Biodegradable in the soil. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 1.44 g O <sub>2</sub> /g substance                         |
| Chemical oxygen demand (COD)    | 2.1 g O <sub>2</sub> /g substance                          |
| ThOD                            | 3.17 g O <sub>2</sub> /g substance                         |

| <b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b> |   |
|---|---|
| Persistence and degradability                                   | May cause long-term adverse effects in the environment. |

| <b>xylene (1330-20-7)</b>     |  |
|-------------------------------|--|
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. |

### 12.3. Bioaccumulative potential

| <b>4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)</b> |  |
|--|--|
| BCF fish 1   | 2 – 5 (Pisces, Estimated value)  |
| Partition coefficient n-octanol/water (Log Pow)                | 1.9 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method) |
| Bioaccumulative potential                                      | Low potential for bioaccumulation (BCF < 500).   |

| <b>ethylbenzene (100-41-4)</b>                  |   |
|---|---|
| BCF fish 1                                      | 1 – 2.4 (Other, 6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value) |
| Partition coefficient n-octanol/water (Log Pow) | 3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)                                 |
| Bioaccumulative potential                       | Low potential for bioaccumulation (BCF < 500).  |

| <b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1)</b> |  |
|---|--|
| BCF fish 1  | 2658 – 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value) |
| Partition coefficient n-octanol/water (Log Pow)   | 4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)                             |

| <b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b> |                  |
|---|------------------|
| Partition coefficient n-octanol/water (Log Pow)                 | 2.1 – 6          |
| Bioaccumulative potential                                       | Not established. |

| <b>xylene (1330-20-7)</b>                       |  |
|---|--|
| BCF fish 1                                      | 7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across) |
| Partition coefficient n-octanol/water (Log Pow) | 3.2 (Read-across, 20 °C)   |
| Bioaccumulative potential                       | Low potential for bioaccumulation (BCF < 500).   |

### 12.4. Mobility in soil

| <b>4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)</b> |   |
|--|---|
| Surface tension  | 0.024 N/m (20 °C)                                     |
| Partition coefficient n-octanol/water (Log Koc)                | 2.008 (log Koc, Weight of evidence, Calculated value) |
| Ecology - soil   | Low potential for adsorption in soil.                 |

# HIGH TECK E9050 HIGH SOLIDS EURO CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>ethylbenzene (100-41-4)</b>                  |  |
|---|--|
| Surface tension                                 | 0.071 N/m (23 °C, 0.0582 g/l, EU Method A.5: Surface tension)  |
| Partition coefficient n-octanol/water (Log Koc) | 2.71 (log Koc, PCKOCWIN v1.66, QSAR)                           |
| Ecology - soil                                  | Low potential for adsorption in soil. Toxic to soil organisms. |

| <b>xylene (1330-20-7)</b>                       |   |
|---|---|
| Surface tension                                 | 28.01 – 29.76 mN/m (25 °C)  |
| Partition coefficient n-octanol/water (Log Koc) | 2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)                                      |
| Ecology - soil                                  | Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation. |

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

|                              |   |
|------------------------------|---|
| Regional legislation (waste) | : Disposal must be done according to official regulations.                                    |
| Waste treatment methods      | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |
| Additional information       | : Flammable vapors may accumulate in the container.   |

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

|                                |  |
|--------------------------------|--|
| Transport document description | : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, III |
| UN-No.(DOT)                    | : UN1263   |
| Proper Shipping Name (DOT)     | : Paint<br>including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base               |
| Class (DOT)                    | : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  |
| Packing group (DOT)            | : III - Minor Danger   |
| Hazard labels (DOT)            | : 3 - Flammable liquid   |



|   |       |
|---|-------|
| DOT Packaging Non Bulk (49 CFR 173.xxx) | : 173 |
| DOT Packaging Bulk (49 CFR 173.xxx)     | : 242 |

# HIGH TECK E9050 HIGH SOLIDS EURO CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |  |
|--|--|
| DOT Special Provisions (49 CFR 172.102)                          | : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.<br>B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.<br>IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).<br>T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)<br>TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.<br>TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP. |
| DOT Packaging Exceptions (49 CFR 173.xxx)                        | : 150  |
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : 60 L   |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)     | : 220 L  |
| DOT Vessel Stowage Location                                      | : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  |
| Other information  | : No supplementary information available.  |

### Transportation of Dangerous Goods

|   |   |
|---|---|
| Transport document description  | : UN1263 PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass), 3, III   |
| UN-No. (TDG)  | : UN1263  |
| Proper Shipping Name (Transportation of Dangerous Goods)                    | : PAINT   |
| TDG Primary Hazard Classes  | : 3 - Class 3 - Flammable Liquids   |
| Packing group   | : III - Minor Danger  |
| TDG Special Provisions  | : 59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20 per cent nitrocellulose if the nitrocellulose contains not more than 12.6 per cent nitrogen (by dry mass),142 - The following shipping names may be used to meet the requirements of Part 3 (Documentation) and Part 4 (Dangerous Goods Safety Marks) when these dangerous goods are offered for transport in the same means of containment: (a)"PAINT RELATED MATERIAL" may be used for a means of containment containing both paint and paint related material; (b)"PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE" may be used for a means of containment containing both paint, corrosive, flammable, and paint related material, corrosive, flammable; (c)"PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE" may be used for a means of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and (d)"PRINTING INK RELATED MATERIAL" may be used for a means of containment containing both printing ink and printing ink related material. SOR/2014-306 |
| Explosive Limit and Limited Quantity Index                                  | : 5 L   |
| Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index | : 60 L  |

### Transport by sea

|                                       |  |
|---------------------------------------|--|
| Transport document description (IMDG) | : UN 1263 PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass), 3, III |
| UN-No. (IMDG)                         | : 1263   |
| Proper Shipping Name (IMDG)           | : PAINT  |
| Class (IMDG)                          | : 3 - Flammable liquids  |
| Packing group (IMDG)                  | : III - substances presenting low danger   |
| Limited quantities (IMDG)             | : 5 L  |

# HIGH TECK E9050 HIGH SOLIDS EURO CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Air transport

|                                       |  |
|---------------------------------------|--|
| Transport document description (IATA) | : UN 1263 Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass), 3, III |
| UN-No. (IATA)                         | : 1263   |
| Proper Shipping Name (IATA)           | : Paint  |
| Class (IATA)                          | : 3 - Flammable Liquids  |
| Packing group (IATA)                  | : III - Minor Danger   |

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

|                            |                   |         |
|----------------------------|-------------------|---------|
| isobutyl methyl ketone     | CAS-No. 108-10-1  | 5 – 23% |
| ethylbenzene               | CAS-No. 100-41-4  | < 5%    |
| xylene, mixture of isomers | CAS-No. 1330-20-7 | 5 – 23% |

#### 4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on EPA Hazardous Air Pollutant (HAPS)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 5000 lb

#### ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on EPA Hazardous Air Pollutant (HAPS)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 1000 lb

#### reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

FRI - FRI - indicates a polymeric substance containing no free-radical initiator in its Inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

PMN - PMN - indicates a commenced PMN substance.

XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

#### solvent naphtha (petroleum), light aromatic (64742-95-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### reaction mass of ethylbenzene, m-xylene and p-xylene

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### xylene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on EPA Hazardous Air Pollutant (HAPS)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 100 lb

### 15.2. International regulations

#### CANADA

#### 4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)

Listed on the Canadian DSL (Domestic Substances List)

#### ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)

# HIGH TECK E9050 HIGH SOLIDS EURO CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**reaction mass of  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1)**

Listed on the Canadian DSL (Domestic Substances List)

**solvent naphtha (petroleum), light aromatic (64742-95-6)**

Listed on the Canadian DSL (Domestic Substances List)

**reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)**

Listed on the Canadian DSL (Domestic Substances List)

**reaction mass of ethylbenzene, m-xylene and p-xylene**

Listed on the Canadian DSL (Domestic Substances List)

**xylene (1330-20-7)**

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

### National regulations

**4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)**

Listed on IARC (International Agency for Research on Cancer)

**ethylbenzene (100-41-4)**

Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

#### HIGH TECK E9050 HIGH SOLIDS EURO CLEAR

|   |     |
|---|-----|
| U.S. - California - Proposition 65 - Carcinogens List | Yes |
|---|-----|

|   |     |
|---|-----|
| U.S. - California - Proposition 65 - Developmental Toxicity | Yes |
|---|-----|

|   |    |
|---|----|
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | No |
|---|----|

|   |    |
|---|----|
| U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No |
|---|----|

**⚠ WARNING:** This product can expose you to 4-methylpentan-2-one, isobutyl methyl ketone, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

| Component  | Carcinogenicity | Developmental toxicity | Reproductive toxicity male | Reproductive toxicity female | No significant risk level (NSRL)         | Maximum allowable dose level (MADL) |
|--|-----------------|------------------------|----------------------------|------------------------------|--|-------------------------------------|
| 4-methylpentan-2-one, isobutyl methyl ketone(108-10-1) | X               | X                      |                            |                              |  |                                     |
| ethylbenzene(100-41-4)                                 | X               |                        |                            |                              | 54 µg/day (inhalation); 41 µg/day (oral) |                                     |

| Component  | State or local regulations  |
|--|---|
| 4-methylpentan-2-one, isobutyl methyl ketone(108-10-1) | U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List |
| ethylbenzene(100-41-4)                                 | U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List |

# HIGH TECK E9050 HIGH SOLIDS EURO CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Component         | State or local regulations  |
|-------------------|---|
| xylene(1330-20-7) | U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List |

### SECTION 16: Other information


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 01/06/2020

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



SDS US GHS (GHS HazCom2012)

*The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.*