



Safety Data Sheet acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

1 Identification

- **Product identifier**
- **Trade name:** 1406 2.8 VOC GALAXY SILVER SINGLE STAGE
- **Article number:** 1406
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
HIGH TECK PRODUCTS
PO BOX 24631
WEST PALM BEACH, FLORIDA 33416
USA
877-900-8325
info@highteckproducts.com
- **Information department:** Product safety department
- **Emergency telephone number:** 800 424-9300 (Chemtrec)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

Substances and mixtures which, in contact with water, emit flammable gases 2

H225 Highly flammable liquid and vapor.

H261 In contact with water releases flammable gas.



GHS08 Health hazard

Germ Cell Mutagenicity 1B

Carcinogenicity 1B

H340 May cause genetic defects.

H350 May cause cancer.



GHS07

Skin Irritation 2

Eye Irritation 2A

Sensitization - Skin 1

Specific Target Organ Toxicity - Single Exposure 3

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

Trade name: 1406 2.8 VOC GALAXY SILVER SINGLE STAGE

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

4-chloro-alpha,alpha,alpha-trifluorotoluene
 n-butyl acetate
 Solvent naphtha (petroleum), light arom.
 acetone
 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

· **Hazard statements**

Highly flammable liquid and vapor.
 In contact with water releases flammable gas.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause an allergic skin reaction.
 May cause genetic defects.
 May cause cancer.
 May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not allow contact with water.
 Handle under inert gas. Protect from moisture.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 Take off contaminated clothing and wash it before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.
 If eye irritation persists: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use CO2, sand, extinguishing powder to extinguish.
 Store in a dry place. Store in a closed container.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

Trade name: 1406 2.8 VOC GALAXY SILVER SINGLE STAGE

(Contd. of page 2)

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 2

The substance demonstrates unusual reactivity with water.

- **HMIS-ratings (scale 0 - 4)**



Health = *2

Fire = 3

Reactivity = 2

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

123-86-4	<i>n</i> -butyl acetate	10-25%
98-56-6	4-chloro- α,α,α -trifluorotoluene	10-25%
67-64-1	acetone	2.5-10%
110-43-0	heptan-2-one	2.5-10%
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	0-10%
7429-90-5	aluminium	2.5-10%
1330-20-7	xylene	$\leq 2.5\%$
1330-20-7	xylene	$\leq 2.5\%$
64742-95-6	Solvent naphtha (petroleum), light arom.	$\leq 2.5\%$
8052-41-3	Stoddard solvent	$\leq 2.5\%$
100-41-4	ethylbenzene	$\leq 2.5\%$
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	$\leq 2.5\%$

4 First-aid measures

- **Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

Trade name: 1406 2.8 VOC GALAXY SILVER SINGLE STAGE

(Contd. of page 3)

- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Extinguishing powder. Do not use water.
CO₂. Do not use water.
Sand. Do not use water.
Special powder for metal fires. Do not use water.
CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

123-86-4	<i>n</i> -butyl acetate	5 ppm
67-64-1	acetone	200 ppm
110-43-0	heptan-2-one	150 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	9.3 mg/m ³
1330-20-7	xylene	130 ppm
8052-41-3	Stoddard solvent	300 mg/m ³
100-41-4	ethylbenzene	33 ppm
71-36-3	butan-1-ol	60 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
122-99-6	2-phenoxyethanol	1.5 ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

Trade name: 1406 2.8 VOC GALAXY SILVER SINGLE STAGE

(Contd. of page 4)

7664-38-2	phosphoric acid	3 mg/m ³
77-58-7	dibutyltin dilaurate	1.1 mg/m ³
64-17-5	ethanol	1,800 ppm
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
57-55-6	Propylene glycol	30 mg/m ³
78-83-1	butanol	150 ppm
1309-37-1	diiron trioxide	15 mg/m ³
67-56-1	methanol	530 ppm
108-38-3	m-xylene	130 ppm
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
67-63-0	propan-2-ol	400 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
70657-70-4	2-methoxypropyl acetate	50 ppm

PAC-2:

123-86-4	n-butyl acetate	200 ppm
67-64-1	acetone	3200* ppm
110-43-0	heptan-2-one	670 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	100 mg/m ³
1330-20-7	xylene	920* ppm
8052-41-3	Stoddard solvent	1,800 mg/m ³
100-41-4	ethylbenzene	1100* ppm
71-36-3	butan-1-ol	800 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
122-99-6	2-phenoxyethanol	16 ppm
7664-38-2	phosphoric acid	30 mg/m ³
77-58-7	dibutyltin dilaurate	8 mg/m ³
64-17-5	ethanol	3300* ppm
14808-60-7	Quartz (SiO ₂)	33 mg/m ³
57-55-6	Propylene glycol	1,300 mg/m ³
78-83-1	butanol	1,300 ppm
1309-37-1	diiron trioxide	360 mg/m ³
67-56-1	methanol	2,100 ppm
108-38-3	m-xylene	920 ppm
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
67-63-0	propan-2-ol	2000* ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
70657-70-4	2-methoxypropyl acetate	1,000 ppm

PAC-3:

123-86-4	n-butyl acetate	3000* ppm
67-64-1	acetone	5700* ppm
110-43-0	heptan-2-one	4000* ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m ³
1330-20-7	xylene	2500* ppm

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

Trade name: 1406 2.8 VOC GALAXY SILVER SINGLE STAGE

(Contd. of page 5)

8052-41-3	Stoddard solvent	29500** mg/m ³
100-41-4	ethylbenzene	1800* ppm
71-36-3	butan-1-ol	8000** ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
122-99-6	2-phenoxyethanol	97 ppm
7664-38-2	phosphoric acid	150 mg/m ³
77-58-7	dibutyltin dilaurate	48 mg/m ³
64-17-5	ethanol	15000* ppm
14808-60-7	Quartz (SiO ₂)	200 mg/m ³
57-55-6	Propylene glycol	7,900 mg/m ³
78-83-1	butanol	8000* ppm
1309-37-1	diiron trioxide	2,200 mg/m ³
67-56-1	methanol	7200* ppm
108-38-3	m-xylene	2500* ppm
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
67-63-0	propan-2-ol	12000** ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
70657-70-4	2-methoxypropyl acetate	5,000 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 At this time, the other constituents have no known exposure limits.

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

Trade name: 1406 2.8 VOC GALAXY SILVER SINGLE STAGE

(Contd. of page 6)

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI

110-43-0 heptan-2-one

PEL	Long-term value: 465 mg/m ³ , 100 ppm
REL	Long-term value: 465 mg/m ³ , 100 ppm
TLV	Long-term value: 50 ppm

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

8052-41-3 Stoddard solvent

PEL	Long-term value: 2900 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV	Long-term value: 100 ppm

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

Ingredients with biological limit values:**67-64-1 acetone**

BEI	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

Trade name: 1406 2.8 VOC GALAXY SILVER SINGLE STAGE

(Contd. of page 7)

1330-20-7 xylene

BEI 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

1330-20-7 xylene

BEI 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing.
 - Wash hands before breaks and at the end of work.
 - Store protective clothing separately.
 - Avoid contact with the eyes and skin.
- **Breathing equipment:**
 - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

Trade name: 1406 2.8 VOC GALAXY SILVER SINGLE STAGE

(Contd. of page 8)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	Silver
Odor:	Characteristic
Odor threshold:	Not determined.

· pH-value: Not determined (pH N/A in solvent coatings)

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55.8-56.6 °C (132.4-133.9 °F)

· Flash point: <-18 °C (<-0.4 °F)

· Flammability (solid, gaseous): Highly flammable.
Contact with water liberates extremely flammable gases.

· Auto igniting: 370 °C (698 °F)

· Decomposition temperature: Not determined.

· Ignition temperature: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	1.2 Vol %
Upper:	7.5 Vol %

· Vapor pressure at 20 °C (68 °F): 10.7 hPa (8 mm Hg)

· Vapor pressure at 50 °C (122 °F): 55 hPa (41.3 mm Hg)

· Density at 20 °C (68 °F): 1.0653 g/cm³ (8.8899 lbs/gal)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

Trade name: 1406 2.8 VOC GALAXY SILVER SINGLE STAGE

(Contd. of page 9)

· Solvent content:	
Organic solvents:	33.4-34.3 %
VOC content:	25.76-26.74 %
	366.2 g/l / 3.06 lb/gal
· Solids content: 49.9 %	
· Other information No further relevant information available.	

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Contact with water releases flammable gases.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	2B
1330-20-7	xylene	3
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
64-17-5	ethanol	1
14808-60-7	Quartz (SiO ₂)	1
1309-37-1	diiron trioxide	3
95-47-6	o-xylene	3
106-42-3	p-xylene	3
108-38-3	m-xylene	3
67-63-0	propan-2-ol	3

- **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

(Contd. on page 11)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

Trade name: 1406 2.8 VOC GALAXY SILVER SINGLE STAGE

(Contd. of page 10)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|-------------------------------------|---|
| · UN-Number | |
| · DOT, IMDG, IATA | UN3148 |
| · UN proper shipping name | |
| · DOT | Water-reactive liquid, n.o.s. (Aluminum powder) |
| · IMDG, IATA | WATER-REACTIVE LIQUID, N.O.S. (ALUMINIUM POWDER) |
| · Transport hazard class(es) | |
| · DOT | |
| · Class | 4.3 Substances which, in contact with water, emit flammable gases |



(Contd. on page 12)

USA

Safety Data Sheet


acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

Trade name: 1406 2.8 VOC GALAXY SILVER SINGLE STAGE

(Contd. of page 11)

· Label	4.3
· IMDG, IATA	
	
· Class	4.3 Substances which, in contact with water, emit flammable gases
· Label	4.3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Substances which, in contact with water, emit flammable gases
· Hazard identification number (Kemler code):	429
· EMS Number:	F-G,S-N
· Segregation groups	(SGG15) Powdered metals
· Stowage Category	E
· Stowage Code	SW2 Clear of living quarters.
· Handling Code	H1 Keep as dry as reasonably practicable
· Segregation Code	SG26 In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 5 L
· IMDG	
· Limited quantities (LQ)	500 ml
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 3148 WATER-REACTIVE LIQUID, N.O.S. (ALUMINIUM POWDER), 4.3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 13)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

Trade name: 1406 2.8 VOC GALAXY SILVER SINGLE STAGE

(Contd. of page 12)

Section 313 (Specific toxic chemical listings):

7429-90-5	aluminium
1330-20-7	xylene
100-41-4	ethylbenzene
71-36-3	butan-1-ol
122-99-6	2-phenoxyethanol
7664-38-2	phosphoric acid
67-56-1	methanol
95-47-6	o-xylene
106-42-3	p-xylene
108-38-3	m-xylene
67-63-0	propan-2-ol

TSCA (Toxic Substances Control Act):

123-86-4	n-butyl acetate	ACTIVE
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIVE
67-64-1	acetone	ACTIVE
110-43-0	heptan-2-one	ACTIVE
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	ACTIVE
7429-90-5	aluminium	ACTIVE
1330-20-7	xylene	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
8052-41-3	Stoddard solvent	ACTIVE
100-41-4	ethylbenzene	ACTIVE
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	ACTIVE
71-36-3	butan-1-ol	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
122-99-6	2-phenoxyethanol	ACTIVE
82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate	ACTIVE
7664-38-2	phosphoric acid	ACTIVE
77-58-7	dibutyltin dilaurate	ACTIVE
51274-00-1	ALPHA-IRON(III) OXIDE	ACTIVE
64-17-5	ethanol	ACTIVE
14808-60-7	Quartz (SiO ₂)	ACTIVE
57-55-6	Propylene glycol	ACTIVE
78-83-1	butanol	ACTIVE
1309-37-1	diiron trioxide	ACTIVE
67-56-1	methanol	ACTIVE
95-47-6	o-xylene	ACTIVE
106-42-3	p-xylene	ACTIVE
108-38-3	m-xylene	ACTIVE
64742-47-8	Distillates (petroleum), hydrotreated light	ACTIVE
34590-94-8	Dipropylene glycol monomethyl ether	ACTIVE
67-63-0	propan-2-ol	ACTIVE

(Contd. on page 14)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

Trade name: 1406 2.8 VOC GALAXY SILVER SINGLE STAGE

(Contd. of page 13)

· **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene
67-56-1	methanol
95-47-6	o-xylene
106-42-3	p-xylene
108-38-3	m-xylene

· **Proposition 65**

· **Chemicals known to cause cancer:**

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene
100-41-4	ethylbenzene
14808-60-7	Quartz (SiO ₂)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5	ethanol
67-56-1	methanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
1330-20-7	xylene	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D
71-36-3	butan-1-ol	D
95-47-6	o-xylene	I
106-42-3	p-xylene	I
108-38-3	m-xylene	I

· **TLV (Threshold Limit Value)**

67-64-1	acetone	A4
7429-90-5	aluminium	A4
1330-20-7	xylene	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
77-58-7	dibutyltin dilaurate	A4
64-17-5	ethanol	A3
14808-60-7	Quartz (SiO ₂)	A2
1309-37-1	diiron trioxide	A4
95-47-6	o-xylene	A4
106-42-3	p-xylene	A4
108-38-3	m-xylene	A4
67-63-0	propan-2-ol	A4

(Contd. on page 15)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

Trade name: 1406 2.8 VOC GALAXY SILVER SINGLE STAGE

(Contd. of page 14)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7 Quartz (SiO₂)

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

4-chloro-alpha,alpha,alpha-trifluorotoluene

n-butyl acetate

Solvent naphtha (petroleum), light arom.

acetone

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

· **Hazard statements**

Highly flammable liquid and vapor.

In contact with water releases flammable gas.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not allow contact with water.

Handle under inert gas. Protect from moisture.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

If eye irritation persists: Get medical advice/attention.

(Contd. on page 16)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 08/22/2019

Trade name: 1406 2.8 VOC GALAXY SILVER SINGLE STAGE

(Contd. of page 15)

Wash contaminated clothing before reuse.
 In case of fire: Use CO₂, sand, extinguishing powder to extinguish.
 Store in a dry place. Store in a closed container.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Product Safety Dept.

· **Date of preparation / last revision** 02/27/2024

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Substances and mixtures which, in contact with water, emit flammable gases 2: Substances and mixtures which in contact with water emit flammable gases – Category 2

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B

Carcinogenicity 1B: Carcinogenicity – Category 1B

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3