

Page 1/12

Printing date 02/27/2024

Reviewed on 02/26/2024

1 Identification

· Product identifier

· Trade name: 8401 2.1 VOC FAST ACTIVATOR

· Article number: 8401

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: HIGH TECK PRODUCTS PO BOX 24631 WEST PALM BEACH, FLORIDA 33416 USA

877-900-8325

info@highteckproducts.com

· Information department: Product safety department

Emergency telephone number: 800 424-9300 (Chemtrec)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Sensitization - Respiratory 1 H334 May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Carcinogenicity 2 H351 Suspected of causing cancer.



GHS07

H315 Causes skin irritation. Skin Irritation 2

Eye Irritation 2A H319 Causes serious eye irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: 8401 2.1 VOC FAST ACTIVATOR

(Contd. of page 1)

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms







GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

4-chloro-alpha.alpha.alpha-trifluorotoluene

poly(hexamethylene diisocyanate)

methyl acetate

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsina.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 3)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: 8401 2.1 VOC FAST ACTIVATOR

(Contd. of page 2)

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2 Fire = 3REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

_	components:	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	25-50%
79-20-9	methyl acetate	25-50%
28182-81-2	poly(hexamethylene diisocyanate)	25-50%
4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	2.5-10%
123-86-4	n-butyl acetate	≤2.5%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: 8401 2.1 VOC FAST ACTIVATOR

(Contd. of page 3)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:		
79-20-9	methyl acetate	250 ppm
28182-81-2	poly(hexamethylene diisocyanate)	7.8 mg/m ⁻
4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	0.02 ppm
123-86-4	n-butyl acetate	5 ppm
· PAC-2:		
79-20-9	methyl acetate	1,700 ppm
28182-81-2	poly(hexamethylene diisocyanate)	86 mg/m³
4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	0.14 ppm
123-86-4	n-butyl acetate	200 ppm
· PAC-3:		·
79-20-9	methyl acetate	10000* ppm
28182-81-2	poly(hexamethylene diisocyanate)	510 mg/m³
4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	0.6 ppm
123-86-4	n-butyl acetate	3000* ppm

7 Handling and storage

- Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: 8401 2.1 VOC FAST ACTIVATOR

(Contd. of page 4)

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

79-20-9 methyl acetate

PEL Long-term value: 610 mg/m³, 200 ppm

REL Short-term value: 760 mg/m³, 250 ppm

Long-term value: 610 mg/m³, 200 ppm

TLV Short-term value: 250 ppm Long-term value: 200 ppm

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

REL Short-term value: 0.18 mg/m³, 0.02 ppm

Long-term value: 0.045 mg/m³, 0.005 ppm

Skin

TLV Long-term value: 0.005 ppm

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Short-term value: 950 mg/m³, 200 ppm

Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 150 ppm Long-term value: 50 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

(Contd. on page 6)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: 8401 2.1 VOC FAST ACTIVATOR

· Breathing equipment:

(Contd. of page 5)

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: According to product specification

Odor: Product specificOdor threshold: Not determined.

• pH-value: Not determined (pH N/A in solvent coatings)

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 57 °C (134.6 °F)

· Flash point: -10 °C (14 °F)

· Flammability (solid, gaseous): Highly flammable.

· Decomposition temperature: Not determined.

· Ignition temperature: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/

vapor mixtures are possible.

(Contd. on page 7)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: 8401 2.1 VOC FAST ACTIVATOR

	(Contd.	of pa
Explosion limits:		
Lower:	3.1 Vol %	
Upper:	16 Vol %	
Vapor pressure at 20 °C (68 °F):	220 hPa (165 mm Hg)	
Vapor pressure at 50 °C (122 °F):	800 hPa (600 mm Hg)	
Density at 20 °C (68 °F):	1.1362 g/cm³ (9.4816 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	35.1 %	
Water:	0.5 %	
VOC content:	2.27 %	
	71.8 g/l / 0.60 lb/gal	
Solids content:	31.3 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 8)

(Contd. of page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: 8401 2.1 VOC FAST ACTIVATOR

Harmful Irritant

Carcinogenic categories

· IARC (International Agency for Research on Cancer)

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Not hazardous for water.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· **DOT, IMDG, IATA** UN1263

· UN proper shipping name

DOT Paint IMDG. IATA PAINT

(Contd. on page 9)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: 8401 2.1 VOC FAST ACTIVATOR

(Contd. of page 8)

· Transport hazard class(es)

· DOT



· Class 3 Flammable liquids

· Label 3

· IMDG, IATA



· Class 3 Flammable liquids

· Label

Packing group

· DOT, IMDG, IATA

· Environmental hazards: Not applicable.

· Special precautions for user Warning: Flammable liquids

· Hazard identification number (Kemler code): 33 · EMS Number: F-E,S-E

Stowage Category B

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

• **Quantity limitations** On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1263 PAINT, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

· Section 313 (Specific toxic chemical listings):

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

(Contd. on page 10)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: 8401 2.1 VOC FAST ACTIVATOR

(Contd. of page 9)

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

Proposition 65

· Chemicals known to cause cancer:

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

4-chloro-alpha, alpha, alpha-trifluorotoluene

poly(hexamethylene diisocyanate)

methyl acetate

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 11)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: 8401 2.1 VOC FAST ACTIVATOR

(Contd. of page 10)

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves/protective clothing/eve protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Product Safety Dept.
- · Date of preparation / last revision 02/27/2024
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Skin Irritation 2: Skin corrosion/irritation - Category 2

(Contd. on page 12)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: 8401 2.1 VOC FAST ACTIVATOR

(Contd. of page 11)

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Sensitization - Respiratory 1: Respiratory sensitisation – Category 1

Sensitization - Respiratory 1: Respiratory Sensitisation - Category 1
Sensitization - Skin 1: Skin sensitisation - Category 1
Carcinogenicity 2: Carcinogenicity - Category 2
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.