

# Safety Data Sheet

Revision Date 18-Feb-2021

# **1. IDENTIFICATION**

- · Product identifier
- · Trade name: 77130 2.1 VOC MULTI-PURPOSE CLEAR
- · Article number: 77130
- Details of the supplier of the safety data sheet • Manufacturer/Supplier:
- High Teck Products
  PO Box 24631
  West Palm Beach, FL 33416 USA
  877-900-8325
  E-Mail Address: highteck@highteck.com
- \_\_\_\_\_\_\_\_.
- · Information department: Product safety department
- Emergency telephone number:<br/>24 Hrs Emergency Contact:CHEMTREC: 800-255-3924 or 813-248-0585

# 2. HAZARDS IDENTIFICATION

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1H334May cause allergy or asthma symptoms or breathing difficulties if inhaled.Carc. 2H351Suspected of causing cancer.



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H336 May cause drowsiness or dizziness.

## · Label elements

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2) USA

(Contd. of page 1)

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: 4-chloro-alpha, alpha, alpha-trifluorotoluene poly(hexamethylene diisocyanate) acetone n-butyl acetate 3-isocyanatomethyl-3.5.5-trimethylcyclohexyl isocyanate bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause drowsiness or dizziness. Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. [In case of inadequate ventilation] wear respiratory protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Wash contaminated clothing before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3) USA

(Contd. of page 2)

- Classification system:
- NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)

HEALTH *2	Health = *2
FIRE 3	Fire = 3
REACTIVITY 0	Reactivity = 0

- Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

## 3. COMPOSITION/INFORMATION ON INGREDITENTS

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous	components:	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	25-50%
67-64-1	acetone	10-25%
123-86-4	n-butyl acetate	10-25%
28182-81-2	poly(hexamethylene diisocyanate)	2.5-10%
4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	≤2.5%
79-20-9	methyl acetate	≤2.5%
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	≤2.5%

# 4. FIRST AID MEASURE

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed* No further relevant information available.

USA (Contd. on page 4)

(Contd. of page 3)

## **5. FIRE-FIGHTING MEASURES**

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

# 6. ACCIDENTAL RELEASE MEASURE

Wear protective Environmental Dilute with plent Do not allow to Methods and m Absorb with liqu Dispose contan Ensure adequat Reference to o See Section 7 ff See Section 8 ff See Section 13 Protective Act	y of water. enter sewers/ surface or ground water. <b>naterial for containment and cleaning up:</b> iid-binding material (sand, diatomite, acid binders, universal binders ninated material as waste according to item 13. te ventilation.	s, sawdust).
PAC-1:		
67-64-1 ac		200 ppm
123-86-4 n-b	-	5 ppm
	ly(hexamethylene diisocyanate)	7.8 mg/m³
	socyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	0.02 ppm
79-20-9 me	-	250 ppm
110-43-0 he	ptan-2-one	150 ppm
108-65-6 2-r	nethoxy-1-methylethyl acetate	50 ppm
· PAC-2:		
67-64-1 ac	etone	3200* ppm
123-86-4 n-b	putyl acetate	200 ppm
28182-81-2 po	ly(hexamethylene diisocyanate)	86 mg/m <sup>3</sup>
4098-71-9 3-i	socyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	0.14 ppm
79-20-9 me	thyl acetate	1,700 ppm
110-43-0 he	ptan-2-one	670 ppm
108-65-6 2-r	nethoxy-1-methylethyl acetate	1,000 ppm
· PAC-3:		
67-64-1 ac	etone	5700* ppm
123-86-4 n-b	putyl acetate	3000* ppm
	ly(hexamethylene diisocyanate)	510 mg/m <sup>3</sup>
	socyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	0.6 ppm
79-20-9 me		10000* ppm
		(Contd. on page 5)
		USA

110-43-0 heptan-2-one 108-65-6 2-methoxy-1-methylethyl acetate (Contd. of page 4) 4000\* ppm 5000\* ppm

## 7. HANDLING AND STORAGE

#### · Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
   Protect against electrostatic charges.
   Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
   Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

#### 67-64-1 acetone

- PEL Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm
- REL Long-term value: 590 mg/m<sup>3</sup>, 250 ppm
- TLV Short-term value: 1187 mg/m<sup>3</sup>, 500 ppm Long-term value: 594 mg/m<sup>3</sup>, 250 ppm BEI

#### 123-86-4 n-butyl acetate

- PEL Long-term value: 710 mg/m<sup>3</sup>, 150 ppm
- REL Short-term value: 950 mg/m<sup>3</sup>, 200 ppm Long-term value: 710 mg/m<sup>3</sup>, 150 ppm
- TLV Short-term value: 712 mg/m<sup>3</sup>, 150 ppm Long-term value: 238 mg/m<sup>3</sup>, 50 ppm

#### 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

- REL Short-term value: 0.18 mg/m<sup>3</sup>, 0.02 ppm Long-term value: 0.045 mg/m<sup>3</sup>, 0.005 ppm Skin
- TLV Long-term value: 0.045 mg/m<sup>3</sup>, 0.005 ppm

(Contd. of page 5)

## 79-20-9 methyl acetate

PEL Long-term value: 610 mg/m<sup>3</sup>, 200 ppm

REL Short-term value: 760 mg/m<sup>3</sup>, 250 ppm Long-term value: 610 mg/m<sup>3</sup>, 200 ppm

*TLV* Short-term value: 757 mg/m<sup>3</sup>, 250 ppm Long-term value: 606 mg/m<sup>3</sup>, 200 ppm

#### · Ingredients with biological limit values:

#### 67-64-1 acetone

BEI 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)

· Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

## • Eye protection:



Tightly sealed goggles

USA (Contd. on page 7)

(Contd. of page 6)

9. PHYSICA	L AND CHEMICAL PROPERTIES
<ul> <li>Information on basic physical and c</li> <li>General Information</li> </ul>	hemical properties
<ul> <li>Appearance:</li> <li>Form:</li> <li>Color:</li> <li>Odor:</li> <li>Odor threshold:</li> </ul>	Liquid Clear Characteristic Not determined.
· pH-value:	Not determined (pH N/A in solvent coatings)
<ul> <li>Change in condition Melting point/Melting range: Boiling point/Boiling range:</li> </ul>	Undetermined. 55.8-56.6 °C (132.4-133.9 °F)
· Flash point:	<-18 °C (<-0.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C (698 °F)
<ul> <li>Decomposition temperature:</li> </ul>	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
<ul> <li>Explosion limits: Lower: Upper:</li> </ul>	1.2 Vol % 13 Vol %
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)
<ul> <li>Density at 20 °C (68 °F):</li> <li>Relative density</li> <li>Vapor density</li> <li>Evaporation rate</li> </ul>	≥1.0878 g/cm³ (≥9.0777 lbs/gal) Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with Water:</li> </ul>	Fully miscible.
· Partition coefficient (n-octanol/wate	r): Not determined.
<ul> <li>Viscosity:</li> <li>Dynamic:</li> <li>Kinematic:</li> </ul>	Not determined. Not determined.
<ul> <li>Solvent content:</li> <li>Organic solvents:</li> <li>Water:</li> <li>VOC content:</li> </ul>	33.4 % 0.0 % 11.31 % ≥123.0 g/l / ≥1.03 lb/gal
Solids content:	36.0 %
· Other information	No further relevant information available.

# **10. STABILITY AND REACTIVITY**

· Reactivity No further relevant information available.

(Contd. of page 7)

- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## **11. TOXICOLOGICAL INFORMATION**

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization:
- Sensitization possible through inhalation.
- Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

- Irritant
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

- **NTP (National Toxicology Program)** None of the ingredients is listed.
- · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## **12. ECOLOGICAL INFORMATION**

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

USA (Contd. on page 9)

2B

(Contd. of page 8)

# **13. DISPOSAL CONSIDERATION**

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

## **14. TRANSPORT INFORMATION**

	UN-Number DOT, IMDG, IATA	UN1263		
	UN proper shipping name DOT IMDG, IATA	Paint PAINT		
	Transport hazard class(es)			
	DOT			
	Class	3 Flammable liquids		
	Label	3		
	IMDG, IATA			
	Class	3 Flammable liquids		
•	Label	3		
	Packing group DOT, IMDG, IATA	11		
	Environmental hazards: Marine pollutant:	No		
•	Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids 33 F-E, <u>S-E</u> B		
	<i>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</i>	Not applicable.		
			(Contd. on page 10	) 5A

USA

(Contd. of page 9)

· Transport/Additional information:

·DOT

- · Quantity limitations
- ·IMDG
- · Limited quantities (LQ)
- Excepted quantities (EQ)

On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 1263 PAINT, 3, II

## **15. REGULATORY INFORMATION**

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
   Sara
- Section 355 (extremely hazardous substances):

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

- Section 313 (Specific toxic chemical listings): 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

· TSCA (Toxic Substances Control Act):		
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIVE
67-64-1	acetone	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
28182-81-2	poly(hexamethylene diisocyanate)	ACTIVE
4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	ACTIVE
9004-36-8	Cellulose Acetate Butyrate	ACTIVE
79-20-9	methyl acetate	ACTIVE
110-43-0	heptan-2-one	ACTIVE
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate	ACTIVE
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE

#### · Hazardous Air Pollutants

None of the ingredients is listed.

#### · Proposition 65

· Chemicals known to cause cancer:

98-56-6 4-chloro-alpha, alpha, alpha-trifluorotoluene

- Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed.

	(Contd. of page 10)
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Carcinogenic categories	
· EPA (Environmental Protection Agency) 67-64-1 acetone	1
	I
• TLV (Threshold Limit Value) 67-64-1 acetone	A4
	A4
<ul> <li>NIOSH-Ca (National Institute for Occupational Safety and Health)</li> <li>None of the ingredients is listed.</li> </ul>	
· GHS label elements	
The product is classified and labeled according to the Globally Harmonized System (GF · Hazard pictograms	1S).
GHS02 GHS07 GHS08	
· Signal word Danger	
· Hazard-determining components of labeling:	
4-chloro-alpha,alpha,alpha-trifluorotoluene poly(hexamethylene diisocyanate)	
acetone	
n-butyl acetate	
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	
· Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
May cause an allergic skin reaction.	
Suspected of causing cancer.	
May cause drowsiness or dizziness. • <b>Precautionary statements</b>	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.	
Contaminated work clothing must not be allowed out of the workplace.	
Wear protective gloves/protective clothing/eye protection/face protection.	
[In case of inadequate ventilation] wear respiratory protection.	r/shower
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water IF INHALED: Remove person to fresh air and keep comfortable for breathing.	/3/IUWE/.
	(Contd. on page 12) USA

(Contd. of page 11)

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Wash contaminated clothing before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16. OTHER INFORMATION. INCLUDING DATE OF PREPARATION OF THE LAST REVISION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

- · Contact: Product Safety Dept.
- · Date of preparation / last revision 02/18/2021 / 1
- Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

- DOT: US Department of Transportation
- IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

- Resp. Sens. 1: Respiratory sensitisation Category 1 Skin Sens. 1: Skin sensitisation – Category 1
- Carc. 2: Carcinogenicity Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3

\* Data compared to the previous version altered.

USA