

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019

1 Identification

- **Product identifier**
- **Trade name:** 1#07 CHARCOAL MIST METALLIC SINGLE STAGE
- **Article number:** 1#07
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 2 f, B
 -3 O 3 g K w · 7 o v
 k³ g - [> & g K³ [≤ V 8 g . / 3 g o o · v 7
 M b p
 .
- **Information department:** Product safety department
- **Emergency telephone number:**
 i r f 2 f p f b " 0
 , y A N z q A ,
 u R R 2 · w · 2 s o R R

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: 1407 CHARCOAL MIST METALLIC SINGLE STAGE

(Contd. of page 1)

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light arom.
 n-butyl acetate
 acetone
 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

- **Hazard statements**

Highly flammable liquid and vapor.
 Causes serious eye irritation.
 May cause an allergic skin reaction.
 May cause genetic defects.
 May cause cancer.
 May cause drowsiness or dizziness.

- **Precautionary statements**

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 If skin irritation or rash occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use for extinction: CO2, powder or water spray.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2
 Fire = 3
 Reactivity = 0

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: 1407 CHARCOAL MIST METALLIC SINGLE STAGE

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)

HEALTH	2	Health = *2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

123-86-4	<i>n</i> -butyl acetate	10-25%
98-56-6	4-chloro- α , α , α -trifluorotoluene	2.5-10%
110-43-0	heptan-2-one	2.5-10%
67-64-1	acetone	2.5-10%
7429-90-5	aluminium powder (stabilised)	2.5-10%
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	0-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	\leq 2.5%
1330-20-7	xylene	\leq 2.5%
1333-86-4	Carbon black	\leq 2.5%
100-41-4	ethylbenzene	\leq 2.5%
13463-67-7	titanium dioxide	\leq 2.5%
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	\leq 2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

USA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: 1407 CHARCOAL MIST METALLIC SINGLE STAGE

(Contd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

123-86-4	<i>n</i> -butyl acetate	5 ppm
110-43-0	heptan-2-one	150 ppm
67-64-1	acetone	200 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	9.3 mg/m ³
1330-20-7	xylene	130 ppm
1333-86-4	Carbon black	9 mg/m ³
100-41-4	ethylbenzene	33 ppm
13463-67-7	titanium dioxide	30 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
71-36-3	butan-1-ol	60 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
122-99-6	2-Phenoxyethanol	1.5 ppm
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
64-17-5	ethanol	1,800 ppm
67-56-1	methanol	530 ppm
70657-70-4	2-methoxypropyl acetate	50 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m ³
7664-38-2	phosphoric acid	3 mg/m ³
7440-50-8	copper	3 mg/m ³
100-42-5	styrene	20 ppm
8052-41-3	Stoddard solvent	300 mg/m ³
67-63-0	propan-2-ol	400 ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: 1407 CHARCOAL MIST METALLIC SINGLE STAGE

		(Contd. of page 4)
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
· PAC-2:		
123-86-4	<i>n</i> -butyl acetate	200 ppm
110-43-0	heptan-2-one	670 ppm
67-64-1	acetone	3200* ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	100 mg/m ³
1330-20-7	xylene	920* ppm
1333-86-4	Carbon black	99 mg/m ³
100-41-4	ethylbenzene	1100* ppm
13463-67-7	titanium dioxide	330 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
71-36-3	butan-1-ol	800 ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
122-99-6	2-Phenoxyethanol	16 ppm
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
64-17-5	ethanol	3300* ppm
67-56-1	methanol	2,100 ppm
70657-70-4	2-methoxypropyl acetate	1,000 ppm
77-58-7	dibutyltin dilaurate	8 mg/m ³
7664-38-2	phosphoric acid	30 mg/m ³
7440-50-8	copper	33 mg/m ³
100-42-5	styrene	130 ppm
8052-41-3	Stoddard solvent	1,800 mg/m ³
67-63-0	propan-2-ol	2000* ppm
14808-60-7	Quartz (SiO ₂)	33 mg/m ³

· PAC-3:		
123-86-4	<i>n</i> -butyl acetate	3000* ppm
110-43-0	heptan-2-one	4000* ppm
67-64-1	acetone	5700* ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m ³
1330-20-7	xylene	2500* ppm
1333-86-4	Carbon black	590 mg/m ³
100-41-4	ethylbenzene	1800* ppm
13463-67-7	titanium dioxide	2,000 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
71-36-3	butan-1-ol	8000** ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
122-99-6	2-Phenoxyethanol	97 ppm
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
64-17-5	ethanol	15000* ppm
67-56-1	methanol	7200* ppm
70657-70-4	2-methoxypropyl acetate	5,000 ppm
77-58-7	dibutyltin dilaurate	48 mg/m ³

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: 1407 CHARCOAL MIST METALLIC SINGLE STAGE

(Contd. of page 5)

7664-38-2	phosphoric acid	150 mg/m ³
7440-50-8	copper	200 mg/m ³
100-42-5	styrene	1100* ppm
8052-41-3	Stoddard solvent	29500** mg/m ³
67-63-0	propan-2-ol	12000** ppm
14808-60-7	Quartz (SiO ₂)	200 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 At this time, the other constituents have no known exposure limits.

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

110-43-0 heptan-2-one

PEL	Long-term value: 465 mg/m ³ , 100 ppm
REL	Long-term value: 465 mg/m ³ , 100 ppm
TLV	Long-term value: 233 mg/m ³ , 50 ppm

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
-----	--

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: 1407 CHARCOAL MIST METALLIC SINGLE STAGE

(Contd. of page 6)

REL Long-term value: 590 mg/m³, 250 ppm
 TLV Short-term value: 1187 mg/m³, 500 ppm
 Long-term value: 594 mg/m³, 250 ppm
 BEI

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm
 REL Short-term value: 655 mg/m³, 150 ppm
 Long-term value: 435 mg/m³, 100 ppm
 TLV Short-term value: 651 mg/m³, 150 ppm
 Long-term value: 434 mg/m³, 100 ppm
 BEI

1333-86-4 Carbon black

PEL Long-term value: 3.5 mg/m³
 REL Long-term value: 3.5* mg/m³
 *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
 TLV Long-term value: 3* mg/m³
 *inhalable fraction

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm
 REL Short-term value: 545 mg/m³, 125 ppm
 Long-term value: 435 mg/m³, 100 ppm
 TLV Long-term value: 87 mg/m³, 20 ppm
 BEI

· Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Acetone (nonspecific)

1330-20-7 xylene

BEI 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-
 Medium: end-exhaled air
 Time: not critical
 Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: 1407 CHARCOAL MIST METALLIC SINGLE STAGE

(Contd. of page 7)

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Liquid

Color:

According to product specification

· **Odor:**

Product specific

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined (pH N/A in solvent coatings)

· **Change in condition**

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

55.8-56.6 °C (132.4-133.9 °F)

· **Flash point:**

<-18 °C (<-0.4 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

370 °C (698 °F)

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: 1407 CHARCOAL MIST METALLIC SINGLE STAGE

(Contd. of page 8)

· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
· Density at 20 °C (68 °F):	1.0904 g/cm ³ (9.0994 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	32.7 %
VOC content:	26.42 %
	174.5 g/l / 1.46 lb/gal
Solids content:	53.9 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: 1407 CHARCOAL MIST METALLIC SINGLE STAGE

(Contd. of page 9)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
1333-86-4	Carbon black	2B
100-41-4	ethylbenzene	2B
13463-67-7	titanium dioxide	2B
64-17-5	ethanol	1
100-42-5	styrene	2B
67-63-0	propan-2-ol	3
14808-60-7	Quartz (SiO ₂)	1

- **NTP (National Toxicology Program)**

100-42-5	styrene	R
14808-60-7	Quartz (SiO ₂)	K

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

USA

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019



Trade name: 1407 CHARCOAL MIST METALLIC SINGLE STAGE

(Contd. of page 10)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| UN-Number | UN1263 |
| DOT, IMDG, IATA | UN1263 |
| UN proper shipping name | Paint |
| DOT | PAINT |
| IMDG, IATA | PAINT |
| Transport hazard class(es) | |
| DOT | |
|  | |
| Class | 3 Flammable liquids |
| Label | 3 |
| IMDG, IATA | |
|  | |
| Class | 3 Flammable liquids |
| Label | 3 |
| Packing group | II |
| DOT, IMDG, IATA | II |
| Environmental hazards: | Not applicable. |
| Special precautions for user | Warning: Flammable liquids |
| Danger code (Kemler): | 33 |
| EMS Number: | F-E, S-E |
| Stowage Category | B |
| Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| Transport/Additional information: | |
| DOT | |
| Quantity limitations | On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L |

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: 1407 CHARCOAL MIST METALLIC SINGLE STAGE

(Contd. of page 11)

<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN 1263 PAINT, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
100-41-4	ethylbenzene
71-36-3	butan-1-ol
122-99-6	2-Phenoxyethanol
67-56-1	methanol
7664-38-2	phosphoric acid
7440-50-8	copper
100-42-5	styrene
67-63-0	propan-2-ol

- **TSCA (Toxic Substances Control Act):**

123-86-4	n-butyl acetate	ACTIVE
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIVE
110-43-0	heptan-2-one	ACTIVE
67-64-1	acetone	ACTIVE
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
1330-20-7	xylene	ACTIVE
1333-86-4	Carbon black	ACTIVE
100-41-4	ethylbenzene	ACTIVE
13463-67-7	titanium dioxide	ACTIVE
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
71-36-3	butan-1-ol	ACTIVE
108-83-8	2,6-dimethylheptan-4-one	ACTIVE
122-99-6	2-Phenoxyethanol	ACTIVE
34590-94-8	Dipropylene glycol monomethyl ether	ACTIVE
64-17-5	ethanol	ACTIVE
147-14-8	Phthalocyanine Blue	ACTIVE
82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate	ACTIVE

(Contd. on page 13)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: 1407 CHARCOAL MIST METALLIC SINGLE STAGE

(Contd. of page 12)

67-56-1	methanol	ACTIVE
77-58-7	dibutyltin dilaurate	ACTIVE
7664-38-2	phosphoric acid	ACTIVE
7440-50-8	copper	ACTIVE
100-42-5	styrene	ACTIVE
8052-41-3	Stoddard solvent	ACTIVE
67-63-0	propan-2-ol	ACTIVE
14808-60-7	Quartz (SiO ₂)	ACTIVE

· **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene
67-56-1	methanol
100-42-5	styrene

· **Proposition 65**

· **Chemicals known to cause cancer:**

98-56-6	4-chloro-alpha, alpha, alpha-trifluorotoluene
1333-86-4	Carbon black
100-41-4	ethylbenzene
13463-67-7	titanium dioxide
100-42-5	styrene
14808-60-7	Quartz (SiO ₂)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5	ethanol
67-56-1	methanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D
71-36-3	butan-1-ol	D
7440-50-8	copper	D

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
1330-20-7	xylene	A4
1333-86-4	Carbon black	A4
100-41-4	ethylbenzene	A3
13463-67-7	titanium dioxide	A4
64-17-5	ethanol	A3
77-58-7	dibutyltin dilaurate	A4

(Contd. on page 14)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: 1407 CHARCOAL MIST METALLIC SINGLE STAGE

(Contd. of page 13)

100-42-5	styrene	A4
67-63-0	propan-2-ol	A4
14808-60-7	Quartz (SiO ₂)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
13463-67-7	titanium dioxide
14808-60-7	Quartz (SiO ₂)

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light arom.

n-butyl acetate

acetone

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

· **Hazard statements**

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

(Contd. on page 15)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: 1407 CHARCOAL MIST METALLIC SINGLE STAGE

(Contd. of page 14)

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Product Safety Dept.

· **Date of preparation / last revision** 08/23/2019 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3