Printing date 12/17/2019 Revised On 12/17/2019

1 Identification of the substance and manufacturer

Trade name: 9983 PAINTABLE RUBBER UNDERCOAT

Product code: NO99830000

Paint and coatings application. Recommended use:

Uses advised against: Any that differs from the recommended use.

High Teck Products Manufacturer/Supplier: P.Ö. Box 24631

West Palm Beach, FL 33416

United States

Customer Service: 877-900-8235 email: info@highteckproducts.com ChemTrec: 800-424-9300

Emergency telephone number:

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated. Press. Gas

Skin Irrit. 2 H315 Causes skin irritation.

Repr. 1B H360 May damage fertility or the unborn child.

STOT SE 3 H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure. STOT RE 2

GHS Hazard pictograms

Precautionary statements







GHS02 GHS04 GHS07 GHS08

Signal word Danger

Extremely flammable aerosol. **Hazard statements**

Contains gas under pressure; may explode if heated.

Causes skin irritation.

May damage fertility or the unborn child.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Gildinida Boodi phoni		The product to a mixture of the capetanece noted below with normazaradae additione.	
Dangerous components:			
1317-65-3	Calcium Carbonate		25.2%
8052-42-4	Asphalt		18.0%
108-88-3	Toluene		16.2%
	VM&P Naphtha		13.5%
14807-96-6	Talc		8.1%
74-98-6	propane		6.3%
106-97-8	n-butane		3.7%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact: After eye contact: After swallowing: Rinse opened eye for several minutes under running water. Then consult a doctor.

Rinse mouth with water. Do not induce vomiting.

Most important symptoms and Dizziness effects:

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Printing date 12/17/2019 Revised On 12/17/2019

Trade name: 9983 PAINTABLE RUBBER UNDERCOAT

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents:

Special hazards:

Protective equipment for

firefighters:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Methods and material for

containment and cleaning up:

Use respiratory protective device against the effects of fumes/dust/aerosol.

Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling

Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

8052-42-4 Asphalt

REL (USA) Ceiling limit value: 5* mg/m³
*15-min; See Pocket Guide App. A

TLV (USA) Long-term value: 0.5* mg/m³

*inh. fraction; as benzene-soluble aerosol; BEIp

108-88-3 Toluene

PEL (USA) Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

10-min peak per 8-hr shift

REL (USA) Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm

Long-term value: 75 mg/m³, 20 ppm TLV (USA)

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm

REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) refer to Appendix F inTLVs&BEIs book; D, EX

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

Ingredients with biological limit values:

8052-42-4 Asphalt

BEI (USA)

Medium: urine

Time: end of shift at end of workweek

Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)

Immediately remove all soiled and contaminated clothing. Hygienic protection: Wash hands after use.

Store protective clothing separately.

Avoid contact with the skin. Avoid contact with the eyes and skin.

Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn.

If you suspect overexposure conditions exist, please consult an authority on chemical hygeine. Hand protection:

Nitrile gloves

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol.

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet

Printing date 12/17/2019 Revised On 12/17/2019

Trade name: 9983 PAINTABLE RUBBER UNDERCOAT

Odor: Aromatic Odor threshold: Not determined.

nH-value: Not determined Melting point/Melting range Undetermined. Boiling point: -44 °C (-47.2 °F) Flash point: -19 °C (-2.2 °F)

Flammability (solid, gas): Extremely flammable. Decomposition temperature: Not determined.

Product is not self-igniting. Auto igniting:

In use, may form flammable/explosive vapour-air mixture.

Danger of explosion: Lower Explosion Limit: 1.1 Vol % **Upper Explosion Limit:** 7 Vol %

Not determined. Vapor pressure:

Between 0.77 and 0.85 (Water equals 1.00) **Relative Density:**

Vapor density Not determined. Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined. Not determined. Solubility: Not determined. Viscosity:

VOC content (less exempt solvents): 23.5 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Not fully evaluated. Chemical stability:

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

Information on toxicological effects: No data available.

Skin effects: Irritant to skin and mucous membranes.

Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Hazardous for water, do not empty into drains.

Aquatic toxicity: Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated Other information:

solvents.

Bioaccumulative potential: No further relevant information available. No further relevant information available. Mobility in soil: Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN1950 **UN-Number** DOT N/A

Consumer_Commodity ORM-D DOT

Aerosols, flammable

ADR 1950 AEROSOLS

Transport hazard class(es):

Class

Special precautions for user: Warning: Gases

EMS Number: F-D.S-Ŭ

Packaging Group:

(Contd. on page 4)

Safety Data Sheet

Printing date 12/17/2019 Revised On 12/17/2019

Trade name: 9983 PAINTABLE RUBBER UNDERCOAT

UN "Model Regulation": UN 1950 AEROSOLS, 2.1 (Contd. of page 3)

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

Toxic Substances Control Act

All hazardous ingredients are found on the inventory list of substances.

(TSCA): Canadian Domestic Substances List (DSL):

All ingredients are listed or exempted.

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

1333-86-4 Carbon black

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

EPA:

None of the ingredients is listed.

16 Other information

Contact: Regulatory Affairs