



# Safety Data Sheet

## Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name** : Universal Urethane Reducer - Slow 7730

#### Recommended use of the chemical and restrictions on use

Recommended use : Reserved for industrial and professional use.

#### Manufacturer or supplier's details

**Company** : High Teck Products  
**Address** : PO Box 24631  
West Palm Beach, FL 33416  
USA

#### Emergency telephone number:

High Teck Products:-877-900-8325

**Additional Information:** : Regulatory Information Number: 877-900-8325  
Email: [highteck@highteck.com](mailto:highteck@highteck.com)

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 2

Skin irritation : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2 (Central nervous system, Kidney, Liver)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2 (Auditory system, Eyes)

Aspiration hazard : Category 1

#### GHS label elements

Hazard pictograms : 

Signal word : Danger



## Safety Data Sheet

### Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

- Hazard statements : H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H361 Suspected of damaging fertility or the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
- Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
**Disposal:**



# Safety Data Sheet

## Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

CAS-No.	Chemical name	Weight percent
67-64-1	Acetone	30 - 50
68410-97-9 / 64742-49-0 / 64742-89-8	Distillates, pet, lt dist hydrotreat process, low-boil AND/OR Naphtha (pet), hydrotreated lt AND/OR Solvent naphtha (pet), lt aliph.	10 - 20
108-88-3	Toluene	10 - 20
108-65-6	Glycol ether PM acetate	10 - 20
110-19-0	Isobutyl acetate	10 - 20
123-86-4	n-Butyl acetate	5 - 10
1330-20-7	Mixed xylenes	5 - 10
100-41-4	**Ethylbenzene	1 - 5

Actual concentration is withheld as a trade secret

Any Concentration shown as a range is due to batch variation.

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.



## Safety Data Sheet

### Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

If symptoms persist, call a physician.  
Take victim immediately to hospital.

---

#### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides  
Unburned hydrocarbons  
Smoke  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

---

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).



# Safety Data Sheet

## Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
67-64-1	Acetone	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA Z-1
		TWA	750 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
		STEL	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA P0
		STEL	750 ppm 1,780 mg/m <sup>3</sup>	CAL PEL
		C	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m <sup>3</sup>	CAL PEL



# Safety Data Sheet

## Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

68410-97-9 / 64742-49-0 / 64742-89-8	Distillates, pet, lt dist hydrotreat process, low-boil AND/OR Naphtha (pet), hydrotreated lt AND/OR Solvent naphtha (pet), lt aliph.	TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	400 ppm 1,600 mg/m <sup>3</sup>	OSHA P0
108-88-3	Toluene	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m <sup>3</sup>	NIOSH REL
		ST	150 ppm 560 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		TWA	100 ppm 375 mg/m <sup>3</sup>	OSHA P0
		STEL	150 ppm 560 mg/m <sup>3</sup>	OSHA P0
		PEL	10 ppm 37 mg/m <sup>3</sup>	CAL PEL
		C	500 ppm	CAL PEL
		STEL	150 ppm 560 mg/m <sup>3</sup>	CAL PEL
108-65-6	Glycol ether PM acetate	TWA	50 ppm	US WEEL
		PEL	100 ppm 541 mg/m <sup>3</sup>	CAL PEL
		STEL	150 ppm 811 mg/m <sup>3</sup>	CAL PEL
110-19-0	Isobutyl acetate	TWA	150 ppm	ACGIH
		TWA	150 ppm 700 mg/m <sup>3</sup>	NIOSH REL
		TWA	150 ppm 700 mg/m <sup>3</sup>	OSHA Z-1
		TWA	150 ppm 700 mg/m <sup>3</sup>	OSHA P0
123-86-4	n-Butyl acetate	TWA	150 ppm	ACGIH
		STEL	200 ppm	ACGIH
		ST	200 ppm 950 mg/m <sup>3</sup>	NIOSH REL
		TWA	150 ppm 710 mg/m <sup>3</sup>	NIOSH REL
		TWA	150 ppm 710 mg/m <sup>3</sup>	OSHA Z-1
		TWA	150 ppm 710 mg/m <sup>3</sup>	OSHA P0
		STEL	200 ppm 950 mg/m <sup>3</sup>	OSHA P0
		PEL	150 ppm 710 mg/m <sup>3</sup>	CAL PEL
		STEL	200 ppm 950 mg/m <sup>3</sup>	CAL PEL
		TWA	50 ppm	ACGIH



# Safety Data Sheet

## Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

		STEL	150 ppm	ACGIH
1330-20-7	Mixed xylenes	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m3	CAL PEL
		C	300 ppm	CAL PEL
		PEL	100 ppm 435 mg/m3	CAL PEL
100-41-4	**Ethylbenzene	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
		PEL	5 ppm 22 mg/m3	CAL PEL
		STEL	30 ppm 130 mg/m3	CAL PEL

### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

In the case of vapour formation use a respirator with an approved filter.

### Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.



## Safety Data Sheet

### Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : No data available
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Freezing Point : No data available
- Boiling Point : No data available
- Flash point : < 23 °C (73 °F)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available
- Relative density : 0.820 - 0.836 @ 20 °C (68 °F)  
Reference substance: (water = 1)
- Density : 0.828 g/cm<sup>3</sup> @ 20 °C (68 °F)
- Water solubility : No data available
- Solubility in other solvents : No data available
- Partition coefficient: n-octanol/water : No data available
- Auto-ignition temperature : No data available
- Thermal decomposition : No data available





# Safety Data Sheet

## Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources.
Incompatible materials	: Acids Amines Bases Copper Nitrogen oxides (NO <sub>x</sub> ) Oxidizing agents

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

##### Product:

Acute inhalation toxicity : Acute toxicity estimate: 187.08 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

##### Components:

##### **1330-20-7:**

Acute inhalation toxicity : LC50 (Rat, male): 6700 ppm  
Exposure time: 4 h  
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg  
Assessment: The component/mixture is moderately toxic after single contact with skin.

#### Skin corrosion/irritation

##### Components:

**68410-97-9 / 64742-49-0 / 64742-89-8:**



# Safety Data Sheet

## Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

Species: Rabbit  
Exposure time: 4 h  
Result: Irritating to skin.

### **108-88-3:**

Species: Rabbit  
Exposure time: 4 h  
Result: Irritating to skin.

### **1330-20-7:**

Species: Rabbit  
Exposure time: 24 h  
Result: Irritating to skin.

## **Serious eye damage/eye irritation**

### **Components:**

#### **67-64-1:**

Species: Rabbit  
Result: Irritating to eyes.  
Exposure time: 24 h

#### **108-88-3:**

Species: Rabbit  
Result: Irritating to eyes.

#### **1330-20-7:**

Species: Rabbit  
Result: Irritating to eyes.

## **Germ cell mutagenicity**

### **Components:**

#### **68410-97-9 / 64742-49-0 / 64742-89-8:**

Germ cell mutagenicity - Assessment : Mutagenicity classification not possible from current data

#### **108-88-3:**

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

## **Carcinogenicity**

### **Components:**

#### **68410-97-9 / 64742-49-0 / 64742-89-8:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

#### **108-88-3:**

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

### **IARC**

Group 2B: Possibly carcinogenic to humans



## Safety Data Sheet

### Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

100-41-4

\*\*Ethylbenzene

#### OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### Reproductive toxicity

##### Components:

##### **68410-97-9 / 64742-49-0 / 64742-89-8:**

Reproductive toxicity - Assessment

Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

Teratogenicity - Assessment : Embryotoxicity classification not possible from current data.

##### **108-88-3:**

Effects on foetal development

: Species: Rat  
Application Route: inhalation (vapour)  
Dose: 0, 250, 750, 1500, 3000 ppm  
Duration of Single Treatment: 10 d  
Frequency of Treatment: 6 hr/day  
General Toxicity Maternal: NOAEC: 750 ppm  
Developmental Toxicity: NOAEC: 750 ppm  
Symptoms: Maternal toxicity, Reduced body weight, Skeletal malformations

Teratogenicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

Reproductive toxicity - Assessment

No toxicity to reproduction

#### STOT - single exposure

##### Components:

##### **67-64-1:**

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

##### **68410-97-9 / 64742-49-0 / 64742-89-8:**

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.



## Safety Data Sheet

# Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

### **108-88-3:**

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

### **110-19-0:**

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

### **123-86-4:**

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

### **1330-20-7:**

Assessment: May cause respiratory irritation.

## **STOT - repeated exposure**

### **Components:**

#### **108-88-3:**

Exposure routes: Inhalation

Target Organs: Auditory system, Eyes

Assessment: May cause damage to organs through prolonged or repeated exposure., The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

#### **1330-20-7:**

Target Organs: Central nervous system, Kidney, Liver

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

## **Aspiration toxicity**

### **Components:**

#### **68410-97-9 / 64742-49-0 / 64742-89-8:**

May be fatal if swallowed and enters airways.

#### **108-88-3:**

May be fatal if swallowed and enters airways.

#### **1330-20-7:**

May be fatal if swallowed and enters airways.

## **Further information**

### **Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.



## Safety Data Sheet

### Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

#### SECTION 12. ECOLOGICAL INFORMATION

##### Ecotoxicity

##### Components:

##### **68410-97-9 / 64742-49-0 / 64742-89-8:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 10 mg/l  
Exposure time: 96 h
- LC50 (Oncorhynchus mykiss (rainbow trout)): 8.2 mg/l  
Exposure time: 96 h  
Test Type: semi-static test
- LC50 (Pimephales promelas (fathead minnow)): 8.2 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.5 mg/l  
Exposure time: 48 h  
Test Type: Immobilization
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l  
Exposure time: 72 h
- EC50 (Pseudokirchneriella subcapitata (green algae)): 3.7 mg/l  
Exposure time: 96 h  
Test Type: static test
- Toxicity to fish (Chronic toxicity) : NOELR (Pimephales promelas (fathead minnow)): 2.6 mg/l  
Exposure time: 14 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 2.6 mg/l  
Exposure time: 21 d
- Chronic aquatic toxicity- Assessment : Toxic to aquatic life with long lasting effects.

##### **108-88-3:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.5 mg/l  
Exposure time: 96 h  
Test Type: flow-through test
- Toxicity to daphnia and other aquatic invertebrates : LC50 (Ceriodaphnia dubia): 3.78 mg/l  
Exposure time: 48 h  
Test Type: Renewal
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.74 mg/l  
Exposure time: 7 d



## Safety Data Sheet

### Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

Acute aquatic toxicity- Assessment : Toxic to aquatic life.

Chronic aquatic toxicity- Assessment : Harmful to aquatic life with long lasting effects.

#### **110-19-0:**

Toxicity to fish : LC50 (*Oryzias latipes* (Japanese medaka)): 16.6 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : (*Daphnia magna* (Water flea)): 25 mg/l  
Exposure time: 48 h  
Test Type: static test

Acute aquatic toxicity- Assessment : Harmful to aquatic life.

Chronic aquatic toxicity- Assessment : This product has no known ecotoxicological effects.

#### **123-86-4:**

Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): 18 mg/l  
Exposure time: 96 h  
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 44 mg/l  
Exposure time: 48 h  
Test Type: static test

Acute aquatic toxicity- Assessment : Harmful to aquatic life.

Chronic aquatic toxicity- Assessment : This product has no known ecotoxicological effects.

#### **Persistence and degradability**

No data available

#### **Bioaccumulative potential**

#### **Components:**

##### **68410-97-9 / 64742-49-0 / 64742-89-8:**

Partition coefficient: n-octanol/water : log Pow: 2.13 - 4.85 (25 °C)

##### **108-88-3:**

Partition coefficient: n-octanol/water : log Pow: 2.73 (20 °C)  
pH: 7

#### **Mobility in soil**

No data available



# Safety Data Sheet

## Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

### Other adverse effects

#### Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life.  
Harmful to aquatic life with long lasting effects.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

## SECTION 14. TRANSPORT INFORMATION

### DOT (Department of Transportation):

UN1263, PAINT RELATED MATERIAL, 3, II

### IATA (International Air Transport Association):

UN1263, PAINT RELATED MATERIAL, 3, II

### IMDG (International Maritime Dangerous Goods):

UN1263, PAINT RELATED MATERIAL, 3, II, Flash Point:23 °C(73 °F)

---

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Mixed xylenes	1330-20-7	100	1700



## Safety Data Sheet

### Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

Toluene	108-88-3	1000	9090
---------	----------	------	------

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard

**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

108-88-3	Toluene
1330-20-7	Mixed xylenes
100-41-4	**Ethylbenzene

#### Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

108-88-3	Toluene
1330-20-7	Mixed xylenes
100-41-4	**Ethylbenzene

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

67-64-1	Acetone
108-88-3	Toluene
110-19-0	Isobutyl acetate
123-86-4	n-Butyl acetate
1330-20-7	Mixed xylenes
100-41-4	**Ethylbenzene

#### Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

108-88-3	Toluene
110-19-0	Isobutyl acetate
123-86-4	n-Butyl acetate
1330-20-7	Mixed xylenes
100-41-4	**Ethylbenzene
71-43-2	**Benzene
91-20-3	**Naphthalene

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

108-88-3	Toluene
123-86-4	n-Butyl acetate
1330-20-7	Mixed xylenes
100-41-4	**Ethylbenzene
71-43-2	**Benzene
91-20-3	**Naphthalene

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307





## Safety Data Sheet

### Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

108-88-3 Toluene  
100-41-4 \*\*Ethylbenzene

#### Massachusetts Right To Know

67-64-1 Acetone  
108-88-3 Toluene  
110-19-0 Isobutyl acetate  
123-86-4 n-Butyl acetate  
1330-20-7 Mixed xylenes  
100-41-4 \*\*Ethylbenzene  
71-43-2 \*\*Benzene

#### Pennsylvania Right To Know

67-64-1 Acetone  
68410-97-9 /  
64742-49-0 /  
64742-89-8 Distillates, pet, lt dist hydrotreat process,  
low-boil AND/OR Naphtha (pet), hy-  
drotreated lt AND/OR Solvent naphtha  
(pet), lt aliph.  
108-88-3 Toluene  
108-65-6 Glycol ether PM acetate  
110-19-0 Isobutyl acetate  
123-86-4 n-Butyl acetate  
1330-20-7 Mixed xylenes  
100-41-4 \*\*Ethylbenzene  
98-82-8 \*\*Cumene  
71-43-2 \*\*Benzene

#### California Prop 65

**⚠ WARNING:** This product can expose you to chemicals including \*\*Naphthalene, \*\*Benzene, \*\*Cumene, \*\*Ethylbenzene, which is/are known to the State of California to cause cancer, and Toluene, \*\*Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory  
DSL : All components of this product are on the Canadian DSL  
AICS : not determined  
NZIoC : not determined  
ENCS : not determined  
KECI : not determined  
PICCS : not determined  
IECSC : not determined



# Safety Data Sheet


## Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

### SECTION 16. OTHER INFORMATION

#### NFPA:



#### HMIS III:

<b>HEALTH</b>	<b>3*</b>
<b>FLAMMABILITY</b>	<b>3</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
 2 = Moderate, 3 = High  
 4 = Extreme, \* = Chronic

Revision Date : 01/24/2023

Material number:  
 16204002,

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research	TLV	Threshold Limit Value



## Safety Data Sheet

### Universal Urethane Reducer - Slow 7730

Version 1.2

Revision Date: 01/24/2023

	on Cancer		
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		