

**Safety Data Sheet**
acc. to OSHA HCS

Printing date 11/11/2021

Reviewed on 11/11/2021

1 Identification**· Product identifier**

HIGH TECK PRODUCTS
PO BOX 24631
WEST PALM BEACH
33416 - USA
T 877-900-8325
info@nationaloak.com
Emergency: 800 255-3924 (Chemtrec)

2 Hazard(s) identification**· Classification of the substance or mixture**

GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Label elements**· GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

USA



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/11/2021

Reviewed on 11/11/2021

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word *Danger*

· Hazard-determining components of labeling:

4-chloro-alpha,alpha,alpha-trifluorotoluene
Solvent naphtha (petroleum), light arom.
Stoddard solvent
titanium dioxide
2-butanone oxime

· Hazard statements

Highly flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.

· Precautionary statements

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

USA



Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2021

Reviewed on 11/11/2021

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	25-50%
108-65-6	2-methoxy-1-methylethyl acetate	10-25%
107-87-9	pentan-2-one	2.5-10%
110-43-0	heptan-2-one	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%
13463-67-7	titanium dioxide	2.5-10%
7779-90-0	trizinc bis(orthophosphate)	≤2.5%
95-63-6	1,2,4-trimethylbenzene	≤2.5%
7727-43-7	barium sulphate, natural	≤2.5%
108-10-1	4-methylpentan-2-one	≤2.5%
100-41-4	ethylbenzene	≤2.5%
1333-86-4	Carbon black	≤2.5%
8052-41-3	Stoddard solvent	≤2.5%
96-29-7	2-butanone oxime	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 4)

USA



Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2021

Reviewed on 11/11/2021

(Contd. of page 3)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
107-87-9	pentan-2-one	150 ppm
110-43-0	heptan-2-one	150 ppm
13463-67-7	titanium dioxide	30 mg/m ³
7779-90-0	trizinc bis(orthophosphate)	12 mg/m ³
95-63-6	1,2,4-trimethylbenzene	140 ppm
7727-43-7	barium sulphate, natural	15 mg/m ³
108-10-1	4-methylpentan-2-one	75 ppm
100-41-4	ethylbenzene	33 ppm
108-38-3	m-xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
1333-86-4	Carbon black	9 mg/m ³
8052-41-3	Stoddard solvent	300 mg/m ³
96-29-7	2-butanone oxime	30 ppm

(Contd. on page 5)

USA



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/11/2021

Reviewed on 11/11/2021

		(Contd. of page 4)
1330-20-7	xylene	130 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m ³
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
149-57-5	2-ethylhexanoic acid	15 mg/m ³
122-99-6	2-Phenoxyethanol	1.5 ppm
7664-38-2	phosphoric acid	3 mg/m ³
· PAC-2:		
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
107-87-9	pentan-2-one	830 ppm
110-43-0	heptan-2-one	670 ppm
13463-67-7	titanium dioxide	330 mg/m ³
7779-90-0	trizinc bis(orthophosphate)	36 mg/m ³
95-63-6	1,2,4-trimethylbenzene	360 ppm
7727-43-7	barium sulphate, natural	170 mg/m ³
108-10-1	4-methylpentan-2-one	500 ppm
100-41-4	ethylbenzene	1100* ppm
108-38-3	m-xylene	920 ppm
123-86-4	n-butyl acetate	200 ppm
1333-86-4	Carbon black	99 mg/m ³
8052-41-3	Stoddard solvent	1,800 mg/m ³
96-29-7	2-butanone oxime	56 ppm
1330-20-7	xylene	920* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m ³
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
149-57-5	2-ethylhexanoic acid	99 mg/m ³
122-99-6	2-Phenoxyethanol	16 ppm
7664-38-2	phosphoric acid	30 mg/m ³
· PAC-3:		
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
107-87-9	pentan-2-one	5000* ppm
110-43-0	heptan-2-one	4000* ppm
13463-67-7	titanium dioxide	2,000 mg/m ³
7779-90-0	trizinc bis(orthophosphate)	220 mg/m ³
95-63-6	1,2,4-trimethylbenzene	480 ppm
7727-43-7	barium sulphate, natural	990 mg/m ³
108-10-1	4-methylpentan-2-one	3000* ppm
100-41-4	ethylbenzene	1800* ppm
108-38-3	m-xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm
1333-86-4	Carbon black	590 mg/m ³
8052-41-3	Stoddard solvent	29500** mg/m ³
96-29-7	2-butanone oxime	250 ppm
1330-20-7	xylene	2500* ppm
		(Contd. on page 6)

USA



Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2021

Reviewed on 11/11/2021

		(Contd. of page 5)
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
149-57-5	2-ethylhexanoic acid	590 mg/m ³
122-99-6	2-Phenoxyethanol	97 ppm
7664-38-2	phosphoric acid	150 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

108-65-6 2-methoxy-1-methylethyl acetate	
WEEL	Long-term value: 50 ppm
107-87-9 pentan-2-one	
PEL	Long-term value: 700 mg/m ³ , 200 ppm
REL	Long-term value: 530 mg/m ³ , 150 ppm
TLV	Short-term value: 150 ppm
110-43-0 heptan-2-one	
PEL	Long-term value: 465 mg/m ³ , 100 ppm
REL	Long-term value: 465 mg/m ³ , 100 ppm
TLV	Long-term value: 50 ppm
95-63-6 1,2,4-trimethylbenzene	
REL	Long-term value: 125 mg/m ³ , 25 ppm

(Contd. on page 7)

USA



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/11/2021

Reviewed on 11/11/2021

(Contd. of page 6)

TLV	Long-term value: (25) NIC-10 ppm NIC-A4
7727-43-7 barium sulphate, natural	
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 5* mg/m ³ *inhalable fraction; E
108-10-1 4-methylpentan-2-one	
PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV	Short-term value: 75 ppm Long-term value: 20 ppm BEI, A3
100-41-4 ethylbenzene	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 NIC-20 ppm BEI, A3, NIC: OTO, BEI, A3
1333-86-4 Carbon black	
PEL	Long-term value: 3.5 mg/m ³
REL	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m ³ *inhalable fraction, A3
8052-41-3 Stoddard solvent	
PEL	Long-term value: 2900 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV	Long-term value: 100 ppm
96-29-7 2-butanone oxime	
WEEL	Long-term value: 10 ppm DSEN
Ingredients with biological limit values:	
108-10-1 4-methylpentan-2-one	
BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
100-41-4 ethylbenzene	
BEI	0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

(Contd. on page 8)

USA



Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2021

Reviewed on 11/11/2021

(Contd. of page 7)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

*

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

- **Form:** Liquid
- **Color:** According to product specification
- **Odor:** Product specific
- **Odor threshold:** Not determined.

· **pH-value:** Not determined (pH N/A in solvent coatings)

· **Change in condition**

- **Melting point/Melting range:** Undetermined.
- **Boiling point/Boiling range:** 101.7 °C (215.1 °F)

(Contd. on page 9)

USA



Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2021

Reviewed on 11/11/2021

(Contd. of page 8)

· Flash point:	7 °C (44.6 °F)
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.5 Vol %
Upper:	10.8 Vol %
· Vapor pressure at 20 °C (68 °F):	3.4 hPa (2.6 mm Hg)
· Density at 20 °C (68 °F):	1.34 g/cm ³ (11.1823 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	37.0 %
VOC content:	37.14 %
	238.3 g/l / 1.99 lb/gal
· Solids content:	51.7 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 10)



Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2021

Reviewed on 11/11/2021

(Contd. of page 9)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

7779-90-0 trizinc bis(orthophosphate)

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

95-63-6 1,2,4-trimethylbenzene

Oral	LD50	5,000 mg/kg (rat)
------	------	-------------------

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rab)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	2B
14807-96-6	Talc (Mg3H2(SiO3)4)	3
13463-67-7	titanium dioxide	2B
108-10-1	4-methylpentan-2-one	2B
100-41-4	ethylbenzene	2B
95-47-6	o-xylene	3
106-42-3	p-xylene	3
108-38-3	m-xylene	3
1333-86-4	Carbon black	2B
1330-20-7	xylene	3
136-52-7	cobalt(II) 2-ethylhexanoate	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

USA

(Contd. on page 11)



Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2021

Reviewed on 11/11/2021

(Contd. of page 10)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**
· **DOT, IMDG, IATA** UN1263

· **UN proper shipping name**
· **DOT** Paint
· **IMDG, IATA** PAINT

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids

(Contd. on page 12)

USA




Safety Data Sheet

acc. to OSHA HCS

Printing date 11/11/2021

Reviewed on 11/11/2021

(Contd. of page 11)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

* 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

7779-90-0	trizinc bis(orthophosphate)
95-63-6	1,2,4-trimethylbenzene
7727-43-7	barium sulphate, natural
108-10-1	4-methylpentan-2-one
100-41-4	ethylbenzene
95-47-6	o-xylene
106-42-3	p-xylene
108-38-3	m-xylene
1330-20-7	xylene

(Contd. on page 13)

USA



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/11/2021

Reviewed on 11/11/2021

(Contd. of page 12)

136-52-7	cobalt(II) 2-ethylhexanoate
112-34-5	2-(2-butoxyethoxy)ethanol
122-99-6	2-Phenoxyethanol
7664-38-2	phosphoric acid

· **TSCA (Toxic Substances Control Act):**
All components have the value ACTIVE.

· **Hazardous Air Pollutants**

108-10-1	4-methylpentan-2-one
100-41-4	ethylbenzene
95-47-6	o-xylene
106-42-3	p-xylene
108-38-3	m-xylene
1330-20-7	xylene
136-52-7	cobalt(II) 2-ethylhexanoate

· **Proposition 65**

· **Chemicals known to cause cancer:**

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene
13463-67-7	titanium dioxide
108-10-1	4-methylpentan-2-one
100-41-4	ethylbenzene
1333-86-4	Carbon black

· **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**
108-10-1 4-methylpentan-2-one

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

7779-90-0	trizinc bis(orthophosphate)	D, I, II
95-63-6	1,2,4-trimethylbenzene	II
7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
108-10-1	4-methylpentan-2-one	I
100-41-4	ethylbenzene	D
95-47-6	o-xylene	I
106-42-3	p-xylene	I
108-38-3	m-xylene	I
1330-20-7	xylene	I

· **TLV (Threshold Limit Value)**

14807-96-6	Talc (Mg3H2(SiO3)4)	A4
13463-67-7	titanium dioxide	A4
100-41-4	ethylbenzene	A3
95-47-6	o-xylene	A4

(Contd. on page 14)



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/11/2021

Reviewed on 11/11/2021

(Contd. of page 13)

106-42-3	<i>p</i> -xylene	A4
108-38-3	<i>m</i> -xylene	A4
1333-86-4	Carbon black	A4
1330-20-7	xylene	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

4-chloro-alpha, alpha, alpha-trifluorotoluene
Solvent naphtha (petroleum), light arom.
Stoddard solvent
titanium dioxide
2-butanone oxime

· **Hazard statements**

Highly flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.

(Contd. on page 15)

USA

**Safety Data Sheet**
acc. to OSHA HCS

Printing date 11/11/2021

Reviewed on 11/11/2021

(Contd. of page 14)

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Product Safety Dept.

· **Date of preparation / last revision** 11/11/2021 / 1

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity – Category 1B

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

USA