



Product Features & Application

High Teck Products
 PO Box 24631
 West Palm Beach, FL 33416
 1-877-900-8325



- Product: HIT 9274 Professional Seam Sealer (White)
- Product: HIT 9275 Professional Seam Sealer (Black)



Touch Dry 10-40 min

Product Description: High Teck™ Professional Seam Sealer is a fast acting seam and joint sealer. With a quick 30 minute drying time, it maintains flexibility and withstands oxidation, salt water, gas, and other solvents.

Features:

- 🔥 High rubber content
- 🔥 Cures to a tough rubber
- 🔥 Highly elastic with very little shrinkage
- 🔥 Low and high temperature flexibility
- 🔥 Fast drying
- 🔥 Non sagging
- 🔥 Paintable in 30-40 minutes
- 🔥 Serviceable Temperatures from -20F to 160F
- 🔥 Water Resistant

Physical Properties

- Color: White, Black
- Consistency: Non Sag
- Solids: 75% - 95%
- Tensile Strength: 800 psi
- Elongation: Excell of 300%
- Modulus:100: 140 psi
- Weight per Gallon: 1 pound

Application Instructions

- 🔥 Use for channel glazing, porcelain panel construction, sealing and bedding applications subject to racking and distortions on automobile, trucks, trailers, buses, boats and trailer bodies
- 🔥 Tent Patching
- 🔥 Bathtub Caulk
- 🔥 Quarry tile and masonry joints, decks, etc.

Surface Preparation

- 🔥 Surface should be clean and grease/oil free

Application Instructions

- 🔥 Cut cartridge nozzle to desired bead size and caulk
- 🔥 Touch dry and paintable in 10-40 minutes.
- 🔥 Full cure in 24 hours or more.

Note: Avoid applying any materials on or near catalytic converters or mufflers due to extreme heat. In the event the SDS (Safety Data Sheet) on this product is not in your files, you can request one from High Teck Products Regulatory Compliance at 1-877-900-8325 and/or email: info@highteckproducts.com.

