



### Description

#### 9972 - PERFORMANCE GUIDE COAT

High Teck's 9972 Performance Guide Coat is a fast-drying coating that helps quickly identify high/low areas on primed surfaces, offering an ultra-smooth finish. Simply apply a light coat over a primed area. Finish sand with a block or pad, revealing high spots and depressions in the surface, until the guide coat is removed.



### Suggested Uses

Automotive Body Panels  
Fiberglass  
Wood



### Dry Times at 72° F

To Touch: 5 MINUTES  
To Topcoat: 15 MINUTES  
Humidity: 50%  
Thickness: 0.3 MIL



### Technical Data

Coverage:	Up to 15 square feet
Cleanup:	Paint/lacquer thinner
Flammability:	Extremely Flammable
Flash point:	-4° F
Specific Gravity:	0.85
MIR Value:	0.82, does not exceed 0.95
Solids Content:	7%
HAPs Content:	9%
Storage Temperature:	40° - 100° F
Application Temperature:	50° - 90° F
Abrasion Resistance:	Fair
Heat Resistance:	250° F continuous
Resin System:	Acrylic lacquer
Shelf Life:	Guaranteed for 2 years
Gloss:	Flat, <15 (as measured on a 60 degree gloss meter)

**SEE SDS AND PRODUCT LABELS FOR ADDITIONAL SAFETY INFORMATION.**

**NOTE:** High Teck products are not recommended for use in temperatures below 65°F. Using High Teck products below these temperatures will effect dry times and product performance characteristics.