3904 BLENDING REDUCER AEROSOL VERSION: 2.0

# **TECHNICAL DATA SHEET & PROCESS GUIDE**

A specially formulated blend of solvents for fast and effective blending of clearcoats. Produce seamless transitions on blend panels of clearcoats and solid colors for a virtually invisible repair. Ultra fine, soft spray generates immediate results. Ideal for both single and multi-panel repairs.

- · Invisible blend finish
- · For use with all coatings
- Convenient aerosol application means no waste, less mess, no clean-up and no gun required.
- · Reduces polishing time.

# **APPLICATION GUIDE**

# Mixing

Shake the aerosol can for at least 2 minutes before use.

### **Application**

- Sand the blend area with sanding soap or 1500 3000 grit sandpaper to prepare the clearcoat area.
- Holding the aerosol approximately 10" from the panel, apply a light mist coat over the blend area of the freshly applied clearcoat or topcoat.
- Apply 2-3 light coats of High Teck 3904 immediately after clearcoat is applied to blend edge.
- · Follow the clearcoat or topcoat manufacturer's instructions for flash-off and drying.



## STORAGE & VOC INFORMATION

## **Shelf Life**

2 years subject to proper storage conditions.

Aerosol cans should be stored for two hours at room temperature before use. For long-term storage, keep in a dry, well-ventilated area away from direct sunlight and frost. To maximize the lifespan of your aerosol, always invert the can and spray it upside down for a few seconds after each use to clear the nozzle. Remove the nozzle from the can and soak it in gentle thinners if the nozzle becomes blocked.

Recommended Storage Temperature 41°F - 77°F Recommended Application Temperature 68°F

### **VOC Information**

Order Code	Format	Color	MIR
HIT.3904	450ml Aerosol	Clear	N/A

### IMPORTANT: Read full instructions before use.

High Teck Tip: For excellent clearcoat, edge blend with any blender. Polish the area well beyond and into where your clearcoat will stop. Then clean with a wax & grease remover before prepping the area 1500-3000 sandpaper.

## **EMERGENCY TELEPHONE:**

800 424-9300 (Chemtrec)

## IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.

EMERGENCY TELEPHONE: (877) 900-8325, PO BOX 24631, West Palm Beach, FL 33416. info@highteckproducts.com.

This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information. High Teck disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local distributor or via the High Teck website at **www.highteck.com** is not responsible for the results obtained by others over whose methods we have no control and thereof High Teck is not liable for consequential or incidental damages including loss of profits.