



7801V Final Wipeout Wax & Grease Remover is a water-based very low VOC anti-static panel wipe. It is a vital final step before undertaking any painting and sanding operation in order to remove contaminants such as wax, grease, oil, dust, residues or silicones.

DESCRIPTION

7801V – FINAL WIPEOUT LOW VOC WAX & GREASE REMOVER

SURFACE PREPARATION / APPLICATION

- 1) Always shake container before use.
- 2) Using a clean, lint-free cloth, apply generous amount of 7801V to the area to be sanded or coated.
- 3) Allow some time for the solvents to act and dissolve any surface residues.
- 4) While the panel remains wet, wipe with a clean dry cloth until the wax & grease remover has been completely removed.
- 5) If any surface impurities remain, repeat steps 1-4.

OTHER INFORMATION

Final Wipeout Wax & Grease Remover may be diluted up to 100% with water.

7801V is safe to use on all substrates, especially solvent sensitive plastics.

7801V offers excellent anti-static properties that enable the effective removal of surface static build-up.

TECHNICAL DATA

Final Wipeout Wax & Grease Remover: 7801V

V.O.C.

0.2 lbs/gal

FOR INDUSTRY USE ONLY Read MSDS Before Use

Before opening the packages, read all warning labels. Follow all precautions. The material is designed for application only by professionally trained personnel using proper equipment under controlled conditions, and is not intended for sale to the general public
SEE MSDS AND PRODUCT LABELS FOR ADDITIONAL SAFETY INFORMATION

