

## HIGH GLOSS UNIVERSAL CLEAR COAT (4:1)

Description	High Teck European E9000 High Gloss Universal Clear is a high gloss, fast drying clear for overall, spot and panel refinishing.
Health and Safety Statement	<b>FOR PROFESSIONAL USE ONLY</b> . Read full instructions before use. IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist. The supplier disclaims any liability where the user does not wear the recommended personal protective equipment.
Surface preparation	Step 1: Degrease with wax & grease remover, allow to dry.Step 2: Abrade the surfaceOriginal cured paint: Wet sand P800-1000 or Dry sand P600-800.Step 3: Degrease with wax and grease remover as per Step 1 above.Step 4: remove all dust/dirt particles with a tack rag.
VOC	Regulatory VOC: 4.9 lbs/gal or 585 g/l
Information	Material VOC: 4.0 lbs/gal or 481 g/l

TECHNICAL INFORMATION						
Mixing Ratio:	CLEAR COAT : HARDENER 4:1					
Spray Gun	HVLP Gravity gun					
Spray Gun Tip size	1.3mm to 1.6mm					
Viscosity Zahn #2.	19 - 22 secs					
Air Pressure	28 psi at the gun					
Coats	2 to 3 wet coats					
Film Build	1,000 - 1,500 microns					
Flash Off Time	5 - 10 mins					
Tack Free Time	<20 mins					
Through Dry Time (Air)	4 - 6 hours					
Through Dry Time (@ 140°F)	30 mins					
Through Dry Time (I.R.)	15 mins					
Time to Polish	Minimum 5 hours					
Recoat Window	Up to 8 hours then sanding required.					
Tape Time	Overnight					
Pot-Life	6 - 8 hours					
Mixed Solids	33%					

TEMPERATURE RANGE FOR HARDENERS								
Temp °F	<b>50</b> °	60°	<b>70</b> °	<b>80</b> °	90°	<b>100°</b>		
Hardener Speed:								
FAST - 2000								
<b>MEDIUM - 2100</b>								
SLOW - 2200								
EXTRA SLOW - 2300								

WEST PALM BEACH, FL 33413