



## Safety Data Sheet acc. to OSHA HCS

Printing date 08/26/2015

Reviewed on 08/13/2015

### 1 Identification

- **Product identifier**
- **Trade name: 2.1 VOC Multi-Purpose Clearcoat Activator - MEDIUM**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
**High Teck Products**
- **P.O. Box 24631**
- **West Palm Beach, FL. 33416**  
**USA**
- **Information department: Product safety department**
- **Emergency telephone number: CHEMTREC 800-424-9300**

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**  
*poly(hexamethylene diisocyanate)*  
*3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate*

(Contd. on page 2)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2015

Reviewed on 08/13/2015

**Trade name: 2.1 VOC Multi-Purpose Clearcoat Activator - MEDIUM**

(Contd. of page 1)

**· Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

**· Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear respiratory protection.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Wear protective gloves.

Wear eye protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

**IF ON SKIN (or hair):** Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

**If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

**If experiencing respiratory symptoms:** Call a poison center/doctor.

Wash contaminated clothing before reuse.

**If inhaled:** If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

**If skin irritation or rash occurs:** Get medical advice/attention.

**If eye irritation persists:** Get medical advice/attention.

**In case of fire:** Use for extinction: CO<sub>2</sub>, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Classification system:****· NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

**· HMIS-ratings (scale 0 - 4)**

Health = \*1

Fire = 3

Reactivity = 0

(Contd. on page 3)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2015

Reviewed on 08/13/2015

**Trade name: 2.1 VOC Multi-Purpose Clearcoat Activator - MEDIUM**

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

28182-81-2	poly(hexamethylene diisocyanate)	25-50%
98-56-6	4-chloro-alpha, alpha, alpha-trifluorotoluene	25-50%
4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	2.5-10%
79-20-9	methyl acetate	2.5-10%
123-86-4	n-butyl acetate	2.5-10%
110-43-0	heptan-2-one	≤ 2.5%
108-65-6	2-methoxy-1-methylethyl acetate	≤ 2.5%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Remove breathing apparatus only after contaminated clothing have been completely removed.  
In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**  
Supply fresh air or oxygen; call for doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet

(Contd. on page 4)



## Safety Data Sheet acc. to OSHA HCS

Printing date 08/26/2015

Reviewed on 08/13/2015

**Trade name: 2.1 VOC Multi-Purpose Clearcoat Activator - MEDIUM**

(Contd. of page 3)

- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

US

(Contd. on page 5)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/26/2015

Reviewed on 08/13/2015

**Trade name: 2.1 VOC Multi-Purpose Clearcoat Activator - MEDIUM**

(Contd. of page 4)

**8 Exposure controls/personal protection**

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate**

REL Short-term value: 0.18 mg/m<sup>3</sup>, 0.02 ppm  
Long-term value: 0.045 mg/m<sup>3</sup>, 0.005 ppm  
Skin

TLV Long-term value: 0.045 mg/m<sup>3</sup>, 0.005 ppm

**79-20-9 methyl acetate**

PEL Long-term value: 610 mg/m<sup>3</sup>, 200 ppm

REL Short-term value: 760 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 610 mg/m<sup>3</sup>, 200 ppm

TLV Short-term value: 757 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 606 mg/m<sup>3</sup>, 200 ppm

**123-86-4 n-butyl acetate**

PEL Long-term value: 710 mg/m<sup>3</sup>, 150 ppm

REL Short-term value: 950 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 710 mg/m<sup>3</sup>, 150 ppm

TLV Short-term value: 950 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 713 mg/m<sup>3</sup>, 150 ppm

**110-43-0 heptan-2-one**

PEL Long-term value: 465 mg/m<sup>3</sup>, 100 ppm

REL Long-term value: 465 mg/m<sup>3</sup>, 100 ppm

TLV Long-term value: 233 mg/m<sup>3</sup>, 50 ppm

**108-65-6 2-methoxy-1-methylethyl acetate**

WEEL Long-term value: 50 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)



### Safety Data Sheet acc. to OSHA HCS

Printing date 08/26/2015

Reviewed on 08/13/2015

**Trade name: 2.1 VOC Multi-Purpose Clearcoat Activator - MEDIUM**

(Contd. of page 5)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	Clear
Odor:	Characteristic
Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	57 °C (135 °F)

· **Flash point:** -10 °C (14 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 430 °C (806 °F)

· **Decomposition temperature:** Not determined.

(Contd. on page 7)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2015

Reviewed on 08/13/2015

**Trade name: 2.1 VOC Multi-Purpose Clearcoat Activator - MEDIUM**

(Contd. of page 6)

· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
· <b>Vapor pressure:</b>	Not determined.
· <b>Density at 20 °C (68 °F):</b>	1.17803 g/cm <sup>3</sup> (9.831 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	13.0 %
<b>VOC content:</b>	7.2 %
	Coating VOC 125.32 g/l / 1.04 lb/gl
	Material VOC 84.8 g/l / 0.71 lb/gl
<b>Solids content:</b>	50.2 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. on page 8)





## Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2015

Reviewed on 08/13/2015

Trade name: 2.1 VOC Multi-Purpose Clearcoat Activator - MEDIUM

(Contd. of page 7)

### 11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:**

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Harmful

Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

(Contd. on page 9)



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/26/2015

Reviewed on 08/13/2015

**Trade name: 2.1 VOC Multi-Purpose Clearcoat Activator - MEDIUM**

(Contd. of page 8)

· **Other adverse effects** No further relevant information available.**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- |                                       |                            |
|---------------------------------------|----------------------------|
| · <b>UN-Number</b>                    |                            |
| · <b>DOT, IMDG, IATA</b>              | UN1263                     |
| · <b>UN proper shipping name</b>      |                            |
| · <b>DOT</b>                          | Paint                      |
| · <b>IMDG, IATA</b>                   | PAINT                      |
| · <b>Transport hazard class(es)</b>   |                            |
| · <b>DOT</b>                          |                            |
|                                       |                            |
| · <b>Class</b>                        | 3 Flammable liquids        |
| · <b>Label</b>                        | 3                          |
| · <b>IMDG, IATA</b>                   |                            |
|                                       |                            |
| · <b>Class</b>                        | 3 Flammable liquids        |
| · <b>Label</b>                        | 3                          |
| · <b>Packing group</b>                |                            |
| · <b>DOT, IMDG, IATA</b>              | II                         |
| · <b>Environmental hazards:</b>       |                            |
| · <b>Marine pollutant:</b>            | No                         |
| · <b>Special precautions for user</b> | Warning: Flammable liquids |
| · <b>Danger code (Kemler):</b>        | 33                         |

(Contd. on page 10)



### Safety Data Sheet acc. to OSHA HCS

Printing date 08/26/2015

Reviewed on 08/13/2015

**Trade name: 2.1 VOC Multi-Purpose Clearcoat Activator - MEDIUM**

(Contd. of page 9)

· <b>EMS Number:</b>	<i>F-E,S-E</i>
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	<i>Not applicable.</i>
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	<i>On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L</i>
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	<i>1L</i>
· <b>Excepted quantities (EQ)</b>	<i>Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml</i>
· <b>UN "Model Regulation":</b>	<i>UN1263, Paint, 3, II</i>

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

4098-71-9 | 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

· **Section 313 (Specific toxic chemical listings):**

4098-71-9 | 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

· **TSCA (Toxic Substances Control Act):**

*All ingredients are listed.*

· **Proposition 65**

· **Chemicals known to cause cancer:**

*None of the ingredients is listed.*

· **Chemicals known to cause reproductive toxicity for females:**

*None of the ingredients is listed.*

· **Chemicals known to cause reproductive toxicity for males:**

*None of the ingredients is listed.*

· **Chemicals known to cause developmental toxicity:**

*None of the ingredients is listed.*

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

*None of the ingredients is listed.*

(Contd. on page 11)



### Safety Data Sheet acc. to OSHA HCS

Printing date 08/26/2015

Reviewed on 08/13/2015

**Trade name: 2.1 VOC Multi-Purpose Clearcoat Activator - MEDIUM**

(Contd. of page 10)

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*poly(hexamethylene diisocyanate)*

*3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate*

· **Hazard statements**

*Highly flammable liquid and vapor.*

*Causes skin irritation.*

*Causes serious eye irritation.*

*May cause allergy or asthma symptoms or breathing difficulties if inhaled.*

*May cause an allergic skin reaction.*

· **Precautionary statements**

*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

*Use explosion-proof electrical/ventilating/lighting/equipment.*

*Wear respiratory protection.*

*Avoid breathing dust/fume/gas/mist/vapors/spray*

*Wear protective gloves / eye protection / face protection.*

*Wear protective gloves.*

*Wear eye protection / face protection.*

*Ground/bond container and receiving equipment.*

*Keep container tightly closed.*

*Use only non-sparking tools.*

*Take precautionary measures against static discharge.*

*Wash thoroughly after handling.*

*Contaminated work clothing must not be allowed out of the workplace.*

*IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*

*Continue rinsing.*

*Specific treatment (see on this label).*

*If experiencing respiratory symptoms: Call a poison center/doctor.*

*Wash contaminated clothing before reuse.*

*If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.*

*If skin irritation or rash occurs: Get medical advice/attention.*

*If eye irritation persists: Get medical advice/attention.*

(Contd. on page 12)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2015

Reviewed on 08/13/2015

**Trade name: 2.1 VOC Multi-Purpose Clearcoat Activator - MEDIUM**

(Contd. of page 11)

*In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.*

*Take off contaminated clothing and wash it before reuse.*

*Store in a well-ventilated place. Keep cool.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** Environment protection department.

· **Contact:** Mr. Roberts

· **Date of preparation / last revision** 08/26/2015 / -

· **Abbreviations and acronyms:**

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*Flam. Liq. 2: Flammable liquids, Hazard Category 2*

*Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2*

*Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A*

*Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1*

*Skin Sens. 1: Sensitisation - Skin, Hazard Category 1*