



# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Date of issue: 13/03/2015

Revision date:

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Premium Polyester Finishing Putty 4160  
Product group : Bodyfiller

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial  
For professional use only  
Function or use category : Fillers

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

HIGH TECK PRODUCTS  
PO BOX 24631  
WEST PALM BEACH, FLORIDA  
33416 - USA  
T 877-900-8325  
[info@nationaloak.com](mailto:info@nationaloak.com)

#### 1.4. Emergency telephone number

Emergency number : (800) 424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226  
Skin Irrit. 2 H315  
Eye Irrit. 2 H319  
Repr. 2 H361  
STOT RE 1 H372

Full text of H-phrases: see section 16

##### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

R10

Full text of R-phrases: see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) : Danger  
Hazardous ingredients : styrene  
Hazard statements (CLP) : H226 - Flammable liquid and vapour  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H361 - Suspected of damaging fertility or the unborn child  
H372 - Causes damage to organs through prolonged or repeated exposure  
Precautionary statements (CLP) : P202 - Do not handle until all safety precautions have been read and understood  
P263 - Avoid contact during pregnancy/while nursing

# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

P264 - Wash hands thoroughly after handling  
P280 - Wear eye protection, protective clothing, protective gloves  
P302+P352 - IF ON SKIN: Wash with plenty of water  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

No labelling applicable

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
styrene	(CAS No) 100-42-5 (EC no) 202-851-5	5 - 23	Repr.Cat.3; R63 Xn; R20 Xn; R48/20 Xi; R36/38 R10
xylene substance with a Community workplace exposure limit	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9	< 5	R10 Xn; R20/21 Xi; R38
ethylbenzene substance with a Community workplace exposure limit	(CAS No) 100-41-4 (EC no) 202-849-4 (EC index no) 601-023-00-4	< 5	F; R11 Xn; R20

Name	Product identifier	Specific concentration limits
xylene	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9	(C >= 12.5) Xn;R20/21

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
styrene	(CAS No) 100-42-5 (EC no) 202-851-5	5 - 23	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT RE 1, H372
xylene substance with a Community workplace exposure limit	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9	< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
ethylbenzene substance with a Community workplace exposure limit	(CAS No) 100-41-4 (EC no) 202-849-4 (EC index no) 601-023-00-4	< 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of R- and H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Allow breathing of fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	---

#### 6.1.1. For non-emergency personnel

Protective equipment	: Safety glasses. Protective clothing. Gloves.
Emergency procedures	: Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment	: Contain leaking substance. Collect spillage.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust, fume.
Hygiene measures	: Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, Lighting equipment equipment.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Ignition sources, Heat sources, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.
Storage temperature	: < 25 °C
Storage area	: Store in a well-ventilated place.

# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Special rules on packaging

: Keep only in original container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

styrene (100-42-5)		
Austria	Local name	Styrol
Austria	MAK (mg/m <sup>3</sup> )	85 mg/m <sup>3</sup>
Austria	MAK (ppm)	20 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	340 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	80 ppm
Belgium	Local name	Styrène (monomère)
Belgium	Limit value (mg/m <sup>3</sup> )	216 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	432 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	100 ppm
Belgium	Remark (BE)	D
Bulgaria	Local name	Стирен
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	85 mg/m <sup>3</sup>
Bulgaria	OEL STEL (mg/m <sup>3</sup> )	215 mg/m <sup>3</sup>
Croatia	Local name	Stiren
Croatia	GVI (granična vrijednost izloženosti) (mg/m <sup>3</sup> )	430 mg/m <sup>3</sup>
Croatia	GVI (granična vrijednost izloženosti) (ppm)	100 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m <sup>3</sup> )	1080 mg/m <sup>3</sup>
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	250 ppm
Croatia	Naznake (HR)	Xn
Czech Republic	Local name	Styren
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (PEL) (ppm)	24 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	400 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (NPK-P) (ppm)	90 ppm
Czech Republic	Remark (CZ)	D
Denmark	Local name	Styren (1994)
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	105 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	25 ppm
Denmark	Anmærkninger (DK)	LHK
Estonia	Local name	Stüreen (fenüületeen, vinüülbenseen)
Estonia	OEL TWA (mg/m <sup>3</sup> )	90 mg/m <sup>3</sup>
Estonia	OEL TWA (ppm)	20 ppm
Estonia	OEL STEL (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Estonia	OEL STEL (ppm)	50 ppm
Finland	Local name	Styreeni
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	86 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	20 ppm
Finland	HTP-arvo (15 min)	430 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	100 ppm
France	Local name	Styrène
France	VME (mg/m <sup>3</sup> )	215 mg/m <sup>3</sup>
France	VME (ppm)	50 ppm
Germany	Local name	Styrol
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	86 mg/m <sup>3</sup>
Germany	TRGS 900 Occupational exposure limit value (ppm)	20 ppm

# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

styrene (100-42-5)		
Germany	Remark (TRGS 900)	DFG, Y
Greece	OEL TWA (mg/m <sup>3</sup> )	425 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	100 ppm
Greece	OEL STEL (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup>
Greece	OEL STEL (ppm)	250 ppm
Ireland	Local name	Styrene
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	85 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	20 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	170 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (ppm)	40 ppm
Lithuania	Local name	Stirenas (stirolas)
Lithuania	IPRV (mg/m <sup>3</sup> )	90 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	20 ppm
Lithuania	TPRV (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Lithuania	TPRV (ppm)	50 ppm
Lithuania	Remark (LT)	O
Poland	Local name	Styren
Poland	NDS (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Poland	NDSCh (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Portugal	Local name	Estireno, monómero
Portugal	OEL TWA (ppm)	20 ppm
Portugal	OEL STEL (ppm)	40 ppm
Romania	Local name	Stiren (monomer feniletilen)
Romania	OEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Romania	OEL TWA (ppm)	12 ppm
Romania	OEL STEL (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>
Romania	OEL STEL (ppm)	35 ppm
Slovenia	Local name	stiren
Slovenia	OEL TWA (mg/m <sup>3</sup> )	86 mg/m <sup>3</sup>
Slovenia	OEL TWA (ppm)	20 ppm
Slovenia	OEL STEL (mg/m <sup>3</sup> )	344 mg/m <sup>3</sup>
Slovenia	OEL STEL (ppm)	80 ppm
Sweden	Local name	Styrene
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	90 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	20 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	50 ppm
United Kingdom	Local name	Styrene
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	430 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	100 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	1080 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	250 ppm
Norway	Local name	Styren
Norway	Gjennomsnittsverdier (AN) (mg/m <sup>3</sup> )	105 mg/m <sup>3</sup>
Norway	Gjennomsnittsverdier (AN) (ppm)	25 ppm
Norway	Merknader (NO)	M
Switzerland	Local name	Styrène
Switzerland	VME (mg/m <sup>3</sup> )	85 mg/m <sup>3</sup>
Switzerland	VME (ppm)	20 ppm
Switzerland	VLE (mg/m <sup>3</sup> )	170 mg/m <sup>3</sup>
Switzerland	VLE (ppm)	40 ppm
Switzerland	Remark (CH)	4x15

# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

styrene (100-42-5)		
Australia	Local name	Styrene, monomer
Australia	TWA (mg/m <sup>3</sup> )	213 mg/m <sup>3</sup>
Australia	TWA (ppm)	50 ppm
Australia	STEL (mg/m <sup>3</sup> )	426 mg/m <sup>3</sup>
Australia	STEL (ppm)	100 ppm
USA - ACGIH	Local name	Styrene, monomer
USA - ACGIH	ACGIH TWA (ppm)	20 ppm
USA - ACGIH	ACGIH STEL (ppm)	40 ppm
USA - ACGIH	Remark (ACGIH)	CNS impair; URT irr; peripheral
USA - OSHA	Local name	Styrene
USA - OSHA	Remark (OSHA)	(2) See Table Z-2.
ethylbenzene (100-41-4)		
EU	Local name	Ethylbenzene
EU	IOELV TWA (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	200 ppm
EU	Notes	Skin
Austria	Local name	Ethylbenzol
Austria	MAK (mg/m <sup>3</sup> )	440 mg/m <sup>3</sup>
Austria	MAK (ppm)	100 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	880 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	200 ppm
Austria	Remark (AT)	H
Belgium	Local name	Ethylbenzène
Belgium	Limit value (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	100 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	551 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	125 ppm
Belgium	Remark (BE)	D
Bulgaria	Local name	Етилбензен•
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
Bulgaria	OEL STEL (mg/m <sup>3</sup> )	545 mg/m <sup>3</sup>
Croatia	Local name	Etilbenzen
Croatia	GVI (granična vrijednost izloženosti) (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Croatia	GVI (granična vrijednost izloženosti) (ppm)	100 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	200 ppm
Croatia	Naznake (HR)	K EU*, F, Xn
Czech Republic	Local name	Ethylbenzen
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (PEL) (ppm)	50 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (NPK-P) (ppm)	120 ppm
Czech Republic	Remark (CZ)	D
Denmark	Local name	Ethylbenzen
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	217 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	50 ppm
Denmark	Anmærkninger (DK)	EK
Estonia	Local name	Etüülbenseen
Estonia	OEL TWA (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Estonia	OEL TWA (ppm)	100 ppm
Estonia	OEL STEL (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>

# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

ethylbenzene (100-41-4)		
Estonia	OEL STEL (ppm)	200 ppm
Finland	Local name	Etyylibentseeni
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	220 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	880 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	200 ppm
Germany	Local name	Ethylbenzol
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	88 mg/m <sup>3</sup>
Germany	TRGS 900 Occupational exposure limit value (ppm)	20 ppm
Germany	Remark (TRGS 900)	EU,H,13
Greece	OEL TWA (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	100 ppm
Greece	OEL STEL (mg/m <sup>3</sup> )	545 mg/m <sup>3</sup>
Greece	OEL STEL (ppm)	125 ppm
Hungary	Local name	ETILBENZOL
Hungary	AK-érték	442 mg/m <sup>3</sup>
Hungary	CK-érték	884 mg/m <sup>3</sup>
Hungary	Megjegyzések (HU)	b, i; l.
Ireland	Local name	Ethylbenzene
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	100 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (ppm)	200 ppm
Ireland	Notes (IE)	Sk, IOELV
Italy	Local name	Etilbenzene
Italy	OEL TWA (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Italy	OEL TWA (ppm)	100 ppm
Italy	OEL STEL (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
Italy	OEL STEL (ppm)	200 ppm
Lithuania	Local name	Etilbenzenas
Lithuania	IPRV (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	100 ppm
Lithuania	TPRV (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
Lithuania	TPRV (ppm)	200 ppm
Lithuania	Remark (LT)	O
Luxembourg	Local name	Ethylbenzène
Luxembourg	OEL TWA (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Luxembourg	OEL TWA (ppm)	100 ppm
Luxembourg	OEL STEL (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
Luxembourg	OEL STEL (ppm)	200 ppm
Malta	Local name	Ethylbenzene
Malta	OEL TWA (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Malta	OEL TWA (ppm)	100 ppm
Malta	OEL STEL (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
Malta	OEL STEL (ppm)	200 ppm
Netherlands	Local name	Ethylbenzeen
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	215 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	430 mg/m <sup>3</sup>
Netherlands	Remark (MAC)	H
Poland	Local name	Etylobenzen

# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

ethylbenzene (100-41-4)		
Poland	NDS (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	400 mg/m <sup>3</sup>
Portugal	Local name	Etilbenzeno
Portugal	OEL TWA (ppm)	100 ppm
Portugal	OEL STEL (ppm)	125 ppm
Romania	Local name	Etilbenzen
Romania	OEL TWA (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Romania	OEL TWA (ppm)	100 ppm
Romania	OEL STEL (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
Romania	OEL STEL (ppm)	200 ppm
Slovenia	Local name	etilbenzen
Slovenia	OEL TWA (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Slovenia	OEL TWA (ppm)	100 ppm
Slovenia	OEL STEL (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
Slovenia	OEL STEL (ppm)	200 ppm
Sweden	Local name	Ethylbenzene
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	450 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	100 ppm
United Kingdom	Local name	Ethylbenzene
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	441 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	100 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	552 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	125 ppm
United Kingdom	Remark (WEL)	Sk
Iceland	Local name	Etylbensen
Iceland	OEL (8 hours ref) (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Iceland	OEL (8 hours ref) (ppm)	50 ppm
Iceland	OEL (15 min ref) (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
Iceland	OEL (15 min ref) (ppm)	200 ppm
Iceland	Notes (IS)	H
Norway	Local name	Etylbenzen
Norway	Gjennomsnittsverdier (AN) (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Norway	Gjennomsnittsverdier (AN) (ppm)	5 ppm
Norway	Merknader (NO)	H K
Switzerland	Local name	Ethylbenzène
Switzerland	VME (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
Switzerland	VME (ppm)	100 ppm
Switzerland	VLE (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
Switzerland	VLE (ppm)	100 ppm
Switzerland	Remark (CH)	15 min
Australia	Local name	Ethyl benzene
Australia	TWA (mg/m <sup>3</sup> )	434 mg/m <sup>3</sup>
Australia	TWA (ppm)	100 ppm
Australia	STEL (mg/m <sup>3</sup> )	543 mg/m <sup>3</sup>
Australia	STEL (ppm)	125 ppm
USA - ACGIH	Local name	Ethyl benzene
USA - ACGIH	ACGIH TWA (ppm)	20 ppm
USA - ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
USA - OSHA	Local name	Ethyl benzene
USA - OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
USA - OSHA	OSHA PEL (TWA) (ppm)	100 ppm



# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

xylene (1330-20-7)		
EU	Local name	Xylene, mixed isomers, pure
EU	IOELV TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
Austria	Local name	Xylol (alle Isomeren)
Austria	MAK (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Austria	MAK (ppm)	50 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	100 ppm
Austria	Remark (AT)	H
Belgium	Local name	Xylène, isomères mixtes, purs
Belgium	Limit value (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	100 ppm
Belgium	Remark (BE)	D
Bulgaria	Local name	Ксилен (смес от изомери),чист*
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Bulgaria	OEL STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Croatia	Local name	Ksilen (svi izomeri)
Croatia	GVI (granična vrijednost izloženosti) (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Croatia	GVI (granična vrijednost izloženosti) (ppm)	50 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	100 ppm
Croatia	Naznake (HR)	K, EU* K, Xn
Czech Republic	Local name	Xylen technická sm s isomer a (všechny isomery)
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (PEL) (ppm)	50 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	400 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (NPK-P) (ppm)	90 ppm
Czech Republic	Remark (CZ)	D
Denmark	Local name	Xylen, alle isomere (1996)
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	109 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	25 ppm
Denmark	Anmærkninger (DK)	EH
Estonia	Local name	Ksüleen (dimetüülbenseen)
Estonia	OEL TWA (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Estonia	OEL TWA (ppm)	50 ppm
Estonia	OEL STEL (mg/m <sup>3</sup> )	450 mg/m <sup>3</sup>
Estonia	OEL STEL (ppm)	100 ppm
Finland	Local name	Ksyleeni
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	220 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	440 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	100 ppm
France	Local name	Xylène, isomères mixtes, purs
France	VME (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
France	VME (ppm)	50 ppm
France	VLE (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
France	VLE (ppm)	100 ppm

# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

xylene (1330-20-7)		
Germany	Local name	Xylol(allelsomeren)
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	440 mg/m <sup>3</sup>
Germany	TRGS 900 Occupational exposure limit value (ppm)	100 ppm
Germany	Remark (TRGS 900)	DFG,EU,H
Greece	OEL TWA (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	100 ppm
Greece	OEL STEL (mg/m <sup>3</sup> )	650 mg/m <sup>3</sup>
Greece	OEL STEL (ppm)	150 ppm
Hungary	Local name	XILOL(ok)
Hungary	AK-érték	221 mg/m <sup>3</sup>
Hungary	CK-érték	442 mg/m <sup>3</sup>
Hungary	Megjegyzések (HU)	b; EU1
Ireland	Local name	Xylene, mixed isomers
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (ppm)	100 ppm
Ireland	Notes (IE)	Sk, IOELV
Italy	Local name	Xilene, isomeri misti, puro
Italy	OEL TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Italy	OEL TWA (ppm)	50 ppm
Italy	OEL STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Italy	OEL STEL (ppm)	100 ppm
Lithuania	Local name	Ksilenas
Lithuania	IPRV (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m <sup>3</sup> )	450 mg/m <sup>3</sup>
Lithuania	TPRV (ppm)	100 ppm
Lithuania	Remark (LT)	O
Luxembourg	Local name	Xylène, isomères mixtes, purs
Luxembourg	OEL TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Luxembourg	OEL TWA (ppm)	50 ppm
Luxembourg	OEL STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Luxembourg	OEL STEL (ppm)	100 ppm
Malta	Local name	Xylene,mixed isomers,pure
Malta	OEL TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Malta	OEL TWA (ppm)	50 ppm
Malta	OEL STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Malta	OEL STEL (ppm)	100 ppm
Netherlands	Local name	Xyleen, o-, m-, p-isomeren
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	210 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Netherlands	Remark (MAC)	H
Poland	Local name	Ksylen mieszanina izomerów: 1,2-; 1,3-; 1,4-
Poland	NDS (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
Portugal	Local name	Xileno (isómeros )
Portugal	OEL TWA (ppm)	100 ppm
Portugal	OEL STEL (ppm)	150 ppm
Romania	Local name	Xilen (izomeri)
Romania	OEL TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Romania	OEL TWA (ppm)	50 ppm
Romania	OEL STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>

# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

<b>xylene (1330-20-7)</b>		
Romania	OEL STEL (ppm)	100 ppm
Slovenia	Local name	ksilen (mešane izomere)
Slovenia	OEL TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Slovenia	OEL TWA (ppm)	50 ppm
Slovenia	OEL STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Slovenia	OEL STEL (ppm)	100 ppm
Spain	Local name	Xilenos, mezcla isómeros
Spain	VLA-ED (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	50 ppm
Spain	VLA-EC (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Spain	VLA-EC (ppm)	100 ppm
Spain	Notes	vía dérmica, VLB®, VLI
Sweden	Local name	Xylene
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	450 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	100 ppm
United Kingdom	Local name	Xylene, o-,m-,p- or mixed isomers
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	220 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	441 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	100 ppm
United Kingdom	Remark (WEL)	Sk, BMGV
Norway	Local name	Xylen (alle isomere)
Norway	Gjennomsnittsverdier (AN) (mg/m <sup>3</sup> )	108 mg/m <sup>3</sup>
Norway	Gjennomsnittsverdier (AN) (ppm)	25 ppm
Norway	Merknader (NO)	H
Switzerland	Local name	Xylène (tous les isomères)
Switzerland	VME (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
Switzerland	VME (ppm)	100 ppm
Switzerland	VLE (mg/m <sup>3</sup> )	870 mg/m <sup>3</sup>
Switzerland	VLE (ppm)	200 ppm
Switzerland	Remark (CH)	4x15
USA - ACGIH	Local name	Xylene
USA - ACGIH	ACGIH TWA (ppm)	100 ppm
USA - ACGIH	ACGIH STEL (ppm)	150 ppm
USA - ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
USA - OSHA	Local name	Xylenes (o-, m-, p-isomers)
USA - OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
USA - OSHA	OSHA PEL (TWA) (ppm)	100 ppm

### 8.2. Exposure controls

Personal protective equipment	: Avoid all unnecessary exposure.
Materials for protective clothing	: Impermeable clothing
Hand protection	: Wear protective gloves
Eye protection	: Chemical goggles or safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: Wear appropriate mask
Other information	: Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
----------------	----------

# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Appearance	: Paste.
Colour	: Beige.
Odour	: aromatic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 33 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapour
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.16 - 1.2
Solubility	: insoluble in water. soluble in most organic solvents.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 31000 - 41000 cP
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content : 268 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified Based on available data, the classification criteria are not met
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: Not classified Based on available data, the classification criteria are not met

# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Specific target organ toxicity (repeated exposure)	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified Based on available data, the classification criteria are not met
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

#### 12.1. Toxicity

No additional information available

#### 12.2. Persistence and degradability

##### Premium Polyester Finishing Putty 4160

Persistence and degradability	Not established.
-------------------------------	------------------

#### 12.3. Bioaccumulative potential

##### Premium Polyester Finishing Putty 4160

Bioaccumulative potential	Not established.
---------------------------	------------------

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

Additional information : Avoid release to the environment

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to Remove waste in accordance with local and/or national regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Avoid release to the environment.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

UN-No. (ADR)	: 1866
UN-No. (IMDG)	: 1866
UN-No. (IATA)	: 1866
UN-No. (ADN)	: 1866
UN-No. (RID)	: 1866

#### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: RESIN SOLUTION
Proper Shipping Name (IMDG)	: RESIN SOLUTION
Proper Shipping Name (IATA)	: Resin solution
Proper Shipping Name (ADN)	: RESIN SOLUTION
Proper Shipping Name (RID)	: RESIN SOLUTION
Transport document description (ADR)	: UN 1866 RESIN SOLUTION, 3, III, (D/E)
Transport document description (IMDG)	: UN 1866 RESIN SOLUTION, 3, III

#### 14.3. Transport hazard class(es)

##### ADR

Transport hazard class(es) (ADR)	: 3
Danger labels (ADR)	: 3

# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010



### IMDG

Transport hazard class(es) (IMDG) : 3

Danger labels (IMDG) : 3



### IATA

Transport hazard class(es) (IATA) : 3

Hazard labels (IATA) : 3



### ADN

Transport hazard class(es) (ADN) : 3

Danger labels (ADN) : 3



### RID

Transport hazard class(es) (RID) : 3

Danger labels (RID) : 3



#### 14.4. Packing group

Packing group (ADR) : III

Packing group (IMDG) : III

Packing group (IATA) : III

Packing group (ADN) : III

Packing group (RID) : III

#### 14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

#### 14.6. Special precautions for user

##### 14.6.1. Overland transport

Classification code (ADR) : F1


Special provisions (ADR) : 640E

# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

### 14.6.2. Transport by sea

Special provisions (IMDG)	: 223, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

### 14.6.3. Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

### 14.6.4. Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 64E
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0
Carriage prohibited (ADN)	: No
Not subject to ADN	: No

# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### 14.6.5. Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 640E
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30
Carriage prohibited (RID)	: No

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions  
Contains no substance on the REACH candidate list  
Contains no REACH Annex XIV substances

VOC content : 268 g/l

Seveso Information : This product is subject to the Seveso Directive

#### 15.1.2. National regulations

##### Germany

Water hazard class (WGK) : 3 - severe hazard to waters

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of R-, H- and EUH-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2



# Premium Polyester Finishing Putty 4160

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H361	Suspected of damaging fertility or the unborn child
H361d	Suspected of damaging the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
R10	Flammable
R11	Highly flammable
R20	Harmful by inhalation
R20/21	Harmful by inhalation and in contact with skin
R36/38	Irritating to eyes and skin
R38	Irritating to skin
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R63	Possible risk of harm to the unborn child
F	Highly flammable
Xi	Irritant
Xn	Harmful

*The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.*